



# Vehicle Service Equipment Buyer's Guide

Fluid Handling Equipment for Industrial and Commercial Applications







Construction | Fleets and Transportation | Industrial | Mining | Energy | Agriculture

# **Table of Contents**

Page	Page
<b>About Graco</b> 4-6	<b>▶</b> Diesel Exhaust Fluid (DEF) Systems
Graco Resources6	How to Choose Your Graco DEF Solution
► Fluid Management Systems	LD Blue Electric Pumps and Packages
	SD Blue AODD Pumps and Packages
Fluid Management System Selection Guide	LD Blue Manual Pumps
Steps to Build Your Pulse Pro System	DEF Meters
Pulse Hub	DEF Dispense Nozzles
Pulse Dispense Meter	DEF Hose Reels         174           DEF System Accessories         175-179
Pulse Tank Level Monitor (TLM)	
Pulse Pump Air Control (PAC)	Specialty Pumps
Pulse Packages and Accessories	Diaphragm Pump Selector182
Steps to Build Your Pulse FC System	Husky 1050 AODD Pump
Pulse FC Software21	Husky 307 AODD Pump
Pulse FC Starter Kit22	Husky 515 AODD Pump
SD™ Preset Dispense Meters	Husky 716 AODD Pump.       187         Husky 1590 AODD Pump.       188
Pulse FC Packages and Accessories	Husky 2150 AODD Pump
·	Husky 3300 AODD Pump
Oil Pumps	Diaphragm Pump Packages
Oil Pump Selection Guide       28-29         LD Series™ Oil Pumps       30-45	Diaphragm Pump Accessories
LD Series ™ Oil Pump Accessories	Undercoating and Rustproofing Pumps
Mini Fire-Ball® 225 Oil Pumps	Undercoating and Rustproofing Pump Packages 197-198
Fire-Ball® 300 Oil Pumps	Undercoating and Rustproofing Accessories
Fire-Ball® 425 Oil Pumps	Bulldog <sup>®</sup> 43:1 Oil Pump
Fast-Ball <sup>®</sup> Oil Pumps	Fast-Flo® 1:1 Pumps
NXT <sup>™</sup> High-Flo® Oil Pumps	Fast-Flo 1:1 Pump Accessories
NXT Dura-Flo® Oil Pumps	APEX™ and APEX On-Demand
Dyna-Star® Hydraulic Oil Pumps	Piston Hand Pumps210
Power-Star™ Hydraulic Oil Pumps	► Hose and Cord Reels
Manually Operated Oil Pumps 80-81	Hose Reel Selection Guide
Oil Meters	LD <sup>™</sup> Series Enclosed Hose Reels
Graco Dispense Meters	SD™ Series Hose Reels
LDP5 Electronic Preset Meters	SD <sup>™</sup> Series Cord and Light Reels
EM® Series Electronic Meters	XD Series 10/20 Hose Reels
IM5 In-Line Electronic Meter	XD Series 30 Hose Reels
IM20 In-Line Electronic Meter	XD <sup>™</sup> Series 60/70/80 Powered Hose Reels
SDI15 In-Line Electronic Meter	
Mechanical Meters	Fluid Reclaim Equipment
SDV15 Control Valve	Oil King™       .260         Coolant King™       .261
Dispense Consoles	0il Ace™
	16-Gallon Mobile Receiver
Grease Pumps	Big Hauler™ Truck Drain
Grease Pump Selection Guide	Track Receivers
LD Series <sup>™</sup> Grease Pump Accessories	Diaphragm Evacuation Pumps267
Mini Fire-Ball <sup>®</sup> 225 Grease Pumps117-120	Evacuation Pump Packages
Fire-Ball® 300 Grease Pumps	Fluid Reclaim Accessories
Fire-Ball® 425 Grease Pumps	Accessories
GT 750 36:1 Grease Pumps	Air Regulators and Valves
NXT <sup>™</sup> Check-Mate <sup>®</sup> Grease Pumps	Air Valves
Dyna-Star® Hydraulic Grease Pumps147-148	Hose Fittings
Viscount® II Grease Pumps	Lubrication Hoses
Manually-Operated Grease Pumps151	Air/Water Hoses
Grease Dispense Valves and Guns	Quick Connect Fittings281
Dispense Valve and Gun Selection Guide	Adapters and Fittings
Accu Shot™ Metered Grease Valve	Warranty Information 284-286
Pro Shot <sup>™</sup> Non-Metered Valve	•
Heavy-Duty Grease Guns	Index

# **About Graco**

Established in 1926, Graco has built a worldwide reputation for high quality, reliable and technically advanced products, world-class manufacturing and outstanding customer service. Headquartered in Minneapolis, Minnesota, Graco works closely with distributors around the world to offer innovative products that set the quality standard for spray finishing, paint circulation, lubrication, sealant and adhesives dispensing, process application and contractor power equipment. These best-in-class products are manufactured in the U.S. and China and supplied through our distribution centers around the world. Every day, Graco's fluid-handling equipment and systems move, measure, mix, control, dispense and spray a variety of fluids and materials.



# **Lubrication Equipment Division**

From the first air-powered grease gun to our industry-leading Fire-Ball pump, Graco's Lubrication Equipment Division is what started it all. We manufacture equipment to monitor, control, manage and dispense fluids. Offering innovative equipment for all your vehicle services, industrial and automatic lubrication needs. We offer a full range of high-quality pumps, meters, valves, hose reels and accessories to increase production and reduce waste and downtime.

Graco offers a full line of quality equipment to meet the varying needs of vehicle maintenance and repair. Streamline your workflow and move more lubricants through your shop. We offer reliable, high-quality equipment you can depend on for fuel, diesel, antifreeze, oil and grease. Our versatile fluid inventory control and management systems are designed to accurately track the use of oil, grease and other automotive fluids at vehicle maintenance facilities, and our lubrication equipment ensures you deliver fluids to the right spot in your shop. From light-duty applications to high-performance concepts designed for heavy-duty jobs, our equipment is known for its rugged, durable and long-life design.



**Machining** is a core competency of Graco – it enables complete control of the component parts needed to ensure precise metering, reliable dispensing and fluid movement.

When it comes to **research and development**, Graco is one step ahead, ensuring we offer the best possible solutions. To guarantee superior quality and to meet the changing requirements of your markets, we prioritize investing resources in research and development. Innovative technologies and extensive field testing are a natural part of our process to develop new products. Also, every aspect of our production is subject to constant testing and

evaluation. It's the foundation to deliver products with long service life and low cost of ownership. The insurance to help you grow your business.



We understand our customers. We build a partnership, working and striving towards new solutions, together. We are at the service of our distribution partners, supporting you along the way. Look at Graco not just as a manufacturer or supplier but as an extension of your business. Our dedicated and experienced teams offer unique capabilities to help you meet your specific goals and challenges.

- Innovative, high-quality products with unique features
- A professional warranty and high service rate
- Purchasing conditions aimed at profitable growth
- A committed sales and marketing team for tailor-made support of expanding sales opportunities
- Continuous technical, commercial and hands-on training

Our world-class distribution centers and unrivaled global distributor network give Graco a unique industry advantage that allows us to rapidly deliver our products to end users worldwide.

Exceeding customer expectations is our priority. Our multilingual team of customer service specialists and technical engineers are available to you. Graco offers instructor-lead training sessions in the United States, EMEA and Asia Pacific. These courses teach theory and hands-on practical applications, covering basic operational to advanced technical knowledge. Each training session can be adapted to your specific needs.

Offering more than just products, we are focused on building relationships, identifying and developing business opportunities with you. Our sales team is available to collaborate, define strategies to assist in navigating through our product offering and provide advice on promotional activities.

Graco's marketing specialists investigate ways to expand the market and develop the right technologies for any application, in close cooperation with distributors and field users. We offer tailor-made



promotional and communication support, from defining strategic requirements to developing marketing campaigns, organizing events and creating digital or printed material.



# **Did You Know?**

# Graco also manufactures and sells a complete line of automatic lubrication systems and accessories!



# **Graco Resources**

Graco has developed tools and resources to help educate and better serve our distribution channel. Check them out today:



# Graco Sales Book

Stay up-to-date with the newest information from Graco by downloading the Graco Sales Book App.

Graco Sales Book is an innovative mobile application, designed to give Distributors access to Graco product information, including brochures, manuals, videos, and training documents - all on your mobile device.

Download today by visiting Salesbook.graco.com



# Graco University

Graco University is an e-learning module that can be accessed online, anytime, and contains assets that help educate you on Graco products.

This innovative online learning program gives the tools to stay on the leading edge with a variety of resources such as virtual and instructor led courses, online books, live and on-demand video presentations, and much more.

Learn more today at training.graco.com



# Graco Gear

Graco Gear is your one-stop shop for branded merchandise and other tools that will help you build customer relationships.

Order shirts, hats, banners, and more whenever you need! You can even add your logo for a small fee. Most orders ship next day.

Start shopping today at gracogear.com



# **FLUID MANAGEMENT SYSTEMS**

	Page
Fluid Management System Selection Guide	9
Benefits of Pulse® Pro Fluid Management	10
Steps to Build Your Pulse Pro System	11
Pulse Hub	12-13
Pulse Dispense Meter	14-15
Pulse Tank Level Monitor (TLM)	16
Pulse Pump Air Control (PAC)	17
Pulse Extender and Remote Extender	18
Pulse Packages and Accessories	19
Steps to Build Your Pulse FC System	20
Pulse FC Software	21
Pulse FC Starter Kit	22
SD <sup>™</sup> Preset Dispense Meters	23-24
Pulse FC Packages and Accessories	25
Traditional Box – Wired Fluid Control Compon	ents26






# **Choosing a Graco Fluid Management Solution**

FEATURE	Traditional Box	Pulse FC	Pulse Pro
Control. Regulate the amount of fluid that's dispens	sed to reduce spillage and w	aste.	
Allow control of dispenses	<b>✓</b>	<b>✓</b>	<b>✓</b>
Restrict the quantity of fluid	<b>✓</b>	<b>✓</b>	<b>✓</b>
Ensure correct amount of fluid	<b>✓</b>	<b>✓</b>	<b>✓</b>
Meters. Put control into the hands of your technicia	ans so they can be more pro	ductive, accurate and ac	countable.
Works with petroleum, synthetic based oils, anti-freeze	<b>✓</b>	<b>✓</b>	<b>✓</b>
Works with windshield wash solvent	<b>✓</b>		<b>✓</b>
Meter displays quantity dispensed		<b>✓</b>	<b>✓</b>
Fluid measured at dispense point (highly accurate)		<b>✓</b>	<b>✓</b>
Installation. Seamless integration simplifies disper	nses without compromising v	vorkflows or productivity	
Works with oil bar	<b>✓</b>	<b>✓</b>	<b>✓</b>
Wire-free installation		<b>✓</b>	<b>✓</b>
Wireless communication			<b>✓</b>
Pump air control (PAC)	<b>✓</b>		<b>✓</b>
Flexibility. Accommodate emerging demands to m	aintain or expand productivit	y and profitability.	
Works with mobile roll-around packages		<b>✓</b>	<b>✓</b>
Easy expansion with additional fluids		<b>✓</b>	<b>✓</b>
Easy upgrade to comprehensive fluid management		<b>✓</b>	N/A
<b>User Interface.</b> Access the information necessary	to make more informed deci	sions quickly.	
Simple PC-based software		<b>✓</b>	
No software to install			<b>✓</b>
Accessible from any PC, phone or tablet			<b>✓</b>
Fluid Management. Improve accountability for you	ır entire operations.		
Track dispenses by invoice or work order			<b>✓</b>
Track dispenses by technician			<b>✓</b>
Record fluid type and quantity dispensed			<b>✓</b>
Keeps technician in service bay			<b>✓</b>
Fluid Inventory. Simplify how you re-order and sto	re inventory to minimize dela	ays.	
Monitor tank levels (TLM)			~
Dealer Management Solution (DMS) integration			•
Reporting. Capture critical information and insights	s to simplify decision-making	J.	
Print on dispense			<b>✓</b>
Automated customizable reports			<b>✓</b>
Automated alerts to simplify inventory tasks			•
Software updates		<b>✓</b>	V
Permanent record of all dispenses or authorizations		<b>✓</b>	<b>✓</b>

Pulse® Pro Fluid Management simplifies how forward-thinking shops track and manage bulk fluids in real time – adding more transparency and accountability to drive productivity and profitability.



# **Benefits of Pulse Pro Fluid Management**



Transparency. Monitor every drop, every time - automatically - and minimize shrinkage, rounding and discrepancies.



Scalability. Add Pulse into almost any environment quickly, and even retrofit applications or multiple buildings within the same facility.



Accountability. Track issues to the source via advanced technology, including automated alerts and customizable reports.



Accurate billing. Automatically assign every ounce of fluid directly to a work order to simplify billing and maximize profit margins.



Integration. Capture data, integrate it with popular DMSs and share it with other stakeholders quickly.



Simplicity. Avoid surprises, interruptions and delays. Fluids are tracked and recorded instantly and automatically.




Portability. Pair with mobile dispense units and drums easily to reduce extra steps and hassles for technicians.




Inventory management. Monitor fluid inventory and schedule refills to minimize delays and excessive costs.



# **Pulse® Pro Fluid Management**



# **Steps to Build Your Pulse Pro System:**



# **Add Accessories**



# Pulse® Pro Fluid Management



# Pulse Hub



Simply connect the Pulse Hub to a power source and access your local network to get started. The self-contained device includes everything necessary for users to access monitoring and reporting tools instantly from any network-connected PC, tablet or smartphone.

#### **Pulse Software**

Pulse Pro Fluid Management software is pre-installed on the Pulse HUB and focused on simple intuitive design with powerful information at your fingertips. Get a quick consolidated view of all dispenses for the entire shop via specifically designed web page and easy-to-use software. Track tank levels at a glance. Generate customizable reports and automated e-mail alerts to share critical information with other key decision-makers. For further efficiency and automation, Pulse software can be integrated with your DMS through Pulse standard integrations or our generic third-party interface.



#### Features and Benefits

- No PC software to install Pulse Hub generates a local web page
- Responsive web design Use any-size screen, from a PC to a phone
- Consolidated dispense queue Find everything you need in one convenient table
- Advanced reporting Create and schedule automated reports to track history and fluid usage
- Informative and preventive alerts The software offers over two dozen alert activities
- Automatic software updates Software notifies you when updates are ready to install

Technical Specifications	
Weight	1.0 lb (454 gm)
Power Supply	
Input Power	100-240 VAC line voltage (0.05 A)
To Hub 5 VDC (0.5 amps)	
Warranty	Two years electronics

# Part Number Description 242978 Hub for non-European installation with global power adapter

# **DMS Integration Options for Pulse Pro**

An integration, put simply, is the communication between two separate business systems. Pulse uses integrations to provide enhanced control and monitoring for fluid dispenses.

# **Option 1** – Partner Integrations

#### AssetW**≎**RKS

- Requires FleetFocus: FA or M5 with FluidFocus Module
- Communication through Enterprise Asset Management System



- Requires CDK Drive DMS
- Communication through CDK's Third-Party Access Program

#### Dealertrack 4

- · Requires Dealertrack DMS
- Communication through Dealertrack's Opentrack API



- Requires Excede v9.22+ with Excede Database
- Communication through Excede API v2.0



- Requires PBS DMS
- Communication through PBS Partner Hub



- Requires ERA
- Communication through RCI Web Service

# **Option 2** – Communication through Graco Third Party Interface



 Requires End-user developed integration for non-supported DMS





#### **How It Works**

The interface to business systems or DMS provides two important basic functions:



# Ordering Information

#### **Interface Activation Codes**

Part Number	Description	
25R975	Pulse software with CDK Global Drive	
25R976	Pulse software with Dealertrack	
25R977	Pulse software with AssetWORKS	
25R978	Pulse software with Reynolds & Reynolds	
25R979	Pulse software with Procede Software – 2nd site	
25R980	Pulse software with Procede Software	
25R981	Pulse software with PBS	













# **Pulse Dispense Meter**

The dispense meter is durable and easy to use, giving technicians everything they need at their fingertips. PINs and other data can be entered in moments via a larger, more intuitive display. NFC tags can be used for immediate PIN entry and faster access to work orders.

GRACO



# Large, Intuitive Display

High-contrast display for lowand bright-light conditions.

#### Faster PIN Entry

Built-in NFC reader and simple, efficient controls.

#### Wireless Communication

Communicates dispense information with Hub.

# Ergonomic Design

Lower button placement.



Choose from rigid, flexible or gear lube extensions with automatic flush-mount nozzle design.

#### Long Battery Life

Uses four off-the-shelf AA batteries easy to replace.

# Long-Life Valve Design

Cartridge design for long life and easier repair.

# **Protective Trigger Guard**

Prevents accidental dispenses.

	A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
nical Specifications			
Flow Range*	0.25 to 18 gpm (0.9 to 68 lpm)		
Maximum Working Pressure	1,500 psi (103.4 bar)		
Units of Measure (factory set to quarts)	Pints, quarts, gallons, liters		
Weight	5.3 lbs (2.4 kg)		
Inlet	1/2 in NPT or 3/4 in NPT		
Outlet	3/4 in straight thread 0-ring boss		
Dimensions (without extension)			
Length	13 in (33 cm)		
Width	3.75 in (9.5 cm)		
Height	5.75 in (14.6 cm)		
Maximum Recorded Dispense	999.99 units		
Operating Temperature Range	4°F to 158°F (-16°C to 70°C)		
Storage Temperature Range	-40°F to 158°F (-40°C to 70°C)		
Battery**	4 AA alkaline or lithium batteries		
RF Frequency Band	2,400 to 2,483.5 MHz		
Maximum RF Transmit Power	8 dBm		
Wetted Parts	Aluminum, stainless steel, PBT, nitrile rubber, zinc-plated carbon steel, nickel-plated carbon steel		
Fluid Compatibility	Anti-freeze, gear oil, crankcase oil, ATF, windshield wash (up to 50% alcohol-based solutions		
Meter Accuracy <sup>†</sup>	+/- 0.5 percent		
Warranty	Five year structural, 3 years electronics, 1 year wear components		

<sup>\*</sup>Tested in 10W motor oil. Flow rates vary with fluid pressure, temperature and viscosity.

<sup>&</sup>quot;Battery required to meet life expectancy: Energizer" Akaline E91.

At 2.5 gpm (9.5 lpm), at 70°F (21°C), with 10W oil and 1 gallon dispensed. May require calibration; out-of-box accuracy is +/- 1.25 percent.













# 8 gpm (30 lpm) Meters

Fluid	Extension	Nozzle	Size (in)	Part Number
Oil	Flexible	Automatic		25M319
Oil	Rigid	Quick-Close		25M317
Anti-Freeze	Flexible	Flexible Manual		25M320
AIIII-FIEEZE	Rigid	Anti-Freeze	1/2	25M318
Gear Lube	Gear Lube	Manual		25M326
Windshield Wash	Rigid	None		25M328

# 18 gpm (68 lpm) Meters

Fluid	Extension	Nozzle	Size (in)	Part Number
Oil / Anti France	Flexible	Manual High-Flow	1/2	25M324
	Rigid			25M323
Oil / Anti-Freeze	Flexible	Manual	2/4	25M330
	Rigid	High-Flow	3/4	25M329

## **Accessories**

## **Nozzle and Extension Kits**

	Extension	Fluid	Nozzle Description	Part Number	Compatible Meters
F-780		Oil	Non-drip, quick-close	255852	25M317
	Rigid	Anti-freeze	Non-drip, quick-close	26C267	25M318
- 10		Oil/Anti-freeze	High-flow, non-drip, quick-close	255857	25M323 / 25M329
1	Rigid	Gear lube	Non-drip, quick-close	255854	25M326
		Oil	Automatic, non-drip, quick-close	255853	25M319
	Flexible	Anti-freeze	Non-drip, quick-close	26C268	25M320
		Oil/Anti-freeze	High-flow, non-drip, quick-close	255858	25M324 / 25M330
		Oil	Automatic, non-drip, quick-close	17R220	8 gpm oil meters
E	Nozzle Only	Anti-freeze	Non-drip, quick-close	17T207	8 gpm anti-freeze meters
		Oil/Anti-freeze	High-flow, non-drip, quick-close	255461	18 gpm meters
45	Nozzle Only	Gear lube	Non-drip, quick-close	255470	8 gpm gear lube meters

# **NFC Tags**

Part Number	Description
131462	NFC tags for user identification with meter. 25-pack, blue.

# **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
OGRACO	17S659	Red
0 GRACO	17S660	Blue
O GRACO	17S661	Green
Oanaca	17S662	Yellow
O GRACO	17S663	White

# **Swivel Covers / Impact Protection**

	Part Number	Description
	15T366	Black swivel cover (standard color with meter)
	15T367	Red swivel cover
	15T368	Blue swivel cover
	15T369	Green swivel cover
	15T370	Yellow swivel cover
0	131226	Pulse / SD meter boot

## **Pulse Meter Filter Kits**

Pa	art Number	Description
	25D906	Filter kit includes filters/strainers (15M308) and 0-rings (155332)

# **Pulse® Pro Fluid Management**













Pulse Tank Level Monitor (TLM)
Measure your largest tanks accurately with minimal effort. The monitor's ultrasonic sensor records the tank level and can be configured to e-mail a daily report to key stakeholders detailing tank volumes, low- or high-level warnings and more.

G



## Simple Wireless Setup

Automatic network identification.

# Long Battery Life

Allows for remote installations. Uses four off-the-shelf AA batteries - easy to replace.

## **Built-In Display**

Real-time level visible from built-in display.

# Supports Multiple Tank Shapes

Ability to input strapping table for any tank shape.



Sealed enclosure to accommodate outdoor usage.

## Compact Design

Easily fits into more spaces.

# **On-Demand Readings**

Ability to take reading at any time.



#### **Ordering Information**

Part Number	Description	
25M449	Tank Level Monitor (TLM)	

hnical Specifications	
Ultrasonic Tank Depth Measurement range (Not for use in pressurized tanks)	5 in to 30 ft (12.7 cm to 9.14 m)
Fluid Level Measurement Accuracy	+/- 1.8 in (4.57 cm)
Mounting	1.5 in and 2 in threaded NPT connector (Adapter for BSPP and BSPT thread options available)
Weight (with batteries installed)	1.25 lb (567 g)
RF Frequency Band	2,400 to 2,483.5 MHz
Operating Temperature Range (Display will not function below 32°F [0°C])	-22°F to 185°F (-30°C to 85°C)
Storage Temperature Range	-40°F to 185°F (-40°C to 85°C)
Batteries	Four AA alkaline
Enclosure	IPX5
RF Communication	2,400 to 2,483.5 MHz
Vertical Tanks	
Maximum Volume	999,999 gal (999,999 l)
Maximum Height	30 ft (9.14 m)
Cylindrical Tanks	
Maximum Volume	999,999 gal (999,999 l)
Maximum Height	30 ft (9.14 m)
Maximum Length	30 ft (9.14 m)
Maximum Width	30 ft (9.14 m)
Fluid Compatibility	Automatic transmission fluid, anti-freeze, window wash, coolant, waste water
Warranty	Two years electronics













# **Pulse Pump Air Control (PAC)**

Prevent unauthorized access to fluid inventory. Pump air supply is shut off automatically after the dispense, preventing spills and expensive cleanup if a broken line occurs. Pump operation is enabled only when a dispense has been activated from the meter.



# Easy Installation

Built-in mounting bracket.

# Simple Wireless Setup

Automatic network identification.

# High-Volume Air Valve

Supports a variety of pumps.

## Multiple Thread Options

NPT and BSPP air valve options.



# Ordering Information

Part Number	Description
24Z728	NPT with NEMA 5-15 plug

Technical Specifications			
Minimum Operating Pressure	36 psi (0.25 MPa, 2.5 bar)		
Maximum Operating Pressure	145 psi (1.0 MPa, 10 bar)		
Maximum Air Flow	93 SCFM (2.6 m³/min)		
Power Supply	100–240 VAC line voltage, 24 VDC solenoid		
Power Cord			
Model 24Z676, 24Z677	6 ft SJ00W, 3-wire, 18-gauge cable with flying leads		
Model 24Z728	Power cord with integrated NEMA 5-15 plug		
Current	25 to 60 mA		
RF Frequency Band	2,400-2,483.5 MHz		
Connection Ports Size (inlet, ou	tlet, exhaust)		
Model 24Z676, 24Z728	3/8 in NPT		
Model 24Z677	3/8 BSPP		
Operating Temperature Range	14°F to 122°F (-10°C to 50°C)		
Storage Temperature Range	-40°F to 185°F (-40°C to 85°C)		
Weight	2.44 lbs (1.11 kg)		
Dimensions			
Length	9.5 in (241.3 mm)		
Width	2.25 in (57.2 mm)		
Height	3.75 in (95.3 mm)		
Warranty	Two years electronics		



#### **Pulse Extender**

The Pulse wireless network can easily be expanded to accommodate large shops or a large number of devices. Simply plug the Extender into wall power to extend the network.

# **Expands Pulse Network**

Supports 20 devices and extends the network range.

#### Simple Wireless Setup

Automatic network identification.

# Integrated Electrical Plug

Simply plugs into wall.

# Compact Design

Place conveniently in standard electrical outlet locations.



Technical Specifications					
	Operating Temperature	32°F to 158°F (0°C to 70°C)			
	Power Input	Universal AC input (85 VAC to 265 VAC)			
	Length	2.87 in (7.3 cm)			
	Width	1.97 in (5.0 cm)			
	Height	1.37 in (3.5 cm)			
	Weight	2.50 oz (70.9 g)			
	Warranty	Two years electronics			



#### **Ordering Information**

Part Number	Description
17F885	Extender (Type A)

#### **Pulse Remote Extender**

The Pulse wireless network can easily be expanded to accommodate devices in secondary on-site buildings. Connect the Remote Extender to wall power and local network via Ethernet or Wi-Fi to extend the network.

Pulse"

Remote

Extender



Ethernet or Wi-Fi

10/100Base-T

802.11 b/g/n

3 in (7.62 cm)

3 in (7.62 cm)

1 in (2.54 cm)

Two years electronics

32°F to 104°F (0°C to 40°C)

#### Expands Pulse Network

Supports 20 devices and extends the network range.

#### Simple Wireless Setup

Automatic network identification.

#### Multiple Network **Connection Options**

Utilizes local network Ethernet or Wi-Fi to communicate back to Hub.

#### Compact Design

Easy to place even in tight spaces.

#### **Electrical Power**

Includes plug-in power adapter.



# **Ordering Information**

**Technical Specifications** 

Part Number	Description
17F878	Remote Extender with global power adapter















## **Ordering Information**

## **Roll Around Package**

Pulse Pro Fluid Management wireless technology allows you to control your mobile drums and dispenses by providing security for expensive drums of synthetic and semi-synthetic fluids. Each package contains everything you need to manage your drums in existing Pulse installations. Drum not included.

|--|

Package	Extensions	Package Includes					
Number	EXTENSIONS	Meter	Pump	Downtube	Drum Cart	Air Regulator	Hose
25D948	8 GPM, Rigid	25M317					
25D952	8 GPM, Flexible	25M319	24G576	16F878	24F915	24H420	24H865
25D953	8 GPM, Gear Lube	25M326					



## **Ordering Information**

#### Oil Bar

Part Number	Description	
25D121	Oil Bar Console	
25D130	Oil Bar Dispense Kit	
25N415	Oil Bar Pulse Dispense Meter	



#### il Rar

Components ordered separately. For complete unit, order console (25D121), dispense kit (25D130) (one per meter) and Pulse meters (25N415) as needed.

#### **Accessories**

Can-	Part Number	Description
	249440	Console bracket

#### **Pulse Pro Demo Kit**

Pulse Pro demo case with everything needed to show customers how Pulse Pro will save them time, gain them more billable hours and maximize their fixed operation's profitability.

uhumlis.	Part Number	Description
	25D625	Includes Pulse Hub (24Z978), Pulse Dispense Meter, Pulse TLM (25M449), Pulse PAC (24Z728), Pulse Extender (17F885), Pulse Remote Extender (17F878), Pulse NFC Tag, case and protective foam

Pulse® FC is wire-free, so installation and configurations are easier and cheaper. We've replaced the big box console with fast, reliable and convenient fluid cards scanned at easy-to-handle meters, so users can employ the same type of familiar technologies they use elsewhere.



## **HOW IT WORKS**

1 REQUIRED


Pulse FC is a fluid control system that utilizes SD Preset meters. When put into Pulse FC mode, SD Preset meters will only dispense fluid when authorized with Fluid Cards. These included cards are programmed using the Pulse FC Software and Card Programmer. Once programmed, the cards are simply tapped to the meter which will be preset for the authorized amount of fluid and will not dispense any more than authorized.

**MINIMUM 1 REQUIRED** 

Add Accessories

**Roll Around Package** 

**OPTIONAL** 



20









# GAIN INSIGHT INTO AND CONTROL OF YOUR BULK FLUIDS



**Simplicity.** Avoid surprises, interruptions and delays. Fluids are easily controlled so technicians can spend more time serving more customers.



**Accountability.** Be assured every vehicle or machine receives the appropriate amount of fluid for more accurate billing.



**Scalability.** Add Pulse FC into almost any environment quickly, even retrofit applications and avoid excessive installation costs and delays. You can also easily upgrade to Graco's Pulse Pro.



**Mobility.** Pair with mobile dispense units and drums quickly so your team can conveniently dispense without delays, hassles or extra steps.

# **Pulse FC Software**

Pulse FC is a Windows PC-based software. Paired with the card programmer it allows setup and operation of the system. Cards can be utilized to authorize dispenses, totalize all fluids dispensed, as well as setup and calibrate SD™ Preset meters.













# **Pulse FC Starter Kit**

Enjoy an easy-to-use, easy-to-install, out-of-the-box fluid control system designed for fast wire-free setup and configuration. Pulse FC integrates into existing or new environments quickly and cost-effectively without interrupting daily operations.



## Pulse FC Fluid Cards

Reusable fluid cards can be scanned directly on the SD preset meter's built-in NFC reader.

# Pulse FC Software

Simple PC-based software is used in conjunction with Pulse FC Programmer.

# Pulse FC Software Quick Start

Easy-to-follow instructions for quick system setup.

# **Ordering Information**

Part Number	Description
26C401	Pulse FC Starter Kit – Includes Software, Card Programmer, Software Quick Start and 50-Pack of Fluid Cards











# SD<sup>™</sup> Preset Dispense Meters

With Pulse FC, dispense only precise volumes to create efficiencies for your entire shop operation. Monitor how much fluid you're using. Choose the amount of fluid each technician can dispense in order to maintain accurate inventory.



GRACO



High-contrast screen for reading in all lighting conditions with easy setup and navigation. See what fluid the meter is setup for and exactly how much you are dispensing.

# **Upgrade Option**

Compatible with  $Pulse^{T}$  FC and upgradeable to  $Pulse^{T}$  Pro.

# High Flow

Available in two models -8 gpm (30 lpm) or 18 gpm (68 lpm).

#### **Durable Cast Body**

Designed for heavy duty and harsh applications.

# Automatic Quick-Close Nozzle

Choose from rigid or flexible extensions with non-drip performance.

# Long-Life Valve Design

Cartridge design for fewer and easier repairs.

## Ergonomic Handle Design

Four-finger trigger and easy-to-use button pad reduce worker fatigue.

#### **Typical Applications**

- Automotive dealerships
- · Heavy-duty dealerships
- · Fast lube centers
- · Fleet service facilities
- Service shops
- In-plant
- Mining

# Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor gear, and ATF)
- Anti-freeze

Гес	echnical Specifications				
	Flow Range*	0.25 gpm to 18 gpm (0.9 lpm to 68 lpm)			
	Maximum Working Pressure	1,500 psi (103.4 bar)			
	Units of Measure	Pints, quarts, gallons, liters (factory set to quarts)			
	Metered Dispense Valve Accuracy**	+/- 0.5%			
	Inlet	1/2 in–14 NPT or 3/4 in–14 NPT			
	Outlet	3/4 in–16 straight thread O-ring Boss			
	Maximum Recorded Dispense	9999 units (factory set in quarts)			
	Operating Temperature Range	4°F to 158°F (-20°C to 70°C)			
	Storage Temperature Range	-40°F to 158°F (-40°C to 70°C)			
	Wetted Parts	Aluminum, stainless steel, PBT, nitrile rubber, zinc plated carbon steel, nickel plated carbon steel			
	Dimensions (without extension)	13 in L x 3.75 in W x 5.75 in H (33 cm x 9.5 cm x 14.6 cm)			
	Weight	5.3 lb (2.4 kg)			
	Warranty	Five years overall, three years electronics			
	Instruction Manual	3A6711 and 3A6673			

<sup>\*</sup>Tested in 10W motor oil. Flow rates vary with fluid pressure, temperature and viscosity.

<sup>\*\*</sup>At 2.5 gpm (9.5 lpm), at 70°F (21°C), with 10-weight oil and 1 gallon dispensed. May require calibration.
\*\*\*Battery required to meet life expectancy: Energizer® Alkaline E91.











# Ordering Information

# **SD<sup>™</sup> Preset Electronic Meters**



	Dispense Type	Flow Range gpm (lpm)	Fluid	Extension	Inlet in (NPT)	Part Number				
			Oil -	Rigid	1/2	26C384				
				Flexible	1/2	26C354				
SDP8	Preset (Pulse FC enabled)	0.25-8	0.25–8 (1–30)	Anti-freeze	Anti-freeze	Rigid	1/2	26C385		
	(r diod r o oridation)	(. 55)	Anu-ireeze			Anti-neeze	Anu-neeze	Allii-lieeze	Anu-neeze	Flexible
			Gear lube	Rigid	1/2	26C358				
		0.25–18	011	Rigid	1/2	26C356				
SDP18	Preset			Oil	Flexible	1/2	26C357			
S	(Pulse FC enabled)	(1–68)	Oii	Rigid	3/4	26C360				
				Flexible	3/4	26C361				

# **Nozzle and Extension Kits**

	Extension	Fluid	Nozzle Description	Part Number	Compatible Meters
		Oil	Non-drip, quick-close	255852	SDP8
	Rigid	Anti-freeze	Non-drip, manual open/close	26C267	SDP8
No.		Oil/Anti-freeze	High-flow, non-drip, quick-close	255857	SDP18
<b>N</b> .	Rigid	Gear lube	Non-drip, quick-close	255854	SDP8
		Oil	Automatic, non-drip, quick-close	255853	SDP8
	Flexible	Anti-freeze	Non-drip, manual open/close	26C268	SDP8
•		Oil/Anti-freeze	High-flow, non-drip, quick-close	255858	SDP18
THE STATE OF THE S	Nozzle Only	Oil	Automatic, non-drip, quick-close	17R220	SDP8
4	Nozzle Only	Gear lube	Non-drip, quick-close	255470	SDP8
	Nozzle Only	Oil/Anti-freeze	Non-drip, manual open/close	17T207	SDP8
0	Flexible	Oil/Anti-freeze	Extension only, 2 ft length	131733	SDP8











# **Ordering Information**

## **Roll Around Package**

Pulse FC wire-free technology allows you to control your mobile drums and dispenses by providing security for expensive drums of synthetic and semi-synthetic fluids. Each package contains everything you need to manage your drums in existing installations. Drum not included.

|--|

Package	Extensions	Package Includes					
Number	EXTENSIONS	Meter	Pump	Downtube	Drum Cart	Air Regulator	Hose
26C366	8 GPM, Gear Lube	26C358					
26C367	8 GPM, Flexible	26C354	24G576	16F878	24F915	24H420	24H865
26C409	8 GPM, Rigid	26C384					

#### Oil Bar

Part Number	Description
25D121	Oil Bar Console
25D130	Oil Bar Dispense Kit
25N771	Oil Bar SD Preset Dispense Meter



#### Oil Bar

Components ordered separately. For complete unit, order console (25D121), dispense kit (25D130) (one per meter) and Pulse FC meters (25N771) as needed.

#### **Accessories**

## **Pulse FC Fluid Cards**

(many	Part Number	Description	
Q	130783	Pulse FC Fluid Cards – 50-Pack, White	

# **Pulse FC Demo Kit**

Part Number	Description	
26C399	Includes Pulse FC Dispense Meter, Software, Card Programmer and 5-Pack of Fluid Cards	

#### **SD Meter Filter Kits**

Part Number	Description	
25D906	Filter kit includes filters/strainers (15M308) and 0-rings (155332)	

# **Swivel Covers / Impact Protection**

	Part Number	Description
	15T366	Black swivel cover (standard color with meter)
	15T367	Red swivel cover
	15T368	Blue swivel cover
	15T369	Green swivel cover
	15T370	Yellow swivel cover
8	131226	Pulse / SD meter boot

## **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
O GRACO	17S659	Red
O GRACO	17S660	Blue
Q GRACO	17S661	Green
OGRACO	17S662	Yellow
O GRACO	17S663	White

# **Traditional Box – Wired Fluid Control Components**











# >>> Ordering Information

## **In-Line Meters**

Part Number	Description
236763	Electronic pulse output meter (quarts)
236764	Electronic pulse output meter (liters)
215474	Mechanical pulse output meter (quarts)
244342	Meter pulse converter, used when upgrading old-style modular fluid commander to electronic allows use of 215474/215475 with the EFC.

## **Air Solenoid Valves**

Part Number	Description
215407	Air solenoid valve, 150 psi (10 bar) (1/2 npsm (f) conduit ports for wiring; 1/4 in NPT(F) air ports, adapted to 3/8 (f) IN, 3/8 (m) OUT) operates on 24V DC and 110 VAC. Automatically shuts-off air inlet to pump when pre-set dispensed amount is reached. Materials of construction: brass, SST, Buna.
105474	Air solenoid valve (bare) 150 psi (10 bar), same as 215407 but without wire connectors or adapters. 1/2 in npsm (f) conduit ports for wiring; 1/4 in NPT(F) air ports.150 psi (10.3 bar) max. working pressure.

## **Fluid Solenoid Valves**

Part Number	Description
215487	Fluid solenoid valve, 1/2 in NPT(F) 3,000 psi (207 bar) operates on 24V DC. Automatically shuts-off fluid when pre-set dispensed amount is reached. Includes tube, valve, pin connector, wire plug connector and adapter.
514150	Fluid solenoid valve for anti-freeze, 150 psi max. (10 bar), 1/2 in NPT(F), same as features as 215487.
110025	Bare fluid solenoid valve, 1/2 in NPT(F) 3,000 psi, same features as 215487 above, but without wiring connectors or adapters.

# **Ready-Light Kits**


Part Number	Description
218588	Ready-light kit, signals operator when dispensing can begin. Includes "ready to dispense" indicator light (239019), strainer (240417), fluid solenoid valve (215487) and hardware.
238996	Ready-light with junction box (no solenoid or strainer)
239019	Ready-to-dispense indicator light only
113859	Lamp for indicator only

# **Installation Components**

Part Number	Description
111620	Check valve
223179	Fluid filter kit (for bare electronic meter)
186472	Wall-mounting bracket
108458	Fluid shut-off valve
237893	Thermal relief kit for 900 psi (62 bar), relieves excess heat-induced pressure from dispense system. Male and female ends allow for simple installation.

# Connecting Cables for Connecting Solenoids and Consoles, 90-volt, 2-wire, 18-gauge

Part Number	Description
215481	100 ft (30.5 m) pre-connected at both ends



# **Oil Pump Selection Guide**

Pump Family and		Annual	Line	Simultaneous	Approx.	Air	Fluid	Fluid	Air Operation	Reference
Fluid Pressure Ratio	Typical Applications	Usage	Length	Dispense Points	Free Flow Rate @ 100 psi	Inlet	Inlet	Outlet	Range	Page
Fast-Ball, 1:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	5,000 gal (19,00 l)	< 100 ft (30 m)	1 (no reels)	5 gpm (19 lpm)	1/4 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-80 psi (2.7-12.5 bar)	62
LD, 3:1	Automotive dealerships     Fast lube centers     Lube trucks     Lubricant transfer     Service shops	20,000 gal (75,000 l)	300 ft (91 m)	1 to 2	7.8 gpm (30 lpm)	1/4 NPT(F)	1 NPT(F)	1/2 NPT(F)	20-150 psi (1.37-10.3 bar)	30
LD, 5:1	Automotive dealerships     Fast lube centers     Lube trucks     Lubricant transfer     Service shops	20,000 gal (75,000 l)	300 ft (91 m)	1 to 2	6.7 gpm (25 lpm)	1/4 NPT(F)	1 NPT(F)	1/2 NPT(F)	20-150 psi (1.37-10.3 bar)	30
Mini Fire-Ball 225, 3:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	30,000 gal (113,500 l)	250 ft (76 m)	1 to 2	8.3 gpm (32 lpm)	3/8 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	40-180 psi (2.8-12 bar)	48
Fire-Ball 300, 5:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	35,000 gal (132,000 l)	500 ft (152 m)	1 to 3	12.1 gpm (46 lpm)	3/8 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	40-180 psi (2.8-12 bar)	52
Fire-Ball 425, 3:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 35,000 gal (132,000 l)	Up to 250 ft (76 m)	3 to 4	28.7 gpm (109 lpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	57
Fire-Ball 425, 6:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 35,000 gal (132,000 l	Up to 500 ft (152 m)	3 to 4	17.1 gpm (65 lpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	57
Fire-Ball 425, 10:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 35,000 gal (132,000 l	Up to 750 ft (228.6 m)	3 to 4	11.7 gpm (44 lpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	57

# **Oil Pump Selection Guide**

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Line Length	Simultaneous Dispense Points	Air Inlet	Fluid Inlet	Fluid Outlet	Air Operation Range	Reference Page
NXT High Flo, 3.5:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 250 ft (76 m)	4 to 5	3/4 NPT(F)	1-1/2 NPT(F)	1 NPT(F)	20-100 psi (1.4-7 bar)	69
NXT High Flo, 4.5:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 450 ft (137 m)	4 to 5	3/4 NPT(F)	1-1/2 NPT(F)	1 NPT(F)	20-100 psi (1.4-7 bar)	69
NXT High Flo, 6:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 500 ft (152 m)	4 to 5	3/4 NPT(F)	2 NPT(F)	2 NPT(F)	20-75 psi (1.4-5.2 bar)	69
NXT Dura-Flo, 6:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 500 ft (152 m)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(F)	20-100 psi (1.4-7 bar)	71
NXT Dura-Flo, 10:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 750 ft (228.6 m)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(F)	20-100 psi (1.4-7 bar)	72
NXT Dura-Flo, 12:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 1000 ft (305 m)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(M)	20-100 psi (1.4-7 bar)	72
NXT Dura-Flo, 23:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 35,000 gal (132,000 l)	Up to 1000 ft (305 m)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(M)	20-75 psi (1.4-5.2 bar)	72

Pump Family and Fluid Pressure Ratio	Typical Applications	Maximum Output Flow Rate	Maximum Fluid Output Pressure	Hydraulic Inlet	Hydraulic Outlet	Fluid Inlet	Fluid Outlet	Maximum Hydraulic Inlet Pressure	Reference Page
Dyna-Star 1:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	3 gpm (11 lpm)	1500 psi (102 bar)	3/8 NPT(F)	3/4 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	1500 psi (102 bar)	76
Dyna-Star 1/4:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	10 gpm (38 lpm)	375 psi (25.1 bar)	3/8 NPT(F)	3/4 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	1500 psi (102 bar)	76
Power-Star 1:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	12 gpm (45 lpm)	1500 psi (102 bar)	3/4 NPT(F)	1-1/4 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	1500 psi (102 bar)	78









**5 Year**Warranty!

# **Durable and Hardworking**

Stay ahead of the competition with LD Series pumps. These affordable and full-featured pumps are designed for lower-volume applications. LD pumps are fine-tuned for a compact, flexible and durable solution.

#### Three Inch Air Motor

Provides more power to create better flow.

# **Engineered for Durability**

Patented cup and plate design eliminates the need for O-rings that wear out faster, for a more durable, longer-lasting solution.

#### Modular Air Valve

Air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle-free installations.

#### Pilot Valves

Patented self-cleaning design increases reliability in dirty air environments and minimizes pressure drop with rapid changeovers for reduced stalling and smoother flow.

#### Built-In Thermal Relief and Inlet Strainer

Built-in thermal relief protects your equipment from thermal expansion, and an inlet strainer is built in to protect pump from contaminants.

#### **Typical Applications**


- · Automotive dealerships
- · Fast lube centers
- Service shops

#### Typical Fluids Handled

• Petroleum- and synthetic-based oils (motor, gear and ATF)


#### **Pump Performance**

#### **LD Series 3:1 Pumps**



# (10.3 bar) (B) = 100 psi (6.9 bar) (C) = 70 psi (4.8 bar) (D) = 40 psi Test Fluid :

#### LD Series 5:1 Pumps











nnical Specifications		
	LD Series 3:1	LD Series 5:1
Fluid Pressure Ratio	3:1	5:1
Air Motor Effective Diameter	3 in (76.2 mm)	3 in (76.2 mm)
Maximum Fluid Working Pressure	450 psi (31 bar / 3.1 MPa)	750 psi (51.7 bar / 5.17 MPa)
Approximate Free Flow Rate @ 100 psi	7.8 gal/min (30 liters/min)	6.7 gal/min (25 liters/min)
Output per Cycle	131 cc	102 cc
Approximate Air Use and Flow @ 100 psi (80 cpm)	18 scfm @ 2.8 gpm (0.51 m³/min @ 10.6 lpm)	18 scfm @ 2.1 gpm (0.51 m³/min @ 8.0 lpm)
Air Inlet	1/4 in	1/4 in
Fluid Inlet	1 in	1 in
Fluid Outlet	1/2 in	1/2 in
Air Operation Range	20 psi to 150 psi (1.37 bar to 10.3 bar)	20 psi to 150 psi (1.37 bar to 10.3 bar)
Maximum Recommended Pump Speed	120 cpm	180 cpm
Cycles per Gallon (liter)	29 (7.7)	37 (9.8)
Wetted Parts	Zinc plated carbon, steel, aluminum, nitrile, polyurethane, nickel plated aluminum	Zinc plated carbon, steel, aluminum, nitril polyurethane, nickel plated aluminum
Sound Pressure Level	72.9 dB(A)	72.9 dB(A)
Sound Power Level	82 dB(A)	82 dB(A)
Approximate Weight	7 lb (3.2 kg)	7.7 lb (3.5 kg)
Instruction Manual	3A1334	3A1334

# >>> Ordering Information

# **LD Series 3:1 Pumps**

	Part Number	Description
24G576 3:1 Universal oil pump with bung adapter (24F918)  24G579 3:1 Oil pump with cut-to-length PVC downtube (16F878) and bung adapter (24F918)  24G582 3:1 Oil pump with 55 gal (200 liter) downtube (16F886) and bung adapter (24F918)		3:1 Universal oil pump with bung adapter (24F918)
		3:1 Oil pump with cut-to-length PVC downtube (16F878) and bung adapter (24F918)
		3:1 Oil pump with 55 gal (200 liter) downtube (16F886) and bung adapter (24F918)
	24G585	3:1 Oil pump with 275 gal (1,040 liter) steel downtube (16F885) and bung adapter (24F918)

# **LD Series 5:1 Pumps**

Part Number	Description	
24G588	5:1 Universal oil pump with bung adapter (24F918)	
24G591 5:1 Oil pump with cut-to-length PVC downtube (16F878) and bung adapter (24F91 24G594 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (16F886) and bung adapter (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (24F91 5:1 Oil pump with 55 gal (200 liter) steel downtube (24F91 5:1 Oil pump with		
		24G597

# **LD Series 3:1 Oil Pump Packages**










**Ordering Information** 

#### Mobile Oil Packages - Cart

Air regulator (part 24H420 - ordered separately) must be used for LD pump thermal relief function.







32









# Mobile Oil Packages - Dolly

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.











# Ordering Information

# **Wall Mount Oil Packages**

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.





Package 24H695 installed on a 275 gallon tote (not included in package).

# **Stationary Oil Packages**

Ratio

Hose Kit

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.

	-		A STATE OF THE PARTY OF THE PAR	Par
Package Number	24H800	24H799	24H802	24H801
Ratio	3:1	3:1	3:1	3:1
Pump Part Number	24G576	24G576	24G576	24G576
Suction Tube Size	Universal	Universal	Universal	Universal
Pump Downtube	16F878	16F878	16F878	16F878
Meter Type	Manual	Manual	Preset	Preset
Meter Part Number	25C903	25C904	256216	255277
Meter Extension	Rigid	Flexible	Rigid	Flexible
Hose Kit	24H859	24H859	24H859	24H859
Instruction Manual	3A1335	3A1335	3A1335	3A1335










#### Stationary Oil Packages - Tote

Standard packages include LD Series hose reel. Air regulator (part 24H420 - ordered separately) must be used for LD pump thermal relief function.



Package 24H728 installed on a 275 gallon tote (not included in package).



# **LD Series 3:1 Oil Pump Packages**









Ordering Information

# **Deluxe Stationary Oil Packages - Tote**

Deluxe packages include SD Series hose reel. Air regulator (part 24H420 - ordered separately) must be used for LD pump thermal relief function.



Package Number	24K838	24K842
Ratio	3:1	3:1
Pump Part Number	24G576	24G576
Suction Tube Length	275 gal (1,040 l)	275 gal (1,040 l)
Pump Downtube	16F885	16F885
Reel Type	SD	SD
Hose Reel Part Number	HPM65B	HPM65B
Meter Type	Preset	Manual
Meter Part Number	256216	25C904
Meter Extension	Rigid	Flexible
Hoses and Fittings	24J495	24J495
Top Mount Tote Bracket	24F930	24F930
SD Reel/IBC Tote Bracket	24K285	24K285
Meter Tray	24F914	24F914
Instruction Manual	3A1335	3A1335









## **Tank Mount Oil Packages**

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.



## **LD Series 3:1 Oil Pump Packages**









### Ordering Information

## **Deluxe Tank Mount Oil Packages**

Deluxe packages include SD hose reel, air and fluid hoses with fittings, and mini air regulator.












### **Mobile Oil Packages – Cart**

 $\label{eq:linear_problem} \mbox{Air regulator (part 24H420-ordered separately) must be used for LD pump thermal relief function.}$ 







## **LD Series 5:1 Oil Pump Packages**









Ordering Information

## **Mobile Oil Packages - Dolly**

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.











## **Wall Mount Oil Packages**


Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.



24H836	24H842
5:1	5:1
24G588	24G588
55 gal drum	275 gal tote
24F935	24H666
-	24H859
24F910	24F910
3A1335	3A1335
	5:1 24G588 55 gal drum 24F935 — 24F910

## **Stationary Oil Packages**

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.





Package 24H842 installed on a 275 gallon tote (not included in package).

## **LD Series 5:1 Oil Pump Packages**










**Ordering Information** 

### Stationary Oil Packages - Tote

Standard packages include LD Series hose reel. Air regulator (part 24H420 - ordered separately) must be used for LD pump thermal relief function.



Package 24H894 installed on a 275 gallon tote (not included in package).











Instruction Manual

### **Deluxe Stationary Oil Packages – Tote**

Deluxe packages include SD Series hose reel. Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.





3A1335

3A1335

## **LD Series 5:1 Oil Pump Packages**









Ordering Information

## Oil Packages – Tank Mount

Air regulator (part 24H420 – ordered separately) must be used for LD pump thermal relief function.











### **Deluxe Oil Packages – Tank Mount**

Deluxe packages include SD hose reel, air and fluid hoses with fittings, and mini air regulator.



## **LD Series Oil Pump Accessories**









## >>> Ordering Information

## **Air Regulators**



Part Number	Description
24H420	Mini air pressure regulator with gauge, 1/4 in NPT x 3/8 in NPT, self-relieving

## **Carts**



Part Number	Description	
24F915	Drum cart with pneumatic wheels for 55 gallon drums, includes chain for securing drum to cart	

## **LD Drum Dollies**



	Part Number	Description	
131183 Drum dolly for 35 lb (16 kg) drum			
131184 Drum dolly for 120 lb (54 kg) drum		Drum dolly for 120 lb (54 kg) drum	
129645 Drum dolly for 400 lb (182 kg) drum			

### **Downtubes**

Oil Pumps and Packages



Part Number	Description
16F878	Universal cut to length PVC downtube
16F886	Drum length steel downtube
16F885	Tote length steel downtube

## **Drum Covers**



	Part Number	Description	
24F904 Cover for 35 lb (16 kg) pails			
	24F905 Cover for open-head 120 lb drums		
24F906 Cover for open-head 400 lb drums			

## **Hose and Fitting Kits**



Part Number	Description	Kit Includes			
Part Number	Description	Fluid Hose	Air Hose	Swivel	Union Fitting
24H865	15 ft LD pump fluid hose kit	1/2 in x 15 ft	3/8 in x 6 ft	157705	156684
24H859	6 ft LD pump fluid hose kit	1/2 in x 6 ft	3/8 in x 6 ft	157705	156684

## **Suction Kits**



	Part Number	Description	
LD oil pump suction hose kit for 55 gal (200 L) drum. Includes 55 gal (200 L) drum length madapter, foot valve and 6 ft of 1 in suction hose		LD oil pump suction hose kit for 55 gal (200 L) drum. Includes 55 gal (200 L) drum length metal downtube, bung adapter, foot valve and 6 ft of 1 in suction hose	
	LD oil pump suction hose kit for 275 gal (1,040 L) drum. Includes 275 gal (1,040 L) tote length metal downtubung adapter, foot valve and 6 ft of 1 in suction hose		
LD oil pump suction hose kit and adapter for mounting pump to the side of IBC tote and dispensing from Includes 1 in x 3 ft suction hose, 1 in elbow fitting and union fitting (160022)		LD oil pump suction hose kit and adapter for mounting pump to the side of IBC tote and dispensing from drain. Includes 1 in x 3 ft suction hose, 1 in elbow fitting and union fitting (160022)	









## **Mounting Hardware**

73.E	Part Number	Description
	24F910	LD Series pump wall mounting bracket
	24F918	Bung adapter

## **Tote Mount Accessories**

18	Part Number	Description	
	24F914	Meter drip tray for mounting to the side of IBC tote	
41	24F932	LD Series reel bracket for mounting reel to IBC top mount tote bracket (24F930 and 24F920)	
	24F931	Tote mounting bracket to mount reel on top of IBC tote (pump mounting bracket is not included)	
2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	24F930	Top of tote mounting bracket. For mounting LD Series pump in top of IBC tote.	
	24F920	Bracket for mounting LD Series pump on the side of IBC tote	
	24K285	Bracket for mounting SD Series hose reel to IBC tote mounting bracket 24F930 (24F930 bracket sold separately)	









# Perfect for Medium Pressure, Low-Volume Applications

You can't afford downtime, especially when your shop is small. The Mini Fire-Ball 225 is designed with fewer moving parts, which means less wear and tear and reduced downtime, allowing you to run a more profitable business.

## **Durable Casting**

Thick cast aluminum air motor housing offers unmatched durability.

### Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.

### Corrosion-Resistant

Corrosion-resistant design utilizes liquid salt nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

### Typical Applications


- · Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

### Typical Fluids Handled

· Petroleum- and synthetic-based oils (motor, gear and ATF)

## **Pump Performance**

### Mini Fire-Ball 225 3:1 Pumps
















## Ordering Information

## Mini Fire-Ball 225 3:1 Pumps

Part Number	Description	
246775	3:1 Universal oil pump	
248097	3:1 Universal oil pump with suction tube (15C502) and bung adapter (222308)	

## Mini Fire-Ball 225 3:1 Oil Pump Packages









### **Ordering Information**

### **Oil Packages**



<sup>\*</sup>Order low-level shut-off (203688) (1-1/2 in NPT) separately for metered dispense systems.

<sup>\*\*</sup>Order low-level shut-off (203688) (1-1/2 in NPT) separately for metered dispense systems. Use 3/8 in (9.5 mm) air regulator (109075) as required; must be ordered separately.









## **Bulk Oil Dispensing Packages**



<sup>\*</sup>Order (218549) (1/2 in x 24 in) hose kit separately.

N.T









## Ideal for Medium-Sized Shops with High-Pressure Oil Transfer

Install the Fire-Ball 300 in high-pressure, medium-volume oil dispense applications such as automotive dealerships, fast lube centers and service shops. A three inch differential air motor ensures smooth pumping, and the smooth double-acting pump design provides reliable fluid flow and accurate dispense.

### **Durable Casting**

Thick cast aluminum air motor housing offers unmatched durability.

## Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.

### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

### Corrosion-Resistant

Corrosion-resistant design utilizes liquid nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

### Typical Applications


- · Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

### Typical Fluids Handled

 Petroleum- and synthetic-based oils (motor, gear and ATF)

## Pump Performance

### Fire-Ball 300 5:1 Pumps



### Inlet Air Pressures:











echnical Specifications			
Fluid Pressure Ratio	5:1		
Air Motor Effective Diameter	3 in (76.2 mm)		
Maximum Fluid Working Pressure	900 psi (62 bar / 6.2 MPa)		
Approximate Free Flow Rate @ 100 psi	12.1 gal/min (46 liters/min)		
Output per Cycle	133 cc		
Approximate Air Use and Flow @ 100 psi (80 cpm)	16 scfm @ 2.8 gpm (0.45 m³/min @ 10.6 lpm)		
Air Inlet	3/8 in NPT(F)		
Fluid Inlet	1-1/2 in NPT(F)		
Fluid Outlet	1/2 in NPT(F)		
Air Operation Range	40 psi to 180 psi (2.8 bar to 12 bar)		
Maximum Recommended Pump Speed	70 cpm		
Cycles per Gallon (Liter)	28.4 (7.5)		
Wetted Parts	Steel, polyurethane, aluminum, Buna-N		
Sound Pressure Level	77.8 dB(A)		
Sound Power Level	85.6 dB(A)		
Approximate Weight	17 lb (7.7 kg)		
Instruction Manual	306518		

## >>> Ordering Information

## Fire-Ball 300 5:1 Pumps

Part Number	Description
203876	5:1 Universal oil pump
203872	5:1 Oil pump, 16 gal (120 lb) drum size, for cover mount
203857	5:1 Oil pump, 55 gal (400 lb) drum size, for cover mount
204254	5:1 Oil pump, 55 gal (400 lb) drum size, bung mount
222087	5:1 Oil pump, 275 gal (1,040 lb) tank size, bung mount

## Fire-Ball 300 5:1 Oil Pump Packages









**Ordering Information** 

### **Oil Pump Packages**



<sup>\*</sup>Order low-level cut-off (203688) (1-1/2 in NPT) separately for metered dispense systems. Use 3/8 in (9.5 mm) installation kit (224512) as required.

<sup>\*\*</sup>Order low-level cut- off (203688) (1-1/2 in NPT) separately for metered dispense systems. Use 3/8 in (9.5 mm) air regulator (109075) as required; must be ordered separately.









## **Bulk Oil Dispensing Packages**







Package Number	241633*	224541*	244038*	224534*
Ratio	5:1	5:1 5:1		5:1
Dispensing Location	-	-	-	Bench/Top Tank
Pump	203876	203876	203876	203876
Regulator/Gauge	109075	109075	109075	109075
Nipple	156849	156849	156849	156849
Bung Adapter	222308	222308	222308	222308
Reel Size	1/2 in x 35 ft	1/2 in x 50 ft	1/2 in x 50 ft	1/2 in x 50 ft
Reel Type	SD	SD	SD	SD
Hose Reel	HPM33B	HPM65B	HPM65B	HPM65B
Type of Meter	SD	SD	SD	SD
Manual/Preset	Manual	Manual	Preset	Manual
Meter	25M404	25M404	26C384	25M404
90° Swivel	-	-	-	157416
Air Filter	-			106148
Drain Valve	-	-	-	127711
Hose	-	220598	220598	222063
Thermal Relief Valve	-	-	-	237893
Hose Reel Inlet Kit (Not Included)	218549	218549 218549		218549

<sup>\*</sup>Order (218549) (1/2 in x 24 in) hose reel inlet kit separately.



Package 224534 installed on a bulk tank (not included in package).

## Fire-Ball 300 5:1 Oil Pump Packages









## **Lube Truck Packages**



222086*	206655*	204264*
5:1	5:1	5:1
Lube truck	Lube truck	Lube truck
16 gal (60l) open-head	55 gal (2001) closed-head	55 gal (2001) closed-head
203872	203857	204254
222063	222063	222063
1/2 in x 6 ft (12.7 mm x 1.8 m)	1/2 in x 6 ft (12.7 mm x 1.8 m)	1/2 in x 6 ft (12.7 mm x 1.8 m)
222060	207367	-
-	-	204095
222061	207361	207361
-	-	224579
307883	307883	307883
	5:1  Lube truck  16 gal (60l) open-head  203872  222063  1/2 in x 6 ft (12.7 mm x 1.8 m)  222060  -  222061  -	5:1     5:1       Lube truck     Lube truck       16 gal (60l) open-head     55 gal (200l) closed-head       203872     203857       222063     222063       1/2 in x 6 ft (12.7 mm x 1.8 m)     (12.7 mm x 1.8 m)       222060     207367       -     -       222061     207361       -     -

 $<sup>^*\</sup>mbox{Order }3/8$  in (9.5 mm) air regulator and gauge (109075) separately.









## The Pump of Choice for Your Most **Demanding High-Volume Applications**

The Fire-Ball 425 features a 4.25 inch air motor to supply the power you need for long pipe runs and highervolume dispensing. An ideal choice for applications where multiple dispenses happen at the same time.

## **Durable Casting**

Thick cast aluminum air motor housing offers unmatched durability.

### Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.

## Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

### Corrosion-Resistant

Corrosion-resistant design utilizes liquid nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

### **Typical Applications**

- · Automotive dealerships
- · Fast lube centers
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

### Typical Fluids Handled

· Petroleum- and synthetic-based oils (motor, gear and ATF)









### **Pump Performance**


## Fire-Ball 425 3:1 Pumps



## Fire-Ball 425 6:1 Pumps



## Fire-Ball 425 10:1 Pumps







(A) (B) (C) (C)	= 150 ps (10.3 b) = 100 ps (6.9 ba) = 70 psi (4.8 ba) = 40 psi	i ir)
_	(2.8 ba	r)

hnical Specifications			
Fluid Pressure Ratio	3:1	6:1	10:1
Air Motor Effective Diameter	4.25 in (107.9 mm)	4.25 in (107.9 mm)	4.25 in (107.9 mm)
Maximum Fluid Working Pressure	540 psi (37 bar / 3.7 MPa)	1,100 psi (76 bar / 7.6 MPa)	1,800 psi (124 bar / 12.4 MF
Approximate Free Flow Rate @ 100 psi	28.7 gal/min (109 liters/min)	17.1 gal/min (65 liters/min)	11.7 gal/min (44 liters/mir
Output per Cycle	631 cc	261 cc	189 cc
Approximate Air Use and Flow @ 100 psi (80 cpm)	43 scfm @ 13.4 gpm (1.23 m³/min @ 50.6 lpm)	44 scfm @ 6.7 gpm (1.25 m³/min @ 25.4 lpm)	45 scfm @ 4.0 gpm (1.27 m³/min @ 15.2 lpm
Air Inlet	1/2 in NPT(F)	1/2 in NPT(F)	1/2 in NPT(F)
Fluid Inlet	1-1/2 in NPT(F)	1-1/2 in NPT(F)	1-1/2 in NPT(F)
Fluid Outlet	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)
Air Operation Range	40 psi to 180 psi (2.8 bar to 12 bar)	40 psi to 180 psi (2.8 bar to 12 bar)	40 psi to 180 psi (2.8 bar to 12 bar)
Maximum Recommended Pump Speed	66 cpm	78 cpm	60 cpm
Cycles per Gallon (Liter)	6 (1.6)	14.5 (3.8)	20 (5.3)
Wetted Parts	Steel, polyurethane, aluminum, nitrile	Steel, polyurethane, aluminum, nitrile	Steel, polyurethane, aluminum, nitrile
Sound Pressure Level	82 dB(A)	79.5 dB(A)	78 dB(A)
Approximate Weight	46 lb (20.9 kg)	35 lb (15.9 kg)	29 lb (13.2 kg)
Instruction Manual	308485	308608	308655

## Ordering Information

## Fire-Ball 425 Pumps

Part Number	Description
237526	3:1 Universal oil pump
238108	6:1 Universal oil pump
205626	10:1 Universal oil pump
222065	10:1 Oil pump, 55 gal (400 lb) drum size, cover mount
222095	10:1 Oil pump, 55 gal (400 lb) drum size, bung mount










### **Oil Pump Packages**



<sup>\*</sup>Order low-level cut-off (203688) (1-1/2 in NPT) separately for metered dispense systems.

<sup>\*\*</sup>Order low-level cut-off (203688) (1-1/2 in NPT) separately for metered dispense. Use 1/2 in (12.7 mm) air regulator (104266) and air pressure gauge (100960) as required; must be ordered separately.

## Fire-Ball 425 Oil Pump Packages









## >>> Ordering Information

## **Lube Truck Packages**




Package Number	206656*	222067*
Ratio	10:1	10:1
Package Type	Lube truck	Lube truck
Maximum Container Size	55 gal (200 l) closed-head	55 gal (200 l) closed-head
Pump	222065	222095
Dispense/ Hose Fitting Kit	222066	222066
Fluid Hose Size	1/2 in x 6 ft (12.7 mm x 1.8 m)	1/2 in x 6 ft (12.7 mm x 1.8 m)
Offset Cover	207367	_
Pump Clamp	-	204095
Hold Down Kit	207361	207361
Bung Adapter	-	224579
Instruction Manual	307883	307883

 $<sup>^{\</sup>star}\text{Order}$  1/2 in (12.7 mm) air regulator (104266) and gauge (100960) separately.









Inlet Air Press

=100 psi (6.9 bar)

B =70 psi (4.8 bar)

(2.8 bar)

TEST FLUID: No. 10 Weight Oil

## Fast-Ball 1:1 Oil Pumps








Technical Specifications	
Fluid Pressure Ratio	1:1
Air Motor Effective Diameter	1.4 in (35.6 mm)
Maximum Fluid Working Pressure	180 psi (12.5 bar / 1.25 MPa)
Approximate Free Flow Rate @ 100 psi	5 gal/min (19 liters/min)
Output per Cycle	151 cc
Approximate Air Use and Flow @ 100 psi (80 cpm)	7 scfm @ 3.1 gpm (0.20 m³/min @ 11.7 lpm)
Air Inlet	1/4 in NPT(F)
Fluid Inlet	1-1/2 in NPT(F)
Fluid Outlet	3/4 in NPT(F)
Air Operation Range	40 psi to 180 psi (2.8 bar to 12.4 bar)
Maximum Recommended Pump Speed	100 cpm
Cycles per Gallon	25 cpg
Cycles per Liter	6.6 cpl
Wetted Parts	CS, polyurethane
Sound Pressure Level	74.9 dB(A)
Sound Power Level	83.5 dB(A)
Approximate Weight	8 lb to 14 lb (3 kg to 7 kg)
Instruction Manual	307906

## Ordering Information

## **Pumps**



## **Pump Packages**



Use the quick-reference guide below to determine the part and accessory options available for our most popular oil pumps.

## **Oil Pump Mounting and Accessory Guide**

Pump	Fast-Ball 1:1	Mini Fire-Ball 225 3:1	Fire-Ball 300 5:1	Fire-Ball 425 3:1	Fire-Ball 425 6:1	Fire-Ball 425 10:1
Bung Adapter	222308	222308	222308	_	_	222308
Connection Hose Kit	222118 (18 in / 4537 cm) 222119 (72 in / 182.8 cm)	222062 (18 in / 45.7 cm) 222063 (72 in / 182.8 cm)	222062 (18 in / 45.7 cm) 222063 (72 in / 182.8 cm)	238246 (24 in / 60.9 cm)	238246 (24 in / 60.9 cm)	222068 (18 in / 4537 cm) 222066 (72 in / 182.8 cm)
Wall Mounting Bracket	203987	203987	203987	238245	238245	203987
Thermal Relief Kit*	_	235998	237893	237601	240429	240429
Air Regulator and Gauge	110147	109075	109075	104266 / 100960	104266 / 100961	104266 / 100962
Air Filter	110146	106148	106148	106149	106149	106149
Air Lubricator	110148	214847	214847	214848	214848	214848
Filter, Regulator, Lubricator, and Gauge	110149	110150	110150	217072	217072	217072
Airline Shutoff Valve	110223	110224	110224	110225	110225	110225
Fluid Shutoff Valve	108537	108458	108458	108537	108537	108537
Fluid Outlet Filter	240417	240417	240417	101078	-	_
Low-Level Cutoff	203688	203688	203688	203688	203688	203688
Suction Hose Kit	236054	236054	236054	_	_	_

<sup>\*</sup>Required



## >>> Ordering Information

## **Bleed-Type Air Shut-Off Valves**

0,00	Part Number	Description
	110223	1/4 in NPT
	110224	3/8 in NPT
	110225	1/2 in NPT
	110226	3/4 in NPT

## **Bung Adapters**

		Description	Compatible	Includes				
	Part Number		Pumps	Double Tap bushing	Bushing Sleeve	1 ft x 3/8 in Hose	90° 3/8 in Adapter	Thumb Screw
	222308	Allows direct mounting of all universal length and extended pumps to standard 2 NPT drum bung	Fast-Ball 1:1 Mini Fire-Ball 225 3:1 Fire-Ball 300 5:1 Fire-Ball 425 10:1	-	-	_	-	-
	187754	Acetal bung adapter	All pumps	_	-	_	-	100220
	176684	Bung adapter for suction kit 203992	-	-	-	-	-	100220
	238125	For mounting universal pumps to tanks	Mini Fire-Ball 225 3:1 Fire-Ball 300 5:1 Fire-Ball 425 10:1	191075	172405	238370	155494	-

## **Carts**

-	Part Number	Compatible Container Size
	203650	5 gal (20 l) 10 gal (40 l) 16 gal (60 l)
	222243	120 lb (55 kg)
	111470	55 gal (200 l)

## **Clamps**

Part Number	Description	Compatible Pumps
203156	Used to hold pump securely to the edge of an open top drum	Fast-Ball 1:1 Mini Fire-Ball 225 3:1 Fire-Ball 300 5:1 Fire-Ball 425 6:1 Fire-Ball 425 10:1
210880		Fire-Ball 300 5:1 Fire-Ball 425 10:1

## Dispense Kits for Mini Fire-Ball and Fire-Ball 300 Pumps


Part Number 237075	Part Number	Description	Hose Length	Includes		
	Fait Nullibei	реэсприон	Fluid Hose Manual SD Gear Lube Valve		Manual	
	237075	Use with portable lubricators powered by Fire-Ball 300 Pump	6 ft	220591	255349	307884



### **Downtube – Universal**

n	Part Number	Description
	150502	1-1/2 in ID tube marked for standard container lengths from 20 in to 41 in (.51 m to 1.04 m)


### **Drum Covers**




### **Drum Elevator**

<b>→</b>	Part Number	Part Number Description		Includes			
Part Nun	rait Nullibei	Description	Cover Support	Air Control Kit			
	241663	Air-powered elevator to speed up 55 gal (200 l) drum changes	207562	204385	207561		

### Fluid Shut-Off Valves



### **Fluid T-Strainers**



## >>> Ordering Information

## **Fluid Y-Strainers**



Part Number	Description
110877	1/2 in NPT inlet/outlet strainer, which filters material before entering the pump
110906	1/2 in NPT inlet/outlet strainer, replacement screen
101078	3/4 in NPT inlet/outlet strainer, which filters material before entering the pump
180199	3/4 in NPT inlet/outlet strainer, replacement screen
110878	1 in NPT inlet/outlet strainer, which filters material before entering the pump
110907	1 in NPT inlet/outlet strainer replacement screen

## Hose and Fitting Kits for Mini Fire-Ball 225 and Fire-Ball 300 5:1

			Connection	Includes				
	Part Number	Description	Length	Air Hose Swivel Elbow Fluid Hose Swivel E  204560 155494 220598 15545		Fluid Hose Swivel Elbow		
	222062	For connecting wall-mounted pumps to piping	18 in	204560	155494	220598	155470	
90	222063	Use with drum-mounted pumps	6 ft	203320	155494	220591	155470	

## **Hose and Fitting Kits for Fire-Ball 425 Pumps**



				Hose	Package Includes				
	Part Number	Description	Length	Air Hose	Air Hose Swivel Elbow	Fluid Hose	Fluid Hose Swivel Elbow	Manual	
	222068	For connecting wall- mounted Fire-Ball 425 10:1 pump to piping	15 in	218093	155470	109108	160327	306520	
	238246	For connecting wall- mounted Fire-Ball 425 3:1 and 6:1 pumps to piping	24 in	218903	155470	238247	160327	306520	
	222066	For use with drum- mounted Fire-Ball 425	6 ft	205418	155470	109105	160327	307883	

## >>> Ordering Information

## **Low-Level Cutoffs for Fast-Ball and Fire-Ball Pumps**

Part Number	Description
203688	1-1/2 in NPT cutoff, which prevents air from entering pump when fluid supply from pump is exhausted

### **Portable Bases**

60	Part Number	Description	Compatible Container Size
	205054	Band dolly	5 gal (20 l)
è-é	204144	Band dolly	10 gal (40 l) 16 gal (60 l)
	203622	Caster base	5 gal (20 l) 10 gal (40 l) 16 gal (60 l)

### **Runaway Valve**

Prevents pump damage by automatically closing the air line to stop the pump when a runaway pump condition occurs due to an empty barrel or hose leak.

7	Part Number	Inlet
po gr	224040	3/4 in NPT(fbe)

## **Sealed Bung Adapters**

Part Number	Fire-Ball Length	Adapter Inside Diameter	Compatible Pumps
204076	Full length	2.140 in	Mini Fire-Ball 225 3:1
224579	Universal length	2.159 in	All except Mini Fire-Ball 225 3:1

### **Suction Kits**

	Part Number	Description	Includes			
[ ]	Fait Nullibei	Description	Bung Adapter		6 ft Hose	
	236054	Allows use of Fast-Ball, Mini-Fire-Ball and Fire-Ball universal pumps to work with barrels	188845	101496	109105	

## **Oil Pump Accessories**

## >>> Ordering Information

## **Suction Tubes**



Part Number	Container Size Type of Mount	Compatible Pumps		Includes		
Fait Number	Goritainer Size	Type of Mount		Extension Size	Extension	Foot Spacer
238592	16 gal (60 l)	Cover-mounted	Fast-Ball 1:1 Mini Fire-Ball 225 3:1 Fire-Ball 300 5:1 Fire-Ball 425 10:1	14-1/2 in	191126	110127
238593	55 gal (200 l)	Cover-mounted		21-3/4 in	191128	110127
238595	55 gal (200 l)	Bung-mounted		26 in	191130	110127
238596	275 gal (1,100 l)	Bung-mounted	1 110 Daii 423 10.1	36 in	191131	110127

## **Thermal Relief Valve Kits**



Part Number		Pressure Rating	Compatible Pumps	Includes			
	Fait Nullibei	Fressure nating	Companible Fumps	Valve	Bung Adapter	Swivel	6 ft Hose
	235998	600 psi (41 bar)	Mini Fire-Ball 225 3:1	112174	191075	155494	238370
	237893	900 psi (62 bar)	Fire-Ball 300 5:1 Fire-Ball 425 6:1	112174	191075	155494	238370
	248296	900 psi (62 bar)	Fire-Ball 300 5:1 Fire-Ball 425 6:1	102527	_	-	109163
	237601	600 psi (41 bar)	Fire-Ball 425 3:1	113053	191075	155494	238370
	240429	1,600 psi (110 bar)	Fire-Ball 425 10:1	102527	191075	155494	238370
	248324	1,600 psi (110 bar)	Fire-Ball 425 10:1	113053	_	-	109163

## **Tools for Working on Fire-Ball Air Motors**



Part Number	Description
207579	Padded pliers
171818	Poppet gauge

## **Wall-Mounting Brackets**



Part Number	Description	Compatible Pumps
203987	Clamps onto universal pump tube	Fast-Ball 1:1 Mini Fire-Ball 300 3:1 Fire-Ball 300 5:1 Fire-Ball 425 10:1
238245	Mounts directly to pump flange	Fire-Ball 425 3:1, 6:1, 10:1
236778	Provides mounting to wall surface by flange	Fire-Ball 425 3:1









Tested to outperform and outlast all other pumps on the market — with its long-life design and intuitive, easy-to-use controls — the NXT High-Flo pump is the best value for the money. Fewer parts, faster repairs and long-lasting durability.



Intuitive, easy-to-use DataTrak control gives you pump diagnostics, material usage tracking and pump runaway protection.

### **NXT Air Motor**

Modular design for easier maintenance with rugged body armor that won't rust or dent.

### Modular Air Valves

Easy-to-repair valve eliminates stalling and contains de-icing controls.

## Integrated Air Controls

Easy-turn, lockable regulator is front-mounted for easy access. Compact and modular with built-in filtration.

## Piston Valve with Floating Piston Seal

For maximum pressure balance over a range of material viscosities.

### **Typical Applications**

- Fleet service facilities
- In-plant
- Mining

### Typical Fluids Handled

• Petroleum- and synthetic-based oils (motor, gear and ATF)











### **Pump Performance**

## **NXT 3.5:1 High-Flo Pumps**






## **NXT 4.5:1 High-Flo Pumps**





## **NXT 6:1 High-Flo Pumps**





nnical Specifications			
Fluid Pressure Ratio	3.5:1	4.5:1	6:1
Air Motor Effective Diameter	7.5 in (191 mm)	7.5 in (191 mm)	10.375 in (264 mm)
Maximum Fluid Working Pressure	350 psi (24 bar / 2.4 MPa)	450 psi (31 bar / 3.1 MPa)	500 psi (34 bar / 3.4 MPa)
Output per Cycle	2,000 cc	1,500 cc	2,000 cc
Air Inlet	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)
Fluid Inlet	1-1/2 in NPT(F)	1-1/2 in NPT(F)	2 in NPT(F)
Fluid Outlet	1 in NPT(F)	1 in NPT(F)	2 in NPT(F)
Air Operation Range	20 psi to 100 psi (1.4 bar to 7 bar)	20 psi to 100 psi (1.4 bar to 7 bar)	20 psi to 75 psi (1.4 bar to 5.2 bar)
Maximum Recommended Pump Speed	60 cpm	60 cpm	60 cpm
Cycles per Gallon (Liter)	1.9 (0.5)	2.5 (0.67)	1.9 (0.5)
Wetted Parts	Stainless steel, PTFE, leather, UHMWPE, carbon steel	Stainless steel, PTFE, leather, UHMWPE, carbon steel	Stainless steel, PTFE, leath UHMWPE, carbon steel
Sound Pressure Level	77 dB(A)	77 dB(A)	80 dB(A)
Sound Power Level	87 dB(A)	87 dB(A)	90 dB(A)
Approximate Weight	99 lb (44.9 kg)	99 lb (44.9 kg)	178 lb (80.7 kg)
Instruction Manuals	System – 312862 Pump – 311211 Pump Lower – 311690 Motor – 311238	System – 312862 Pump – 311211 Pump Lower – 311690 Motor – 311238	System – 312862 Pump – 311831 Pump Lower – 311832 Motor – 311238









## Oil Pump Packages with DataTrak

Package Number with DataTrak	247888	247889	247892	247893
Ratio	3.5:1	4.5:1	6:1	6:1
Mounting	255143 (Wall)	255143 (Wall)	255143 (Wall)	218742 (Stand)
Pump with DataTrak and Thermal Relief Kit	24D590	24D591	24D594	24D594
Output per Cycle	2,000 cc	1,500 cc	2,000 cc	2,000 cc
Output at 60 CPM	31.5 gpm (119.2 lpm)	23.2 gpm (87.8 lpm)	31.5 gpm (119.2 lpm)	31.5 gpm (119.2 lpm)
Motor Size	NXT 3400	NXT 3400	NXT 6500	NXT 6500
Maximum Fluid Pressure	350 psi (24.1 bar)	450 psi (31 bar)	500 psi (35.2 bar)	500 psi (35.2 bar)
Maximum Air Input Pressure	100 psi (6.9 bar)	100 psi (6.9 bar)	75 psi (5.2 bar)	75 psi (5.2 bar)
System Manual	312862	312862	312862	312862
Pump Manual	311211	311211	311831	311831
Pump Lower Manual	311690	311690	311832	311832
Motor Manual	311238	311238	311238	311238
Pump Inlet Size	1-1/2 in NPT	1-1/2 in NPT	2 in NPT	2 in NPT
Pump Outlet Size	1 in NPT	1 in NPT	2 in NPT	2 in NPT
4 ft x 3/4 in Air Hose	110048	110048	110048	110048
6 ft x 1 in Fluid Hose	115042	115042	247969	247969
Instruction Manual	309351	309351	307883	306520

## Oil Pump Packages without DataTrak

Package Number without DataTrak	24D602	24D603	24D606	24D607
Ratio	3.5:1	4.5:1	6:1	6:1
Mounting	255143 (Wall)	255143 (Wall)	255143 (Wall)	218742 (Stand)
Pump without DataTrak and Thermal Relief Kit	24D596	24D597	24D600	24D600
Output per Cycle	2,000 cc	1,500 cc	2,000 cc	2,000 cc
Output at 60 CPM	31.5 gpm (119.2 lpm)	23.2 gpm (87.8 lpm)	31.5 gpm (119.2 lpm)	31.5 gpm (119.2 lpm)
Motor Size	NXT 3400	NXT 3400	NXT 6500	NXT 6500
Maximum Fluid Pressure	350 psi (24.1 bar)	450 psi (31 bar)	500 psi (35.2 bar)	500 psi (35.2 bar)
Maximum Air Input Pressure	100 psi (6.9 bar)	100 psi (6.9 bar)	75 psi (5.2 bar)	75 psi (5.2 bar)
System Manual	312862	312862	312862	312862
Pump Manual	311211	311211	311831	311831
Pump Lower Manual	311690	311690	311832	311832
Motor Manual	311238	311238	311238	311238
Pump Inlet Size	1-1/2 in NPT	1-1/2 in NPT	2 in NPT	2 in NPT
Pump Outlet Size	1 in NPT	1 in NPT	2 in NPT	2 in NPT
4 ft x 3/4 in Air Hose	110048	110048	110048	110048
6 ft x 1 in Fluid Hose	115042	115042	247969	247969
Instruction Manual	309351	309351	307883	306520













## Optional DataTrak™ Control

Intuitive, easy-to-use DataTrak control gives you pump diagnostics, material usage tracking and pump runaway protection.

### **NXT Air Motor**

Modular design for easier maintenance with rugged body armor that won't rust or dent.

### Modular Air Valves

Easy-to-repair valve eliminates stalling and contains de-icing controls.

## Integrated Air Controls

Easy-turn, lockable regulator is front-mounted for easy access. Compact and modular with built-in filtration.

## Piston Valve with Floating Piston Seal

For maximum pressure balance over a range of material viscosities.

### **Typical Applications**

- · Fleet service facilities
- In-plant
- Mining

### Typical Fluids Handled

• Petroleum- and synthetic-based oils (motor, gear and ATF)








#### **Pump Performance**


#### Inlet Pressures:




= 40 psi (2.8 bar) air pressure or 600 (41 bar) hydraulic oil pressure

TEST FLUID: No. 10 Weight Oil


#### **NXT Dura-Flo 6:1 Pumps**




#### **NXT Dura-Flo 12:1 Pumps**



#### **NXT Dura-Flo 10:1 Pumps**



#### **NXT Dura-Flo 23:1 Pumps**



# **NXT Dura-Flo Pumps**







nnical Specifications				
Fluid Pressure Ratio	6:1	10:1	12:1	23:1
Air Motor Effective Diameter	7.5 in (191 mm)	10.375 in (264 mm)	7.5 in (191 mm)	10.375 in (264 mm)
Maximum Fluid Working Pressure	620 psi (43 bar / 4.3 MPa)	1,180 psi (81 bar / 8.1 MPa)	1,190 psi (82 bar / 8.2 MPa)	1,725 psi (119 bar / 11.9 MPa)
Output per Cycle	1,000 cc	1,000 cc	580 cc	580 cc
Air Inlet	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)
Fluid Inlet	2 in NPT(F)	2 in NPT(F)	2 in NPT(F)	2 in NPT(F)
Fluid Outlet	1-1/2 in NPT(F)	1-1/2 in NPT(F)	1-1/2 in NPT(F)	1-1/2 in NPT(F)
Air Operation Range	20 psi to 100 psi (1.4 bar to 7 bar)	20 psi to 100 psi (1.4 bar to 7 bar)	20 psi to 100 psi (1.4 bar to 7 bar)	20 psi to 75 psi (1.4 bar - 5.2 bar)
Maximum Recommended Pump Speed	60 cpm	60 cpm	60 cpm	60 cpm
Cycles per Gallon (Liter)	3.8 (1.0)	3.8 (1.0)	6.5 (1.72)	6.5 (1.72)
Wetted Parts	Stainless steel, CS, chrome, zinc, nickel, Buna-N, tungsten carbide, nylon, UHMWPE, leather, PTFE, PEEK	Stainless steel, CS, chrome, zinc, nickel, Buna-N, tungsten carbide, nylon, UHMWPE, leather, PTFE, PEEK	Stainless steel, CS, chrome, zinc, nickel, tungsten carbide, ductile iron, acetal	Stainless steel, CS, chrome, zinc, nickel, tungsten carbide, ductile iron, acetal
Sound Pressure Level	77 dB(A)	80 dB(A)	77 dB(A)	80 dB(A)
Sound Power Level	87 dB(A)	90 dB(A)	87 dB(A)	90 dB(A)
Approximate Weight	113 lb (51.3 kg)	132 lb (59.9 kg)	92 lb (41.7 kg)	102 lb (46.3 kg)
Instruction Manuals	System – 312862 Pump – 311833 Pump Lower – 311717 Motor – 311238	System – 312862 Pump – 311833 Pump Lower – 311717 Motor – 311238	System – 312862 Pump – 311826 Pump Lower – 311825 Motor – 311238	System – 312862 Pump – 311826 Pump Lower – 311829 Motor – 311238









# Ordering Information

# Oil Pump Packages with DataTrak

Package Number with DataTrak	247890	247894	247891	247895
Ratio	6:1	10:1	12:1	23:1
Mounting	255143 (Wall)	255143 (Wall)	255143 (Wall)	255143 (Wall)
Pump with DataTrak and Thermal Relief Kit	24D592	24D595	24D593	-
Output per Cycle	1,000 cc	1,000 cc	580 cc	580 cc
Output at 60 CPM	17.4 gpm (65.9 lpm)	17.4 gpm (65.9 lpm)	9.2 gpm (34.8 lpm)	9.2 gpm (34.8 lpm)
Motor Size	NXT 3400	NXT 6500	NXT 3400	NXT 6500
Maximum Fluid Pressure	620 psi (42.7 bar)	1,180 psi (81.3 bar)	1,190 psi (82.1 bar)	1,725 psi (118.9 bar)
Maximum Air Input Pressure	100 psi (6.9 bar)	100 psi (6.9 bar)	100 psi (6.9 bar)	75 psi (5.2 bar)
System Manual	312862	312862	312862	312862
Pump Manual	311833	311833	311826	311826
Pump Lower Manual	311717	311717	311825	311825
Air Motor Manual	311238	311238	311238	311238
Pump Inlet Size	2 in NPT	2 in NPT	2 in NPT	2 in NPT
Pump Outlet Size	1-1/2 in NPT	1-1/2 in NPT	1-1/2 in NPT	1-1/2 in NPT
4 ft x 3/4 in Air Hose	110048	110048	110048	110048
6 ft x 1 in Fluid Hose	115042	115042	115042	115042
Instruction Manual	312862	312862	312862	312862

# Oil Pump Packages without DataTrak

Package Number without DataTrak	24D604	24D608	24D605
Ratio	6:1	10:1	12:1
Mounting	255143 (Wall)	255143 (Wall)	255143 (Wall)
Pump without DataTrak and Thermal Relief Kit	24D598	24D601	24D599
Output per Cycle	1,000 cc	1,000 cc	580 cc
Output at 60 CPM	17.4 gpm (65.9 lpm)	17.4 gpm (65.9 lpm)	9.2 gpm (34.8 lpm)
Motor Size	NXT 3400	NXT 6500	NXT 3400
Maximum Fluid Pressure	620 psi (42.7 bar)	1,180 psi (81.3 bar)	1,190 psi (82.1 bar)
Maximum Air Input Pressure	100 psi (6.9 bar)	100 psi (6.9 bar)	100 psi (6.9 bar)
System Manual	312862	312862	312862
Pump Manual	311833	311833	311826
Pump Lower Manual	311717	311717	311825
Air Motor Manual	311238	311238	311238
Pump Inlet Size	2 in NPT	2 in NPT	2 in NPT
Pump Outlet Size	1-1/2 in NPT	1-1/2 in NPT	1-1/2 in NPT
4 ft x 3/4 in Air Hose	110048	110048	110048
6 ft x 1 in Fluid Hose	115042	115042	115042
Instruction Manual	312862	312862	312862











# Field-Proven, Energy-Efficient

Hydraulic Dyna-Star pumps provide reliable, quiet, ice-free performance at maximum pressure and low-flow rates and are up to three times more energy efficient than comparable compressed-air systems.

## **Built-In Reliability**

Self-lubricating vertical design for long life and reliable operation in high vibration environments.

#### **Quiet Hydraulic Motor**

No need for add-on mufflers.

# **High-Efficiency Motor**

Uses less hydraulic oil.

#### **Typical Applications**

- Service shops
- · Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

· Petroleum- and synthetic-based oils (motor, gear and ATF)

chnical Specifications				
Fluid Pressure Ratio	1:1	1:1	1/4:1	1:1 Stainless Steel
Pump Number	224741	224742	236753	237653
Applications	Oil dispensing	Oil dispensing	Bulk oil transfer	Anti-freeze dispensing
Drum Size	Universal	55 gal (200 l) Bung- or cover-mounted	Universal	Universal
Maximum Input Pressure	1,500 psi (102 bar)	1,500 psi (102 bar)	1,500 psi (102 bar)	1,000 psi (70 bar)
Maximum Fluid Input Volume	3 gpm (11.4 lpm)	3 gpm (11.4 lpm)	3 gpm (11.4 lpm)	3 gpm (11.4 lpm)
Maximum Output Flow Rate	3 gpm (11.4 lpm)	3 gpm (11.4 lpm)	10 gpm (37.9 lpm)	3 gpm (11.4 lpm)
Maximum Recommended CPM	60	60	60	60
Maximum Fluid Output Pressure	1,500 psi (102 bar)	1,500 psi (102 bar)	375 psi (25.1 bar)	1,500 psi (102 bar)
Hydraulic Supply Inlet	3/8 in NPT	3/8 in NPT	3/8 in NPT	3/8 in NPT
Hydraulic Return Outlet	3/4 in NPT	3/4 in NPT	3/4 in NPT	3/4 in NPT
Fluid Outlet	1/2 in NPT	1/2 in NPT	1/2 in NPT	1/2 in NPT
Fluid Inlet	1-1/2 in NPT	1-1/2 in NPT	1-1/2 in NPT	3/4 in NPT
Maximum Incoming Fluid Temp.	130°F (54°C)	130°F (54°°C)	130°F (54°C)	130°F (54°C)
Wetted Parts	Steel, copper, leather	Steel, copper, leather	Aluminum, steel, nitrile, polyurethane	Steel, copper, leather
Sound Pressure Level	77 dB(A)	77 dB(A)	77 dB(A)	77 dB(A)
Approximate Weight	24 lb (10.9 kg)	24 lb (10.9 kg)	48 lb (21.8 kg)	24 lb (10.9 kg)
Instruction Manual	308155	308155	308390	308155







# >>> Ordering Information

# **Dyna-Star Hydraulic Pumps**

Part Number	Description
224741	1:1 Universal oil pump
224742	1:1 Oil pump for 55 gal (400 lb) drum size, bung- or cover- mounted
236753	1/4:1 Universal oil pump
237653	1:1 Universal stainless steel oil pump

#### **Accessories**

# **Drum Covers**



Part Number	Description
200326	For 55 gal (200 l) drums
204574	For 16 gal (60 l) drums
222058	For 5 gal (20 I) pails
160754	For 5 gal (20 l), 16 gal (60 l) and 55 gal (200 l) bung-mounted pumps

#### **Hydraulic Fluid Controls**

Required for each pump.

2.27	Part Number	Description
	236864	Dyna-Star fluid controls [1,500 psi (102 bar); 3 gpm (11.4 lpm)]. Includes manifold with pressure-reducing valve, flow-control valve, pressure gauge, shut-off ball valves, and 3 ft (0.9 m) supply and return hoses. Instruction manual 308395.
35.5	237904	1:1 Dyna-Star thermal relief valve, 1,600 psi (110 bar)

# **Wall-Mounting Brackets**



Part No	umber	Description
2039	987	For stubby/universal 1:1 Dyna-Star pump
236	778	For stubby/universal 1/4:1 Dyna-Star pump









# Field Proven, Energy Efficient

Hydraulic Power-Star pumps provide reliable, quiet, ice-free performance at maximum pressure and low flow rates and are up to three times more energy efficient than comparable compressed-air systems.

#### **Built-In Reliability**

Self-lubricating vertical design for long life and reliable operation in high vibration environments.

# **Quiet Hydraulic Motor**

No need for add-on mufflers.

# **High-Efficiency Motor**

Uses less hydraulic oil.

#### **Typical Applications**

- Service shops
- · Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

#### Typical Fluids Handled

• Petroleum- and synthetic-based oils (motor, gear and ATF)

ec	echnical Specifications		
	Fluid Pressure Ratio	1:1	
	Pump Number	236754	
	Applications	Bulk oil transfer	
	Drum Size	Universal	
	Maximum Input Pressure	1,500 psi (102 bar)	
	Maximum Fluid Input Volume	12 gpm (45.4 lpm)	
	Maximum Output Flow Rate	12 gpm (45.4 lpm)	
	Maximum Recommended CPM	60	
	Maximum Fluid Output Pressure	1,500 psi (102 bar)	
	Hydraulic Supply Inlet	3/4 in NPT	
	Hydraulic Return Outlet	1-1/4 in NPT	
	Fluid Outlet	1/2 in NPT	
	Fluid Inlet	1-1/2 in NPT	
	Maximum Incoming Fluid Temp.	130°F (54°C)	
	Wetted Parts	Iron, steel, stainless steel, nitrile, polyurethane	
	Sound Pressure Level	78 dB(A)	
	Approximate Weight	100 lb (45.4 kg)	
	Instruction Manual	308391	







# >>> Ordering Information

# **Power-Star Hydraulic Pumps**

Part	Number	Description
23	36754	1:1 Universal oil pump

#### **Accessories**

# **Drum Covers**



Part Number	Description
200326	For 55 gal (200 l) drums
204574	For 16 gal (60 l) drums
222058	For 5 gal (20 I) pails
160754	For 5 gal (20 l), 16 gal (60 l) and 55 gal (200 l) bung-mounted pumps

# **Hydraulic Fluid Controls**

Required for each pump.



Part Number	Description
236865	Power-Star fluid controls [1,500 psi (102 bar); 12 gpm (45.4 lpm)]. Includes manifold with pressure-reducing valve, flow-control valve, pressure gauge, shut-off ball valves, and 3 ft (0.9 m) supply and return hoses. Instruction manual 308395.

# **Wall-Mounting Bracket**



Part Number	Description
236778	For stubby/universal 1/4:1 Power-Star pump









#### **Ordering Information**

#### 16 Gallon (60 I) Metered and Non-Metered Dispensing Packages

Designed for manual dispensing of fluid oil from bulk containers to point of application.



<sup>\*</sup>Hydraulic; can be used for gear oil dispensing.









#### Pail-Dispensing Package for 5 gal (20 I) Pails

Mounts on top of standard 5 gal (20 l) pail (pail not included). Dispenses 1.6 oz to 1.9 oz. (47.3 ml to 56.2 ml) per stroke.



Package Number	226289	
Fluids Handled	Gear lube	
Fluid Hose	4 ft (1.2 m)	
Instruction Manual	306875	

# Pumping Bulk Lubricants from 16 gal (60 l) or 55 gal (200 l) Drums\*

All pumps come with suction tube and bung adapter.




Package Number	114829	226290
Type of Pump	Lever <sup>(1)</sup>	Rotary <sup>(2)</sup>
Fluids Handled	Petroleum-based products, anti-freeze	Petroleum-based products
Delivery Rate	0.1 gal (0.4 l) per downstroke	1 gal (3.7 l) per 18 cycles
Fluid Hose	-	-
Instruction Manual	-	306876

<sup>\*</sup>Drums not included.

<sup>1</sup> Telescopic suction tube mounts 2 in NPT bung opening of 16 gal (60 l) or 55 gal (200 l) drum. Package includes bung adapter and spout outlet

<sup>2</sup> Package has adjustable 2 in NPT bung mounting to allow use with either 16 gal (60 l) or 55 gal (200 l) drum. Package includes bung adapter and spout outlet

Notes	



# **Graco Dispense Meters**

	Fluid	Manual/ Preset	Maximum Working Pressure	Maximum Flow Rate	Intended Use	Warranty	Reference Pages
LDP5 Electronic Preset Meters	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	Preset	1,000 psi (69 bar)	5 gpm (19 lpm)	Indoor	5 years overall (2 years electronics)	85-87
EM Series Electronic Meters	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	Manual	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	5 years overall (3 years electronics)	88-90
SD Series Electronic Meters	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	Manual/ Preset	1,500 psi (103.4 bar)	14 gpm (53 lpm)	Indoor/ Limited Outdoor	7 years overall (3 years electronics)	91-93
IM5 In-Line Meters	Petroleum- and synthetic-based oils (motor, gear and ATF) Anti-freeze Windshield wash fluid	In-Line	500 psi (34 bar)	5 gpm (19 lpm)	Indoor/ Outdoor	5 years overall (2 years electronics)	94
IM20 In-Line Meters	Petroleum- and synthetic-based oils (motor, gear and ATF) Anti-freeze	In-Line	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	5 years overall (3 years electronics)	95
SDI15 In-Line Meters	Petroleum- and synthetic-based oils (motor, gear and ATF) Anti-freeze Diesel exhaust fluid	In-Line	1,500 psi (103.4 bar)	15 gpm (56.8 lpm)	Indoor	7 years overall (3 years electronics)	96
Mechanical Meters	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	Manual/ Preset	1,500 psi (103.4 bar)	8 gpm (30 lpm)	Indoor/ Outdoor	5 years	97-99
SDV15 Control Valves	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	N/A	1,500 psi (103.4 bar)	15 gpm (56.8 lpm)	Indoor/ Outdoor	7 years	100-101
XDV20 Control Valves	Petroleum- and synthetic-based oils (motor, gear and ATF)     Anti-freeze	N/A	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	7 years	102-103











For use in small service shops, fast lubes and low-volume in-plant applications.



Keeps dispenses precise.

## **Operator Controls**

Displays in quarts, pint, gallons or liters. Durable switches for long life.



Fluid Swivel

1/2 inch fluid inlet.

Technical Specifications
Flow Range\*

Wetted Parts

Weight

Warranty

Meter Pressure Loss\*

Instruction Manual

Dimensions (without extension)

Maximum Working Pressure



Choose from rigid or flexible extensions with automatic thermal compensating nozzle.

#### Rugged Meter Body

Superior impact resistance and long life.

#### Comfortable Handle

Ergonomically designed for operator comfort. Two-finger trigger with latching on preset models.

#### **Typical Applications**

- · Automotive dealerships
- · Fast lube centers
- Service shops
- · Fleet services facilities
- In-plant

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- · Anti-freeze

Units of Measure	Quarts, pints, gallons, liters (factory set to quarts)
Accuracy**	+/- 0.5%
Inlet	1/2 in NPT
Outlet	1/2 in NPT
Maximum Totalizer	999,999 gallons or liters
Maximum Recorded Dispense	999.9 units
Maximum Preset Volume	999.9 units (LDP5 only)
Operating Temperature Range	32°F to 120°F (0°C to 48.8°C)
Storage Temperature Range	-30°F to 120°F (-34.4°C to 48.8°C)
Outdoor Use	No
Battery	9 volt alkaline
Battery Life	One year

0.1 gpm to 5 gpm (0.4 lpm to 19 lpm)

1,000 psi (69 bar)

3 lb (1.36 kg)

312668

SST, nitrile rubber, zinc, CS, LCP

90 psi (6.2 bar) @ 5 gpm (19 lpm)

Five years overall, two years electronics

11 in L x 3.25 in W x 3.25 H (28 cm L x 8.3 cm W x 8.3 cm H)

 $<sup>^{\</sup>star}$ Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature, viscosity, inlet and nozzle type.

<sup>\*\*</sup>At 2.5 gpm (9.5 lpm) @ 70°F (21°C) with 10 wt. oil and 1 gal (3.8 l) dispensed. May require recalibration. Out-of-box accuracy ±1.25%. Not recommended for in-line installation.











# Ordering Information

# **LDP5 Electronic Preset Meters**

Automatic nozzle included

	Extension	Inlatin (man)	Part Number	Package Includes	
	EXTENSION	Inlet in (mm)	Part Number	Trigger Guard	Swivel Cover
A	Flexible		258694	Yes	Yes
	Rigid	1/2 (13)	256216	Yes	Yes
P	Flexible		255277	No	No

# **Nozzle Extension Kits**

Extension	Fluid	Nozzle Description	Part Number
	Oil/Anti-freeze	Automatic, thermally compensating	239949
Rigid	Gear lube	Automatic, thermally compensating	239950
	Gear lube	Automatic	238887
Flexible	Oil/Anti-freeze	Automatic, thermally compensating	239951
Nozzle Only	Oil/Anti-freeze/Gear lube	Automatic, thermally compensating	239829
ivozzie Offiy	Oil/Anti-freeze/Gear lube	Automatic	238371











# **EM5/PM5 to LD Series Upgrade Kits**

	Part Number	Description
P	257350	EM5 to LDM5
P	257351	PM5 to LDP5

#### **Accessories**

Part Number	Description
240416	Inlet swivel
114017	Inlet filter, 80 mesh
 240453	Valve repair kit

# **Protective Boots with Trigger Guards**

Part Number	Description
247759	Black
243835	Red
243836	Blue
243837	Green
247760	Yellow

#### **Swivel Covers**

	Part Number	Description
GRAÇO	191294	Black
GRACO	191287	Red
GRACO	191288	Blue
CRACO	191289	Green
GRACO	191295	Yellow

# **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
0 graco	17S659	Red
O GRACO	17S660	Blue
O GRACO	17S661	Green
O GRACO	17S662	Yellow
O GRACO	17S663	White

# **EM® Series Electronic Manual Dispense Meters**











# Low-Flow and High-Flow Manual Meters

Building on the heritage of Graco's first electronic meter, the EM Series features a robust design at an affordable price. Our legacy valve handle features a long-life valve design for years of dependable service. These meters are weather-rated and impact-resistant to withstand the harshest shop conditions.

#### Twist-Close Nozzle Prevents Leaking

Multiple extensions available including rigid, flexible and gear lube.

#### **High-Flow Rates**

Capable of up to 20 gpm.

#### Long Battery Life

Features upgraded electronics and easily replaceable AAA batteries.

#### **Prevent Accidental Dispenses**

Easy-to-hold locking handle.

#### **Proven in Harsh Conditions**

Sealed electronics (IP69K) are protected against direct pressure washing and dust.

#### Legacy Valve

1/2 and 3/4 inch inlets, compatible with oil, ATF, anti-freeze and gear lube.

#### **Typical Applications**

- Automotive dealerships
- · Service and fast lube centers
- Lube trucks
- Mining
- · Heavy-duty dealerships
- · Fleet service facilities
- In-plant

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

echnical Specifications	EM8	EM20	
ecimical opecifications	LIVIO	LIVIZU	
Flow Range	0.25 to 8 gpm (0.95 to 30.3 lpm)	0.25 to 20 gpm (0.95 to 75.7 lpm)	
Maximum Operating Pressure	1,500 psi (102 bar)		
Unit of Measure	Quarts, gallor	ns, pints, liters	
Accuracy/Repeatability	±0.	5%	
Inlet	1/2 NPT	1/2 NPT or 3/4 NPT	
Outlet	3/4 straight thread O-ring boss	7/8 straight thread O-ring boss	
Maximum Totalizer	19,999 units		
Maximum Recorded Dispense	19,999 units		
Operating Temperature Range	-22°F to 180°F (-30°C to 82°C)		
Storage Temperature Range	-40°F to 185°F	(-40°C to 85°C)	
Outdoor Use	Yes – IP69k as p	per DIN 40050-9	
Battery	2 (AAA) alkaline	or 2 (AAA) lithium	
Wetted Parts	Aluminum, stainless steel, carbon s	teel, acetal, nitrile rubber, Geolast™	
Meter Pressure Loss*	30 psi @ 6 gpm	85 psi @ 12 gpm	
Dimensions	13 in L x 3.5 in W x 5.25 in H (33 cm L x 9 cm W x 13.3 cm H)		
Weight	3 lbs (1.36 kg)	3.1 lbs (1.39 kg)	
Warranty	Five years overall, three years electronics and 1 year wear parts		
Instruction Manual	3A5588		

<sup>\*</sup> Tested in 10W oil at 70°F (21°C). Flow rate varies with fluid pressure, temperature, viscosity, inlet fitting size and nozzle type. Geolast is a registered trademark of Advanced Elastomer Systems.











# >>> Ordering Information

		Extension	Inlet in (mm)	Part Number
		Flexible		25C904
EM8		Rigid	1/2 (13)	25C903
		Gear		25C905
		51. 11.	1/2 (13)	25C915
EM20		Flexible	3/4 (19)	25C918
EM		Rigid	1/2 (13)	25C916
			3/4 (19)	25C919

		Inlet in (mm)	Part Number
EM8		1/2 (13)	25D433
EM20	Ä	1/2 (13)	25D436
EM CONTRACTOR OF THE CONTRACTO		3/4 (19)	25D437

# **EM® Series Electronic Manual Dispense Meters**











# >>> Ordering Information

#### **Accessories**

Part Number	Description		
25D934	Electronic control replacement		
129876	Black impact guard for EM8 or EM20		
25D936	Battery kit: includes AAA batteries, Torx screws and bezel seal		
100896	3/4 NPT(M) x 1/2 NPT(F) adapter		

#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
O GRACO	17\$659	Red
Q GRACO	17S660	Blue
O GRACO	17S661	Green
O GRACO	17S662	Yellow
O GRACO	17S663	White

# **Nozzle and Extension Kits**

	Extension	Fluid	Nozzle Description	Part Number	Compatible Meters
4	Rigid	Oil	Non-drip, manual open/close	26C267	EM8
	nigiu	Oii	Non-drip, quick-close	255921	EM20
1	Rigid	Gear lube	Non-drip, quick-close	255854	EM8
4	Flovible	Oil	Non-drip, manual open/close	26C268	EM8
	Flexible	UII	Non-drip, quick-close	255859	EM20
	Nozzle Only	Oil/Anti-freeze	Non-drip, manual open/close	17T207	EM8
	Nozzle Only	Oil/Anti-freeze	Non-drip, quick-close	255793	EM20
90	Nozzle Only	Gear lube	Non-drip, quick-close	255470	EM8
	Flexible	Oil/Anti-freeze	Extension only, 2 ft length	131733	EM8













Graco's premium SD meters were designed from the ground up to provide the best user experience. These robust meters feature high flow, improved ergonomics and a large high-contrast LCD screen to make viewing dispense amounts easy in all lighting conditions.



GRACO

## Large LCD High-Contrast Display

High-contrast screen for reading in all lighting conditions with easy setup and navigation. See what fluid the meter is setup for and exactly how much you are dispensing.

#### Available in Two Models

Manual or preset options. Preset is compatible with Pulse  $^{\text{\tiny TM}}$  FC and upgradeable to Pulse  $^{\text{\tiny TM}}$  Pro.

#### **High Flow**

Available in two models -8 gpm (30 lpm) or 18 gpm (68 lpm).

#### **Durable Cast Body**

Designed for heavy duty and harsh applications.

#### Automatic Quick-Close Nozzle

Choose from rigid or flexible extensions with non-drip performance.

# Long-Life Valve Design

Cartridge design for fewer and easier repairs.

#### Ergonomic Handle Design

Four-finger trigger and easy-to-use button pad reduce worker fatigue.

#### **Typical Applications**

- Automotive dealerships
- Heavy-duty dealerships
- · Fast lube centers
- · Fleet service facilities
- Service shops
- In-plant
- Mining

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor gear, and ATF)
- Anti-freeze
- Windshield wash

# Technical Specifications

Flow Range*	0.25 gpm to 18 gpm (0.9 lpm to 68 lpm)
Maximum Working Pressure	1,500 psi (103.4 bar)
Units of Measure	Pints, quarts, gallons, liters (factory set to quarts)
Metered Dispense Valve Accuracy**	+/- 0.5%
Inlet	1/2 in–14 NPT or 3/4 in–14 NPT
Outlet	3/4 in–16 straight thread O-ring Boss
Maximum Recorded Dispense	9999 units (factory set in quarts)
Operating Temperature Range	4°F to 158°F (-20°C to 70°C)
Storage Temperature Range	-40°F to 158°F (-40°C to 70°C)
Battery Life***	6 months
Wetted Parts	Aluminum, stainless steel, PBT, nitrile rubber, zinc plated carbon steel, nickel plated carbon steel
Dimensions (without extension)	13 in L x 3.75 in W x 5.75 in H (33 cm x 9.5 cm x 14.6 cm)
Weight	5.3 lb (2.4 kg)
Warranty	Five years overall, three years electronics
Instruction Manual	3A6711 and 3A6673

<sup>\*</sup>Tested in 10W motor oil. Flow rates vary with fluid pressure, temperature and viscosity.

<sup>\*\*</sup>At 2.5 gpm (9.5 lpm), at  $70^{\circ}$ F ( $21^{\circ}$ C), with 10-weight oil and 1 gallon dispensed. May require calibration.

<sup>\*\*\*</sup>Battery required to meet life expectancy: Energizer® Alkaline E91.













# >>> Ordering Information

# **SD Electronic Meters**





25M406

	Dispense Type	Flow Range gpm (lpm)	Fluid	Extension	Inlet in (NPT)	Part Number
				Rigid	1/2	26C384
			Oil	Flexible	1/2	26C354
SDP8	Preset (Pulse FC-enabled)	0.25–8 (1–30)	Anti-freeze	Rigid	1/2	26C385
	(	(. 23)	Anti-neeze	Flexible	1/2	26C355
			Gear lube	Rigid	1/2	26C358
				Flexible	1/2	26C357
SDP18	Preset	1.1111	Oil	Flexible	3/4	26C361
S	(Pulse FC-enabled)			Rigid	3/4	26C360
				Rigid	1/2	26C356
			Oil	Flexible	1/2	25M406
				OII	Rigid	1/2
SD M8	Manual	0.25–8	Anti-Freeze	Flexible	1/2	25M407
S	Iviaituai	(1–30)	Anti-Freeze	Rigid	1/2	25M405
			Gear Lube	Rigid	1/2	25M413
			Windshield Wash	Rigid	1/2	25M415
				Flexible	3/4	25M417
SDM18	Manual	0.25–18	Oil	Rigid	3/4	25M416
SDI	IVIdITUdI	(1–68)		Flexible	1/2	25M411
				Rigid	1/2	25M410

# **Nozzle and Extension Kits**

	Extension	Fluid	Nozzle Description	Part Number	Compatible Meters
		Oil	Non-drip, quick-close	255852	SDM8/SDP8
	Rigid	Anti-freeze	Non-drip, manual open/close	26C267	SDM8/SDP8
× ×		Oil/Anti-freeze	High-flow, non-drip, quick-close	255857	SDM18/SDP18
	Rigid	Gear lube	Non-drip, quick-close	255854	SDM8/SDP8
900		Oil	Automatic, non-drip, quick-close	255853	SDM8/SDP8
	Flexible	Anti-freeze	Non-drip, manual open/close	26C268	SDM8/SDP8
		Oil/Anti-freeze	High-flow, non-drip, quick-close	255858	SDM18/SDP18
THE STATE OF THE S	Nozzle Only	Oil	Automatic, non-drip, quick-close	17R220	SDM8/SDP8
4	Nozzle Only	Gear lube	Non-drip, quick-close	255470	SDM8/SDP8
	Nozzle Only	Oil/Anti-freeze	Non-drip, manual open/close	17T207	SDM8/SDP8
60-03	Flexible	Oil/Anti-freeze	Extension only, 2 ft length	131733	SDM8/SDP8
	Rigid	Windshield wash	Extension, nozzle	273079	SDM8











# >>> Ordering Information

# **Filter Kits for SD Series Meters**

- ulu	Part Number	Description
	255885	Kit includes filters/ strainers, spacers and 0-rings

#### **Swivel Covers**

Part Number	Description
15T366	Black
15T367	Red
15T368	Blue
15T369	Green
15T370	Yellow

# **Impact Protection**

	Part Number	Description
0	131226	Pulse/SD meter boot

# **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
O GRACO	17S659	Red
O GRACO	17S660	Blue
O GRACO	17S661	Green
O GRACO	17S662	Yellow
OGRACO	17S663	White














# Heavy-Duty Construction

For indoor or outdoor use.

# Easy-to-Read LCD

Simple operator controls and measures in pints, quarts, liters or gallons

# Easy Battery Replacement

Operates on single 9V alkaline battery.

#### Tracks Totals in Two Modes

Reset total for a periodic dispense history and non-reset total for the meter's total dispense history.

#### **Typical Applications**

- · Automotive dealerships
- · Fast lube centers
- · Service shops
- · Fleet services facilities
- In-plant

#### Typical Fluids Handled

- · Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze
- · Windshield washer fluid

Technical Specifications	
Flow Range*	0.5 gpm to 5 gpm (1.9 lpm to 19 lpm)
Maximum Working Pressure	500 psi (34 bar)
Units of Measure	Quarts, pints, gallons, liters (factory-set to quarts)**
Accuracy	± 0.5%
Inlet/Outlet	1/2 NPT
Maximum Totalizer	99,999
Maximum Recorded Dispense	999.99
Operating Temperature Range	-4°F to 122°F (-20°C to 50°C)
Storage Temperature Range	-13°F to 122°F (-25°C to 50°C)
Outdoor Use	Yes
Battery	9-volt, alkaline
Wetted Parts	Nickel, zinc, zenite, nitrile rubber
Meter Pressure Loss*	25 psi (1.7 bar) @ 5 gpm (19 lpm)
Dimensions	4.25 in L x 3.25 in W x 2.0 in H (10.8 cm L x 8.3 cm W x 5.1 cm H)
Weight	1.8 lb (0.8 kg)
Warranty	Five years overall, two years electronics
Instruction Manual	308687

<sup>\*</sup>Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature and viscosity.

# Ordering Information

#### Meter

Part Number	Description
239824	IM5 low pressure – low-flow in-line meter

#### **Accessory**

Part Number	Description
239876	Strainer kit


<sup>\*\*</sup>Display shows quantity in 0.01 increments up to 999.99 gallons, quarts, pints or liters. Totalizes in gallons or liters up to 99,999 units.











Graco's IM20 in-line meter is weather-rated and shock-resistant, protecting the electronics from intense, high-pressure cleaning and mechanical vibration common in industrial applications.



# Easy-to-Read LCD

Simple operator control. Measures in quarts, gallons, pints and liters.

#### Easy Battery Replacement

Long-lasting, replaceable AAA batteries.



#### Sealed Electronics

IP69K-rated meter. Electronics are safe from pressure washing and dusty environments.

#### Tracks Totals in Two Modes

Reset total for a periodic dispense history and non-reset total for the meter's total dispense history.

#### **Typical Applications**

- Automotive dealerships
- · Service and fast lube centers
- Lube trucks
- Mining
- Heavy-duty dealerships
- · Fleet service facilities
- In-plant

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

lec	nnical	Specifications

Flow Range*	0.25 to 20 gpm (0.95 to 75.7 lpm)
Maximum Working Pressure	1,500 psi (102 bar)
Unit of Measure	Quarts, pints, gallons, liters (factory set to quarts)
Accuracy/Repeatability	±0.5%
Inlet/Outlet	3/4 NPT
Maximum Totalizer	19,999 units
Maximum Recorded Dispense	19,999 units
Operating Temperature Range	-22°F to 180°F (-30°C to 82°C)
Storage Temperature Range	-40°F to 185°F (-40°C to 85°C)
Outdoor Use	Yes - IP69k as per DIN 40050-9
Battery	2 (AAA) alkaline or (2) AAA lithium
Wetted Parts	Aluminum, stainless steel, carbon steel, acetal, nitrile rubber, Geolast™
Meter Pressure Loss*	35 psi @ 12 gpm
Dimensions	4.2 in L x 3.4 in W x 3.2 in H (10.7 cm L x 8. cm W x 8.1 cm H)
Weight	1 lb. 4 oz. (0.57 kg)
Warranty	Five years overall, three years electronics
Instruction Manual	3A5588

\*Tested in 10W oil at 70°F (21°C). Flow rate varies with fluid pressure, temperature, viscosity, inlet fitting size and nozzle type. Geolast is a registered trademark of Advanced Elastomer Systems.

# Ordering Information

Part Number	Description
25C841	IM20 high-flow, high-pressure in-line meter















# **Energy Efficient**

Powered by two AA alkaline batteries.

#### Tracks Totals in Two Modes

Reset total for a periodic dispense history and non-reset total for the meter's total dispense history.

#### **Typical Applications**

- Automotive dealerships
- Fast lube centers
- · Service shops
- · Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- Mining

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze
- · Windshield washer fluid
- · Diesel exhaust fluid

# Rugged Stainless Steel Body

Remains corrosion free in hard environments for years of trouble-free service.

# Large, Easy-to-Read LCD

Simple operator controls and measures in pints, quarts, liters or gallons.

echnical Specifications	
Flow Range*	0.5 gpm to 15 gpm (1.9 lpm to 57 lpm)
Maximum Working Pressure	1,500 psi (103 bar)
Units of Measure	Quarts, pints, gallons, liters (factory-set to quarts)
Accuracy	± 0.5%
Inlet/Outlet	1/2 NPT
Maximum Totalizer	99,999
Maximum Recorded Dispense	999.99
Operating Temperature Range	-4°F to 122°F (-20°C to 50°C)
Storage Temperature Range	-13°F to 122°F (-25°C to 50°C)
Outdoor Use	No
Battery	2AA alkaline
Wetted Parts	Nitrile rubber, SST and Geolast
Meter Pressure Loss*	22 psi (1.5 bar) @ 14 gpm (53 lpm)
Dimensions	5 in L x 3 in W x 2.75 in H (12.7 cm L x 7.6 cm W x 7 cm H)
Weight	1.8 lb (0.8 kg)
Warranty	Seven years overall, three years electronics
Instruction Manual	313048

<sup>\*</sup>Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature and viscosity.

# Ordering Information

#### Meters

Part Number	Description
247453	SDI15 medium/high pressure – medium-/high-flow in-line meter for petroleum- and synthetic-based oils, anti-freeze and windshield washer fluid
24G738	SDI15 medium/high pressure – medium-/high-flow in-line meter for diesel exhaust fluid applications (BSPP)

#### **Accessories**


	Part Number	Description
-	108458	Shutoff ball valve 1/2 NPT(F)
	223179	Strainer kit 1/2 NPT(F) 1/2 NPT(M)











# Impact-Resistant Shroud

Resists scratches and protects knob and dial from damage.

# Simple, Easy Design

Dial and face design is easy to read and set.

#### Fluid Swivel

1/2 inch fluid inlet.

#### Fluid Extension Kits

Choose from rigid or flexible with automatic thermal compensating nozzle.

#### Built-In Totalizer

Helps manage material usage.

# **Durable Cast Housing**

Durable aluminum body is balanced and lightweight with comfortable grip.

#### **Typical Applications**

- Automotive dealerships
- Fast lube centers
- Service shops
- · Heavy-duty dealerships
- Fleet services facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

#### **Technical Specifications**

Flow Range*	0.28 gpm (1.0 lpm) to 8 gpm (30.2 lpm)
Maximum Working Pressure	1,500 psi (103 bar)
Units of Measure	Quarts, gallons, liters
Accuracy	± 1%
Inlet	1/2 in NPT
Outlet	3/4-16 straight thread O-ring boss
Maximum Totalizer	99,999 units
Maximum Recorded Dispense	60 gallons
Operating Temperature Range	-50°F to 160°F (-45°C to 70°C)
Outdoor Use	Yes
Wetted Parts	Brass, aluminum, SST, TPE
Meter Pressure Loss*	30 psi (2.1 bar) @ 4 gpm (15 lpm)
Dimensions	11.5 in L x 5 in W x 6.3 in H (29.2 cm L x 12.7 cm W x 16 cm H)
Weight	3.5 lb (1.6 kg)
Warranty	Five years
Instruction Manual	333492

<sup>\*</sup>Tested with 10W motor oil. Minimum/maximum flow rates will vary with fluid viscosity.











# Ordering Information

# **Manual Meters**

Extension	Model Description	Part Number
Bare	4/16 Liter	24U956
Dale	4/16 Quart	24U959

# **Manual Meter Packages**

	Extension	Model Description	Part Number	Replacement Nozzle/Extension Kit
	4/16 Liter	24V043	255853	
	Flexible	4/16 Quart	24V034	255853
	2	4/16 Liter	24V046	255852
	Rigid	4/16 Quart	24V037	255852
Constate	4/16 Liter	24V049	255854	
	Gear Lube	4/16 Quart	24V040	255854

# **Preset Meters**

	Extension	Model Description	Part Number
	Bare	60 Gallon	24U950
		60 Liter	24U953
To All		60 Quart	24U947











# **Preset Meter Packages**

	Futancian	Model	Dowl Nivershou	Package Includes
	Extension	Description	Part Number	Nozzle Extension
		60 Gallon	24Z129	255853
	Flexible	60 Liter	24Z132	255853
Tall		60 Quart	24Z126	255853
		60 Gallon	24Z128	255852
	Rigid	60 Liter	24Z131	255852
6011		60 Quart	24Z125	255852
		60 Gallon	24V055	24W641
	Short Rigid	60 Liter	24V058	24W641
To W		60 Quart	24V052	24W641
		60 Gallon	24Z130	255854
	Gear Lube	60 Liter	24Z133	255854
15		60 Quart	24Z127	255854

# **Nozzle Extensions**

	Fluid	Extension	Compatible Meter	Part Number
		Flexible	Manual	255853
***	Oil	Rigid	Manual	255852
		Short Rigid	Preset	24W641
	Anti-freeze	Flexible	Manual/Preset	24W306
	Anu-neeze	Rigid	Manual/Preset	255855
00000	Oil/Anti-freeze	Flexible (extension only – 2 ft)	Manual/Preset	131733
<b>N</b>	Gear lube	Rigid	Manual	255854

# **Accessories**

	Part Number	Description
0	256164	Strainer filter kit, 10-pack













# For Standard and **Heavier-Duty Applications**

Designed to perform in larger dealerships, fleet maintenance shops, municipal garages and higher-volume in-plant applications with longer plumbing runs and larger fluid usage.

#### Fluid Extension Kits

Choose from rigid or flexible extensions.

#### Lock-On/Lock-Off Trigger

For hands-free operation.

#### Sturdy Cast Body

Designed for use in tough environments.

#### Fluid Swivel

1/2 inch fluid inlet.

#### **Typical Applications**

- · Automotive dealerships
- · Fast lube centers
- · Service shops
- Lube trucks
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

- · Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

echnical Specifications	
Flow Range*	15 gpm (56.8 lpm)
Maximum Working Pressure	1,500 psi (103 bar)
Inlet	1/2 in NPT
Outlet	3/4-16 straight thread O-ring boss
Operating Temperature Range	-40°F to 180°F (-40°C to 82°C)
Outdoor Use	Yes
Wetted Parts	Aluminum, SST, CS, acetal, nitrile rubber, tpe
Dimensions	12 in L x 8.4 in W x 2.4 in H (30.5 cm L x 21.3 cm W x 6.1 cm H)
Weight	0.4 lb (0.18 kg)
Warranty	Seven years
Instruction Manual	312789

<sup>\*</sup>Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature, viscosity, inlet fitting and nozzle type.











# **SDV15 Control Valve**

***	Fluid	Extension	Inlet in (mm)	Part Number
	Oil/Anti-freeze	Rigid		247712
A	Oli/Altu-Heeze	Flexible	1/2 (13)	247713
	Gear	Gear		247714

# **SDV15 Bare Control Valve**

	Inlet in (mm)	Part Number
O TO THE OWNER OF THE OWNER OWNER OF THE OWNER OWN	1/2 (13)	247717

# **High Flow Nozzles with Extension**

Extension	Part Number
Rigid	255857
Flexible	255858

# **Filter Kit**

	Description	Part Number
0	Strainer filter kit	256164

#### **Quick Close Nozzle**

Extension sold separately.


	Fluid	Part Number
	Oil/Anti-freeze	17T207
4	Gear lube	255470
	Oil/Anti-freeze (high-flow)	255461











Designed to perform in larger dealerships, fleet maintenance shops, municipal garages and higher-volume in-plant applications with longer plumbing runs and larger fluid usage.



#### Fluid Extension Kits

Choose from rigid or flexible extensions with automatic flush-mount nozzle design that re-seats after each dispense to prevent dirt contamination.

#### Lock-On/Lock-Off Trigger

For hands-free operation.

#### Sturdy Cast Body

Designed for use in tough environments.

#### 1/2 and 3/4 Inch Inlet with Swivel Options

Meets standard and high flow requirements.



- High-flow, non-metered oil dispense
- · Automotive dealerships
- · Heavy-duty dealerships
- · Fast lube centers
- · Fleet service facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Anti-freeze

Technical Specifications	
Flow Range*	Up to 20 gpm (75.7 lpm)
Maximum Working Pressure	1,500 psi (103 bar)
Inlet	1/2 in or 3/4 in NPT
Outlet	7/8-14 straight thread O-ring boss
Operating Temperature Range	-40°F to 180°F (-40°C to 82°C)
Outdoor Use	Yes
Wetted Parts	Aluminum, SST, CS, acetal, nitrile rubber, Geolast
Dimensions	12 in L x 8.4 in W x 2.4 in H (30.5 cm L x 21.3 cm W x 6.1 cm H)
Weight	0.4 lb (0.18 kg)
Warranty	Seven years
Instruction Manual	308642

<sup>\*</sup>Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature, viscosity, inlet fitting and nozzle type.













# **XDV20 Control Valve**

Includes high flow, quick-close nozzle.

	Extension	Inlet in (mm)	Part Number	
	Digid	1/2 (13)	247718	
	Rigid	3/4 (19)	247722	
A	Flovible	1/2 (13)	247721	
	Flexible	3/4 (19)	247723	

# **XDV20 Bare Control Valve**

<b>G</b> Con	Inlet in (mm)	Part Number
100	1/2 (13)	247724
1 1	3/4 (19)	247725

#### **Accessories**

	Part Number	Description
	255793	Quick-close high-flow nozzle for oil, ATF and anti-freeze
	255859	Flexible extension with quick-close nozzle (255793)
4	255921	Rigid extension with quick-close nozzle (255793)

# **Meter Dispense Consoles**



>>> Ordering Information

# **Lubricant Dispense Consoles**

Includes upper and lower plates with roller guides and brackets. Hoses not included.

Part Number  222629  223448  222645	Dort Number	Description	Package Includes		
	Description	Dispense Valve Brackets (qty)	Water Bib Brackets (qty)		
	Six-station console	196471 (5)	110236 (1)		
	Four-station console	196471 (3)	110236 (1)		
	222645	Single add-on fluid module	196471 (1)	-	

# **Lubricant Dispense Consoles Accessories**

as rount supplies delicated Accessories					
	Part Number	Description			
	110236	Water bib bracket			
	110237	Dispense valve bracket for XD meters			
1	110285	Pistol-grip dispense valve bracket			
4	196471	Dispense valve bracket for LDP5, EM8 and EM20 meters			
	249440	Dispense valve bracket for SD/Matrix meters			

# >>> Ordering Information

# Oil Dispense Bar

2	Part Number	Description
	220107	Modular oil dispense bar supports up to 3 dispense taps (1 included) and optional meters. Add up to two additional dispense valves with tap kit 220112.

# **Accessories for Oil Dispense Bar**

	Part Number	Description
	220112	Dispenser valve kit for adding dispense valves to modular oil dispense bar.
TO ST	239706	Meter kit for adding IM5 electronic totalizing meter to dispense valve. Reads in gallons, quarts, pints and liters.

Notes		

# GREASE **PUMPS**

	Page
Grease Pump Selection Guide	108-109
LD Series <sup>™</sup> Grease Pumps	110-114
$LD \ Series^{^{\mathrm{TM}}} \ Grease \ Pump \ Accessories \ . \ .$	115-116
Mini Fire-Ball® 225 Grease Pumps	117-120
Fire-Ball® 300 Grease Pumps	121-128
Fire-Ball® 425 Grease Pumps	129-135
Grease Pump Accessories	136-139
GT 750 36:1 Grease Pumps	140-141
NXT <sup>™</sup> Check-Mate <sup>®</sup> Grease Pumps	142-146
Dyna-Star® Hydraulic Grease Pumps	147-148
Viscount® II Grease Pumps	149-150
Manually-Operated Grease Pumps	151





() GRACO

# **Grease Pump Selection Guide**

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Line Length	Simultaneous Dispense Points	Approx. Free Flow Rate @ 100 psi	Air Inlet	Fluid Outlet	Air Operation Range	Reference Page
LD, 50:1	Automotive dealerships     Fast lube centers     Lube trucks     Lubricant transfer     Service shops	Up to 7,000 lbs (3,175 kg)	Up to 100 (30.5 m)	1	4.5 lbs/min (2 kg/min)	1/4 in NPT(F)	1/4 in NPT(F)	20-150 psi (1.37-10.3 bar)	110-116
Mini Fire-Ball 225, 50:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	Up to 10,000 lbs (4,535 kg)	Up to 100 (30.5 m)	1	1.5 lbs/min (0.7 kg/min)	3/8 in NPT(F)	1/4 in NPT(F)	40-140 psi (2.8-10 bar)	117-120 135-138
Fire-Ball 300, 15:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	Up to 10,000 lbs (4,535 kg)	Up to 250 ft (76 m)	1-2	7.5 lbs/min (3.4 kg/min)	3/8 in NPT(F)	1/4 in NPT(F)	40-180 psi (2.8-12.5 bar)	121-123 135-138
Fire-Ball 300, 50:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	Up to 10,000 lbs (4,535 kg)	Up to 250 ft (76 m)	1-2	7.5 lbs/min (3.4 kg/min)	3/8 in NPT(F)	1/4 in NPT(F)	30-140 psi (2.1-9.7 bar)	121-132 124-128 135-138
Fireball 425, 10:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 20,000 lbs (9,072 kg)	Up to 500 ft (152 m)	4 or more	29 lbs/min (13.1 kg/min)	1/2 in NPT(F)	1 in NPT(F)	40-180 psi (2.8-12.5 bar)	129-130 136-139
Fire-Ball 425, 50:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 20,000 lbs (9,072 kg)	Up to 250 ft (76 m)	4 or more	9 lbs/min (4.1 kg/min)	1/2 in NPT(F)	3/8 in NPT(F)	40-150 psi (2.8-10.3 bar)	129-131 133-139
Fire-Ball 425, 75:1	Automotive dealerships     Fast lube centers     Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	> 20,000 lbs (9,072 kg)	Up to 500 ft (152 m)	4 or more	6.5 lbs/min (2.9 kg/min)	1/2 in NPT(F)	3/8 in NPT(F)	40-100psi (2.8-7 bar)	129-130 132-139
GT 750, 36:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Mining	> 20,000 lbs (9,072 kg)	Up to 250 ft (76 m)	4 or more	32 lbs/min (14.5 kg/min)	1/2 in NPT(F)	1 in NPT(F)	40-100psi (2.8-7 bar)	140-141

108

## **Grease Pump Selection Guide**

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Air Inlet	Fluid Outlet	Air Operation Range	Reference Page
Check-Mate 14:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 in NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	142-143 145-146
Check-Mate 26:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	142-143 146
Check-Mate 29:1	Fleet service facilities In-plant large runs Large volume lubricant transfer Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 NPT(F)	1 in NPT(F)	0-100 psi (0-7 bar)	142-143 146
Check-Mate 55:1	Fleet service facilities In-plant large runs Large volume lubricant transfer Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 NPT(F)	1 in NPT(F)	0-100 psi (0-7 bar)	142 144-146
Check-Mate 63:1	Fleet service facilities In-plant large runs Large volume lubricant transfer Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 NPT(F)	3/4 in NPT(M)	0-72 psi (0-4.9 bar)	142 144-146
Check-Mate 68:1	Fleet service facilities     In-plant large runs     Large volume lubricant transfer     Mining remote fill	> 20,000 lbs (9,072 kg)	3/4 NPT(F)	1 in NPT(F)	0-78 psi (0-5.4 bar)	142 144-146

Pump Family and Fluid Pressure Ratio	Typical Applications	Maximum Grease Output Flow Rate	Maximum Grease Output Pressure	Hydraulic Inlet (Supply)	Hydraulic Outlet (Return)	Grease Outlet	Maximum Hydraulic Inlet Pressure	Reference Page
Dyna-Star 5:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	4 lb/min (1.8 kg/min)	7500 psi (517 bar)	3/8 in NPT(F)	3/4 in NPT(F)	1/2 in NPT(F)	1500 psi (102 bar)	147-148
Dyna-Star 10:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	1.1 lb/min (0.5 kg/min)	7500 psi (517 bar)	3/4 in -16 JIC (37° Flare)	3/4 in NPT(F)	1/2 in NPT(F)	600 psi (41 bar)	147-148
Viscount II 2.4:1	Fleet service facilities     Heavy-duty dealerships     In-plant     Lube trucks     Lubricant transfer     Mining     Service shops	54 lb/min (20.4 kg/min)	2300 psi (159 bar)	3/4 in NPT(F)	1 in NPT(F)	1-1/2 in NPT(F)	1500 psi (102 bar)	149-150





**5 Year** Warranty!

### **Durable and hardworking**

Stay ahead of the competition with LD Series pumps. These affordable and full-featured pumps are designed for lowervolume (up to 7,000 lb/year) applications. LD pumps are fine-tuned for a compact, flexible and durable solution.

#### Three-Inch Air Motor

Provides more power to create better flow.

#### **Engineered for Durability**

Patented cup and plate design eliminates the need for O-rings that wear out faster, for a more durable, longer-lasting solution.

#### Modular Air Valve

Air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle-free installations.

#### Pilot Valves

Patented self- cleaning design increases reliability in dirty air environments and minimizes pressure drop with rapid changeovers for reduced stalling and smoother flow.

#### **Typical Applications**


- Automotive dealerships
- · Fast lube centers
- · Service shops
- · Lube trucks

#### Typical Fluids Handled

• Grease up to NLGI #2

#### **Pump Performance**

#### **LD Series 50:1 Pumps**





chnical Specifications	
Fluid Pressure Ratio	50:1
Air Motor Effective Diameter	3 in (76.2 mm)
Annual Usage	Up to 7,000 lb (3,175 kg)
Maximum Fluid Working Pressure	7,500 psi (517 bar / 51.7 MPa)
Approximate Free Flow Rate @ 100 psi	4.5 lb/min (2 kg/min)
Output per Cycle	0.34 oz (9.7 g)
Approximate Air Use and Flow @ 100 psi (80 cpm)	16 @ 1.7 lb/min (0.45 @ 0.77 kg/min)
Air Inlet	1/4 in NPT(F)
Fluid Outlet	1/4 in NPT(F)
Air Operation Range	20 psi to 150 psi (1.37 bar to 10.3 bar)
Max Recommended Pump Speed	120 cpm
Cycles per Pound (Kg)	47 cpp (103 cpk)
Wetted Parts	Steel, brass, nitrile rubber, polyurethane, UHMWPE, acetal
Sound Pressure Level	72.9 dB(A)
Sound Power Level	82 dB(A)
Approximate Weight	35 lb drum – 11.2 lb (5.1 kg) 120 lb drum – 15.0 lb (6.8 kg) 400 lb drum – 17.0 lb (7.7 kg)
Instruction Manual	3A1334

## **LD Series 50:1 Pumps**

Part Number	Description
24G600	For 35 lb (16 kg) pail
24G603	For 120 lb (55 kg) drum
24G606	For 400 lb (180 kg) drum

## **LD Series 50:1 Grease Pump Packages**




Ordering Information

### 35 lb Grease Packages





#### 120 lb Grease Packages





#### 400 lb Grease Packages





#### **LD Pro-Shot™ Non-Metered Grease Valves**



Technical Specifications		
Pressure	7,500 psi (517 bar / 51.7 MPa)	
Wetted Parts Steel, nitrile rubber, PTFE		
Inlet Size	1/4 in	

### >>> Ordering Information

Part Number	Description
129581	LD Pro Shot Grease Valve, 1/4 in NPT

#### **LD Z-Swivel**



- Swivels to prevent twist damage to hoses
- Constructed of heavy-duty steel and ball bearings for smooth and unrestricted movement

# Technical Specifications Pressure 6,000 psi (413 bar / 41.3 MPa) Inlet Size 1/4 in



Part Number	Description
129591	Z-swivel, 1/4 in NPT

## **LD Series 50:1 Grease Pump Accessories**



### Ordering Information

### **Adjustable Bung Adapter**

0	Part Number	Description
	24P623	Adjustable bung adapter for LD pumps

### **Air Regulators**

(9.0)	Part Number	Description
	24H420	Mini self-relieving air regulator with gauge, 1/4 in NPT x 3/8 in npsm

### **Carts**

7	Part Number	Description
M.	24H422	Drum cart with pneumatic wheels for 120 lb drums; includes chain for securing drum to cart
	24F915	Drum cart with pneumatic wheels for 400 lb drums; includes chain for securing drum to cart

### **Drum Covers**

	Part Number	Description
	24F904	Cover for 35 lb (16 kg) pails
	24F905	Cover for open-head 120 lb (54 kg) drums
	24F906	Cover for open-head 400 lb (182 kg) drums

### **LD Drum Dollies**

500	Part Number	Description
	131183	Drum Dolly, 35 lb (16 kg)
	131184	Drum Dolly, 120 lb (54 kg)
	129645	Drum Dolly, 400 lb (182 kg)

### **Follower Plates**

89	Part Number	Description
	24F901	Follower plate for 35 lb (16 kg) pails
	24F902	Follower plate for 120 lb (54 kg) drums
	24F903	Follower plate for 400 lb (182 kg) drums

### **Hose and Fitting Kits**

	Part Number	Description	Includes				
	Part Number		Grease Hose	Grease Hose Size	Air Hose	Air Hose Size	Fitting
00	24H862	6 ft LD grease pump hose kit	24H606	1/4 in NPT(M) x 1/4 in NPT(M) x 6 ft	24H858	3/8 in x 6 ft	156823
00	24J501	6 ft LD grease pump hose kit	24J487	1/4 in NPT(M) x 1/4 in NPT(M) (with 90° swivel) x 6 ft	24H858	3/8 in x 6 ft	156823





# Perfect for Medium Pressure, Low Volume Applications

You can't afford downtime, especially when your shop is small. The Mini Fire-Ball 225 is designed with fewer moving parts, which means less wear and tear and reduced downtime, allowing you to run a more profitable business.

#### **Durable Casting**

Thick cast aluminum air motor housing offers unmatched durability.

#### Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

#### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

#### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long-life without repair.

#### Corrosion-Resistant

Corrosion-resistant design utilizes liquid salt nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

#### **Typical Applications**


- · Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

#### Typical Fluids Handled

Grease up to NLGI #2

#### **Pump Performance**

#### Mini Fire-Ball 225 Pumps







# Mini Fire-Ball® 225 Grease Pumps



Fluid Pressure Ratio	50:1
Air Motor Effective Diameter	2.25 in (57.2 mm)
Annual Usage	Up to 10,000 lb (4,535 kg)
Maximum Fluid Working Pressure	8,400 psi (578 bar / 57.8 MPa)
Approximate Free Flow Rate @ 100 psi	1.5 lb/min (0.7 kg/min)
Output per Cycle	0.12 oz (3.5 g)
Continuous Duty Flow Rate	0.32 lb/min (0.15 kg/min)
Approximate Air Use and Flow @ 100 psi (80 cpm)	9.3 @ 0.62 lb/min (0.26 @ 0.28 kg/min)
Air Inlet	3/8 in NPT(F)
Fluid Outlet	1/4 in NPT(F)
Air Operation Range	40 psi to 140 psi (3 bar to 10 bar)
Max Recommended Pump Speed	100 cpm
Cycles per Pound (Kg)	130 cpp (287 cpk)
Wetted Parts	Carbon steel, zinc plating, brass, polyurethane, ultra-high molecular weight polyethylene, Buna-N
Sound Pressure Level	77.8 dB(A)
Sound Power Level	85.6 dB(A)
Approximate Weight	15 lb (6.8 kg)
Instruction Manual	309966

## Ordering Information

### Mini Fire-Ball 50:1 Pumps

Part Number	Description
246909 For 35 lb (16 kg) pail	
253361	For 35 lb (16 kg) pail, without handle
246780	For 120 lb (55 kg) drum
246781	For 400 lb (180 kg) drum

118



### 35 lb and 50 lb Grease Packages



Р	ackage Number	246910*	246911*	246913*
	Ratio	50:1	50:1	50:1
Type of Package		Portable pail dispenser	Stationary pail dispenser	Cart-mounted pail dispenser
Container Size		35 lb to 50 lb (16 kg to 23 kg)	35 lb to 50 lb (16 kg to 23 kg)	35 lb to 50 lb (16 kg to 23 kg)
	Container	-	204134	204134
Pι	ump Part Number	246909	246909	246909
	Fluid Hose Size	1/4 in x 12 ft	1/4 in x 12 ft	1/4 in x 12 ft
D	ispense Hose Kit	236058	236058	236058
se	12 ft Hose	109151	109151	109151
Includ	Air Coupler	114558	114558	114558
Dispense Kit Includes	Air Fitting	169971	169971	169971
sense	Z-Swivel	202577	202577	202577
Disi	Pro-Shot Valve	242056	242056	242056
	Follower Plate	24F901	**	**
	Drum Cover	222059	24R350	24R350
	Portable Base	-	-	203650
In	struction Manual	309967	309967	309967



<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately. \*\*Order follower plate (220653) separately for 35 lb (16 kg) pails or (220654) for 70 lb (32 kg) bulk.



### 120 lb and 400 lb Grease Packages



<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.





### Ideal for Shops with Grease Transfer

Install the Fire-Ball 300 in grease dispense applications. A differential air motor ensures smooth the double-acting pump design provides reliable grease flow and accurate dispense.

#### Durable

Thick cast aluminum air motor housing offers unmatched durability.

#### Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

#### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.

#### Corrosion-Resistant

Corrosion-resistant design utilizes liquid salt nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

#### **Typical Applications**

- Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

#### Typical Fluids Handled


· Grease up to NLGI #2



### Pump Performance


### Fire-Ball 300 15:1 Pumps

#### **Pump Performance Curve**



### Fire-Ball 300 50:1 Pumps

#### **Pump Performance Curve**



	Fire-Ball 300 15:1	Fire-Ball 300 50:1
Fluid Pressure Ratio	15:1	50:1
Air Motor Effective Diameter	3 in (76.2 mm)	3 in (76.2 mm)
Annual Usage	Up to 10,000 lb (4,535 kg)	Up to 10,000 lb (4,535 kg)
Maximum Fluid Working Pressure	2,700 psi (186 bar / 18.6 MPa)	8,400 psi (579 bar / 57.9 MPa)
Approximate Free Flow Rate @ 100 psi	7.5 lb/min (3.4 kg/min)	7.5 lb/min (3.4 kg/min)
Output per Cycle	1.29 oz (36.6 g)	0.34 oz (9.5 g)
Continuous Duty Flow Rate	0.7 lb/min (0.32 kg/min)	1.19 lb/min (0.54 kg/min)
Approximate Air Use and Flow @ 100 psi (80 cpm)	14 @ 6.5 lb/min (0.40 @ 2.9 kg/min)	21 @ 1.7 lb/min (0.59 @ 0.77 kg/mir
Air Inlet	3/8 in NPT(F)	3/8 in NPT(F)
Fluid Outlet	1/4 in NPT(F)	1/4 in NPT(F)
Air Operation Range	40 psi to 180 psi (2.8 bar to 12.5 bar)	30 psi to 140 psi (3.0 bar to 9.7 bar)
Max Recommended Pump Speed	66 cpm	76 cpm
Cycles per Pound (Kg)	12.4 cpp (27 cpk)	47.4 cpp (105 cpk)
Wetted Parts	Carbon steel, brass, copper, aluminum, PTFE, nitrile rubber, leather	Steel, brass, aluminum, acetal, nitrile rubber, polyurethane
Sound Pressure Level	77.8 dB(A)	77.8 dB(A)
Sound Power Level	85.6 dB(A)	85.6 dB(A)
Approximate Weight	22 lb (10 kg)	22 lb (10 kg)
Instruction Manual	306531	308883

### Ordering Information

#### Fire-Ball 300 Grease Pumps

Part Number	Ratio	Description
206405	15:1	For 35 lb (16 kg) pail
206699	15:1	For 120 lb (55 kg) drum
206700	15:1	For 400 lb (180 kg) drum
239877	50:1	For 35 lb or 70 lb (16 kg or 32 kg) pail
239887	50:1	For 120 lb (55 kg) drum
239888	50:1	For 400 lb (180 kg) drum



## **15:1 Grease Pump Packages**



Pa	ackage Number	222078	220170	220171
Type of Package		Stationary Pail Dispenser	Stationary Drum Dispenser	Cover-Mounted Drum Dispenser
Ratio		15:1	15:1	15:1
	Container Size	35 lb (16 kg)	120 lb (55 kg)	400 lb (180 kg)
Pu	mp Part Number	206405	206699	206700
	Dispense Kit	222080	222081	222081
	Fluid Hose	1/4 in x 15 ft	1/4 in x 25 ft	1/4 in x 25 ft
	Hose Part Number	109165	109167	109167
	Air Coupler	110198	110198	110198
S	Air Fitting	-	169971	169971
clude	Closed Nipple	156849	156849	156849
Dispense Kit Includes	Z-Swivel	202577	202577	202577
ense	Fitting(s)	169971	-	-
Dispe	Dispenser	Pro-Shot	Pro-Shot	Pro-Shot
	Dispenser Part Number	242056	242056	242056
	Air Regulator	110234	110234	110234
	Air Pressure Gauge	100960	100960	100960
	Drum Cover	222058	204574	200326
Ins	struction Manual	307882	307882	307882



#### 50:1 25 to 50 lb Grease Pump Packages



<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.

124

<sup>\*\*</sup>Order follower plate 220654 separately, if needed.



#### 50:1 120 lb Grease Pump Packages



<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.



### 50:1 120 lb Grease Pump Packages (Cont.)



Package Number		225014*	222073*
Type of Package		Stationary supply	Stationary supply topper-inductor
Ratio		50:1	50:1
Container Size		120 lb (55 kg)	120 lb (55 kg)
Pι	ımp Part Number	239887	239887
	Dispense Kits	222072	_
	Fluid Hose	1/4 in x 6 ft	-
	Hose Part Number	109150	-
SS	6 ft Coupled Hose	203320	-
clude	Air Coupler	-	-
Dispense Kit Includes	Air Fitting	-	-
	Z-swivel	-	-
Dispe	Fitting(s)	155494/155541	-
	Dispenser	-	-
	Dispenser Part Number	-	-
	Fluid Hose Size	See kit above	-
	Air Hose Size	See kit above	-
	Follower Plate	24F902	-
	Drum Cover	24R350	-
	Holster	-	-
	Portable Base	-	-
	Elevator	-	204121
	Pump Support	-	222074
	Hold Down Kit	-	_
In	struction Manual	307880	306523

<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.

### 50:1 400 lb Grease Pump Packages



P	ackage Number	225016*	226013*
1	Type of Package	Stationary supply	Stationary supply topper-inductor
	Ratio	50:1	50:1
	Container Size	400 lb (180 kg)	400 lb (180 kg)
Pι	ımp Part Number	239888	239888
Но	se and Fitting Kits	222072	204467
səpn	Fluid Hose	1/4 in x 6 ft	1/4 in x 6 ft
Dispense Kit Includes	Hose Part Number	109150	109150
ense K	6 ft Coupled Hose	203320	-
Dispe	Fitting(s)	155494/155541	100206/156971/205528
	Air Hose Size	3/8 in x 6 ft	3/8 in x 6 ft
	Follower Plate	24F903	-
	Drum Cover	200326	-
	Elevator	-	204385
	Pump Support	-	204461
	Inductor Plate	-	204353
	Base	-	205339
In	struction Manual	307880	306556

<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.



### **50:1 Grease Pump Lube Truck Packages**



Р	ackage Number	222085*	222071*
Type of Package		Lube truck	Lube truck
	Ratio	50:1	50:1
	Container Size	120 lb (55 kg)	400 lb (180 kg)
Pι	ımp Part Number	239887	239888
	Dispense Kits	222072	222072
sapn	Fluid Hose	1/4 in x 6 ft	1/4 in x 6 ft
it Incl	Hose Part Number	109150	109150
Dispense Kit Includes	6 ft Coupled Hose	203320	203320
Dispe	Fitting(s)	155494/155541	155494/155541
	Air Hose Size	3/8 in x 6 ft	3/8 in x 6 ft
	Follower Plate	220654	223845
	Drum Cover	222060	207366
	Hold Down Kit	222061	207361
ln	struction Manual	307880	307880

<sup>\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.



### 50:1 Grease Pump Side Pocket and Horizontal Mount Packages







# The Pump of Choice for Your Most Demanding Applications!

The Fire-Ball 425 features a large air motor to supply the power you need for long pipe runs and higher-volume dispensing. An ideal choice for applications where multiple dispenses happen at the same time.

### **Durable Casting**

Thick cast aluminum air motor housing offers unmatched durability.

#### Fewer Repairs

Fewer moving parts in the air motor assembly means less downtime and low repair cost.

#### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

### Superior Sealing

Non-metallic poppet valves offer positive sealing performance, even with contaminated "dirty" air environments for long life without repair.

#### Corrosion-Resistant

Corrosion-resistant design utilizes liquid salt nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

#### **Typical Applications**

- Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

#### Typical Fluids Handled


• Grease up to NLGI #2






#### **Pump Performance**

### Fire-Ball 425 10:1 Pumps






### Fire-Ball 425 50:1 Pumps





### Fire-Ball 425 75:1 Pumps





	EL D. II 40E 40.4	E. D. II 405 E0 4	FI D II 405 FF :
	Fire-Ball 425 10:1	Fire-Ball 425 50:1	Fire-Ball 425 75:1
Fluid Pressure Ratio	10:1	50:1	75:1
Air Motor Effective Diameter	4.25 in (108 mm)	4.25 in (108 mm)	4.25 in (108 mm)
Annual Usage	20,000+ lb (9,072+ kg)	20,000+ lb (9,072+ kg)	20,000+ lb (9,072+ kg)
Maximum Fluid Working Pressure	1,800 psi (124 bar / 12.4 MPa)	7,500 psi (517 bar / 51.7 MPa)	7,500 psi (517 bar / 51.7 MPa)
Approximate Free Flow Rate @ 100 psi	29 lb/min (13.1 kg/min)	9 lb/min (4.1 kg/min)	6.5 lb/min (2.9 kg/min)
Output per Cycle	5.82 oz (164.7 g)	1.06 oz (30 g)	0.71 oz (20 g)
Continuous Duty Flow Rate	3.5 lb/min (1.59 kg/min)	3.35 lb/min (1.52 kg/min)	1.95 lb/min (0.88 kg/min)
Approximate Air Use and Flow @ 100 psi (80 cpm)	45 @ 29 lb/min (1.3 @ 13 kg/min)	43 @ 5.3 lb/min (1.2 @ 2.4 kg/min)	43 @ 3.5 lb/min (1.2 @ 1.6 kg/mir
Air Inlet	1/2 in NPT(F)	1/2 in NPT(F)	1/2 in NPT(F)
Fluid Outlet	1 in NPT(F)	3/8 in NPT(F)	3/8 in NPT(F)
Air Operation Range	40 psi to 180 psi (2.8 bar to 12.5 bar)	40 psi to 150 psi (2.8 bar to 10.4 bar)	40 psi to 100 psi (2.8 bar to 7 bar
Max Recommended Pump Speed	60 cpm	60 cpm	60 cpm
Cycles per Pound	2.75 срр	15.1 cpp	22.7 cpp
Cycles per Kg	6 cpk	33 cpk	50 cpk
Wetted Parts	Steel, brass, aluminum, leather, Buna-N	CS, brass, aluminum, leather	CS, brass, aluminum, leather
Sound Pressure Level	80.9 dB(A)	80.9 dB(A)	80.9 dB(A)
Sound Power Level	94.6 dB(A)	94.6 dB(A)	94.6 dB(A)
Approximate Weight	38 lb (17.2 kg)	34 lb to 37 lb (15 kg to 17 kg)	30 lb to 37 lb (14 kg to 17 kg)
Instruction Manual	309407	306674	308777

### Ordering Information

#### Fire-Ball 425 Grease Pumps

Part Number		Ratio	Description
	965124	10:1	Stubby pump
	965129*	10:1	For 400 lb (180 kg) drum
	205394	50:1	For 120 lb (55 kg) drum
	205395	50:1	For 400 lb (180 kg) drum

Part Number	Ratio	Description
239731	75:1	For 35 or 70 lb (16 or 32 kg) pail
239729	75:1	For 120 lb (55 kg) drum
239730	75:1	For 400 lb (180 kg) drum

<sup>\*</sup>Includes 2 in NPT Bung Adapter (part number 222308).



## 50:1 120 lb and 400 lb Grease Pump Packages



F	ackage Number	223108*	225781*	226018*	
	Type of Package	Stationary Supply	Stationary Supply	Stationary Supply Topper-Inductor	
	Ratio	50:1	50:1	50:1	
	Container Size	120 lb (55 kg)	400 lb (180 kg)	400 lb (180 kg)	
Pı	ımp Part Number	205394	205395	205395	
	Dispense Kits	222076	222076	205102	
səpr	Fluid Hose	3/8 in x 6 ft	3/8 in x 6 ft	3/8 in x 6 ft	
Dispense Kit Includes	Hose Part Number	109163	109163	109163	
ense K	6 ft Coupled Hose	205418	205418	-	
Dispe	Fitting(s)	155470/155494	155470/155494	156859/196220/205528	
	Air Hose Size	1/2 in x 6 ft	1/2 in x 6 ft	1/2 in x 6 ft	
	Drum Cover 204574		200326	-	
	Follower Plate	223344	223846	-	
	Pump Support	-	-	204461	
	Elevator	-	-	204385	
	Inductor Plate	-	-	205699	
	Base	-	-	205339	
In	struction Manual	307880	307880	306556	

 $<sup>^{*}</sup>$ Use 1/2 in (12.7 mm) air regulator (104266) and gauge (100960); must be ordered separately.



## 75:1 120 lb and 400 lb Grease Pump Packages



Package Number		244635*	244636*	244637*	
Type of Package Ratio Container Size Pump Part Number		Stationary Cover-Mount	Stationary Cover-Mount	Stationary Inductor	
		75:1	75:1	75:1	
		120 lb (55 kg)	400 lb (180 kg)	400 lb (180 kg)	
		239729	239730	239730	
	Dispense Kits	222076	222076	205102	
sapn	Fluid Hose	3/8 in x 6 ft	3/8 in x 6 ft	3/8 in x 6 ft	
Kit Includes	Hose Part Number	109163	109163	109163	
Dispense K	6 ft Coupled Hose	205418	205418	-	
Dispe	Fitting(s)	155470/155494	155470/155494	156859/196220/205528	
	Air Hose Size	1/2 in x 6 ft	1/2 in x 6 ft	1/2 in x 6 ft	
	Drum Cover	204574	200326	-	
	Follower Plate	223344	223846	-	
	Pump Support	-	-	204461	
Elevator Inductor Plate		-	-	204385	
		-	-	205699	
	Base	_	_	205339	
In	struction Manual	307880	307880	306556	

 $<sup>^{\</sup>star}$ Use 1/2 in (12.7 mm) air regulator (104266) and gauge (100960); must be ordered separately.



### 50:1 and 75:1 Grease Pump Lube Truck Packages

Package Nui		223107*	222075*	243817*	243818**	
Type of Pack	kage	Lube Truck	Lube Truck	Lube Truck	Lube Truck	
Ratio		50:1	50:1	75:1	75:1	
Container S	Size	120 lb (55 kg)	400 lb (180 kg)	120 lb (55 kg)	400 lb (180 kg)	
Pump Part Nu	umber	205394	205395	239729	239730	
Dispense F	Kits	222076	222076	222076	222076	
ह्य Fluid H	lose	3/8 in x 6 ft	3/8 in x 6 ft	3/8 in x 6 ft	3/8 in x 6 ft	
Fluid Hose Part Hose Part 6 ft Couple	Number	109163	109163	109163	109163	
6 ft Couple	ed Hose	205418	205418	205418	205418	
Fitting	g(s)	155470/155494	155470/155494	155470/155494	155470/155494	
Air Hose S	ize	1/2 in x 6 ft	1/2 in x 6 ft	1/2 in x 6 ft	1/2 in x 6 ft	
Drum Cov	/er	222060	207366	222060	207366	
Follower Pl	late	223344	223846	223344	223846	
Hold Down	Kit	222061	207361	222061	207361	
Instruction M	lanual	307880	307880	307880	307880	

 $<sup>^{\</sup>star}\text{Use}$  1/2 in (12.7 mm) air regulator (104266) and gauge (100960); must be ordered separately.

<sup>\*\*</sup>Use 3/8 in (9.5 mm) air regulator (109075); must be ordered separately.



### **Grease Pump RAM Packages**






		Part 257435 (Ram Assembly) not shown	Part 257435 (Ram Assembly) not shown	
P	ackage Number	244905	244906	
Type of Package		Stationary Ram	Stationary Ram	
Ratio		50:1	75:1	
Container Size		400 lb (180 kg)	400 lb (180 kg)	
Pump Part Number		Fire-Ball 425 – 205395	Fire-Ball 425 – 239730	
	Dispense Kits	222076	222076	
sapn	Fluid Hose	3/8 in x 6 ft	3/8 in x 6 ft	
Dispense Kit Includes	Hose Part Number	109163	109163	
ense k	6 ft Coupled Hose	205418	205418	
Disp	Fitting(s)	155470/155494	155470/155494	
	Air Hose Size	1/2 in x 6 ft	1/2 in x 6 ft	
	Ram	257435	257435	
	Adapter Kit	224266	224266	
	Air Regulator and Gauge	*	244844	
R	am Plate Seal Kit	247335	247335	
ı	Pump Mount Kit	247337	247337	
In	struction Manual	309345	309345	

<sup>\*</sup>Air gauge included with RAM controller.


#### RAM-Mount

- Force feed high volume pumps
- · Extreme viscous grease
- Reduce waste
- · Clean and convenient method of drum change





### 50:1 and 75:1 Grease Pump Side Pocket and Horizontal Mount Packages





### **Air Regulators**

2
7

Part Number	Description
109075	3/8 in NPT (fbe) with gauge
244844	1/2 in NPT (fbe) with gauge

### **Bleed-Type Air Shut-Off Valves**




Part Number	Description
110223	1/4 in NPT
110224	3/8 in NPT
110225	1/2 in NPT
110226	3/4 in NPT

### **Bung Adapters**



Part Number	Dimensions	Compatible Pumps
239965	1.65 in ID	Fire-Ball 425, 50:1 Fire-Ball 425, 75:1
239966	1.29 in ID	Fire-Ball 300, 15:1 Fire-Ball 300, 50:1

### **Dispense Hose and Fitting Kits**



		Includes							
Part Number	Compatible Pump(s)	Fluid Hose Size	Fluid Hose	Grease Dispense Valve	Z-Swivel	3/8 in Closed Nipple	Quick- Disconnect Nipple	Quick- Disconnect Coupler	3/8 in Air Regulator
222080	Fire-Ball 300, 15:1	1/4 in x 15 ft	109165	242056	202577	156849	169971	110198	110234
222081	Fire-Ball 300, 15:1	1/4 in x 25 ft	109167	242056	202577	156849	169971	110198	110234
236058	Mini Fire-Ball 225, 50:1	1/4 in x 12 ft	109151	242056	202577	_	169971	114558	_
222070	Fire-Ball 300, 50:1	1/4 in x 12 ft	109151	242056	202577	-	169971	114558	_
26C183	Fire-Ball 300, 50:1	1/4 in x 12 ft	109151	26C184	202577	-	169971	114558	_
222383	Mini Fire-Ball 225, 50:1 Fire-Ball 300, 50:1	1/4 in x 25 ft	109154	242056	202577	-	169971	114558	_

### **Hose and Fitting Kits**



				Inclu	udes	
Part Number	Pressure Rating	Compatible Pumps	6 ft Air Hose	Air Hose Swivel Elbow	6 ft Fluid Hose	Fluid Hose Swivel Elbow
222072	5,000 psi (345 bar)	Fire-Ball 300, 50:1	203320	155494	109150	155541
222076	4,000 psi (276 bar)	Fire-Ball 425, 50:1	205418	155470	109163	155494



### **Drum Covers**

Part Number	Description	Compatible Pumps
222059	Cover for 35 lb (16 kg) pails	Mini Fire-Ball 225, 50:1 Fire-Ball 300, 50:1
24R350	LD Cover for open-head 35 lb (16 kg), 70 lb (32 kg) or 120 lb (55 kg) drums	Mini Fire-Ball 225, 50:1 Fire-Ball Pumps
204574	SD Cover for open-head 70 lb (32 kg) or 120 lb (55 kg)	Mini Fire-Ball 225, 50:1 Fire-Ball Pumps
200326 Cover for open-head 400 lb (180 kg) drums		Mini Fire-Ball 225, 50:1 Fire-Ball 300, 15:1 Fire-Ball 300, 50:1 Fire-Ball 425, 10:1 and 50:1
160754	Bung-adapter plate for mounting pump to 120 lb (55 kg) or 400 lb (180 kg) drum covers	Fire-Ball Pumps

#### **Drum Elevator**

-3ps	Part Number	Number		Includes		
		Description	Cover Support	Drum Elevator	Air Control Kit	
	241663	Air-powered elevator to speed up 400 lb (180 kg) drum changes	207562	204385	207561	

### **Mounting Accessories for Fire-Ball Pumps**

600	Part Number	Description
	948393	Flange Adapter (male) for Fire-Ball 300 Pumps
	948392	Flange Adapter (male) for Fire-Ball 425 Pumps
	512874	Coupler (female), 3 in thread



#### **Follower Plates**



#### **High-Pressure Grease Shut-Off Valve**

Part Number	Description	Pressure Rating	Inlet
202869	High-pressure needle valve	5,000 psi (345 bar)	1/2 in

#### **Lincoln-to-Graco Adapter Kit**

Part Number	Description	Compatible Pump
241246	For replacing a Series 20 Lincoln	Fire-Ball 300, 50:1



### **Portable Bases**

	Part Number	Description
S.	131183	Drum dolly, 35 lb (16 kg)
Q,	131184	Drum dolly, 120 lb (54 kg)
	129645	Drum dolly, 400 lb (182 kg)
	203622	Caster base for 120 lb (54 kg) drums

### **Carts**

	Part Number	Description	Compatible Container Size
	203650	Drums fit onto recess on formed base. Rim clamps secure drum onto cart.	35 lb (16 kg) 70 lb (32 kg) 120 lb (55 kg)
4	222243	Heavy-duty drum cart with pneumatic wheels	120 lb (55 kg)
	111470	Heavy-duty drum truck on roll-around base	400 lb (180 kg)

### **Pro-Shot Dispense Valves**



Part Number	Description		
242055	1/4 in NPT(F) inlet without coupler or extension		
242056	/4 in NPT(F) inlet with coupler and extension 200389		
242057	3/8 in NPT(F) inlet without coupler or extension		
242058	3/8 in NPT(F) inlet with coupler and extension 200389		
224872	Includes 30 in (76.2 cm) whip hose (109148), Z-Swivel (202577), and grease valve (242056)		

### **Swivel**

	Part Number	Description
933	202577	Z-Swivel allows non-binding movement for hard-to-reach locations, 1/4-18 NPT



## Fewer Strokes and Longer Pump Life

The GT 750 pump was engineered to perform in challenging applications and changing environments. The large 7.5-inch air motor and pump lower combination allows the GT 750 pump to move the same amount of grease with up to four times fewer pump strokes.



#### Efficient Air Motor

Use less air to move more grease.

#### **High Flow Rates**

Up to 32 lb/min of grease.

#### High Volume Per Stroke

Pump more grease without having to drive pump too quickly to damage seals.

### Proven Pump Technology

Based on Graco NXT™ pump technology.

### Multiple Tank Options

Available in 35, 120 and 400 lb down tube lengths.


#### **Typical Applications**

- Lube trucks
- Mining
- Heavy-duty dealerships
- · Fleet service facilities
- In-plant

#### Typical Fluids Handled

· Grease up to NLGI #2


#### **Pump Performance**



nnical Specifications	
Fluid Pressure Ratio	36:1
Air Pressure Operating Range	40-100 psi (3-7 bar)
Maximum Working Pressure	3,600 psi (248 bar)
Maximum Recommended Continuous Pump Speed	60 cycles per minute
Air Motor Effective Diameter	7.5 in (190 mm)
Stroke	4.75 in (121 mm)
Air Inlet	1/2 in NPT
Fluid Outlet	1 in NPT
Maximum Delivery	32 lb/min (13.6 kg/min)
Pump Weight	59 lb (26.8 kg)
Wetted Parts	Steel, brass, Buna-N, urethane ductile iron, aluminum
Sound Power (measured at 70 psi [4.8 bar], 20 CPM per ISO-9414-2)	77.2 dBa
Sound Pressure (tested at 3.28 ft [1 m] from equipment)	70.5 dBa
Pump Cycles Per Pound	3 cycles
Pump Cycles Per KG	6 cycles
Warranty	Five years overall and 1 year wear parts
Instruction Manual	3A5363

140











>>> Ordering Information

### GT 750 36:1 Grease Pumps

_	Part Number	Description
	24W498	GT 750, 36:1 Grease Pump, stubby length
	25D116	GT 750, 36:1 Grease Pump, 120 lb length
	24W337	GT 750, 36:1 Grease Pump, 400 lb length
	25P544	GT 750, 36:1 Grease Pump, 400 lb length inductor

### **Accessories**

### **Cam Lock Adapters**

Part Number	Description
131380	Male Cam Lock Adapter – 3 in
131394	Female Cam Lock Adapter – 3 in


### **Drum Covers**

	Part Number	Description
10000	204574	Cover for 120 lb (54 kg) drums
	200326 Cover for 400 lb (182 kg) drums	Cover for 400 lb (182 kg) drums
	160754	Bung Adapter Plate (used to mount pump to drum cover) – 2 in

### **Follower Plates**

	Part Number	Description
	223700	Follower plate for 120 lb (54 kg) drums
	223701	Follower plate for 400 lb (182 kg) drums





### **Move Large Amounts of Grease Fast**

Tested to outperform and outlast all other pumps on the market – with its long-life packing design and intuitive, easy-to-use controls – the NXT™ High-Flo pump is the best value for the money. Fewer parts, faster repairs, and long-lasting durability.

#### Optional DataTrak Control

Intuitive, easy-to-use DataTrak<sup>™</sup> control gives you pump diagnostics, material usage tracking and pump runaway protection.

#### **NXT Air Motor**

Modular design for easier maintenance with rugged body armor that won't rust or dent.

#### Modular Air Valves

Easy-to-repair valve eliminates stalling and contains deicing controls.

#### Integrated Air Controls

Easy-turn, lockable regulator is front-mounted for easy access. Compact and modular with built-in filtration.

### Piston Valve with Floating Piston Seal

For maximum pressure balance over a range of material viscosities.

#### **Typical Applications**

- · Fleet services facilities
- In-plant
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2




#### **Pump Performance**




#### **NXT 14:1 Check-Mate Pumps**

#### 14:1 (E) Check-Mate Pumps cycles/min 30 1600 (11.2, 112) Fluid Pressure in psig (MPa, bar) Air Flow in SCFM (m3/min) 1200 (8.4, 84) 120 (3.4) 800 B (5.6, 56) 400 © (2.8, 28)(6.4) (9.8) (14.8) (19.7) (24.6) (29.5) Fluid Flow in gpm (lpm)

### **NXT 26:1 Check-Mate Pumps**



### **NXT 29:1 Check-Mate Pumps**



chnical Specifications						
	NXT Check-Mate 14:1	NXT Check-Mate 26:1	NXT Check-Mate 29:1			
Fluid Pressure Ratio	14:1	26:1	29:1			
Air Motor	NXT 3400	NXT 6500	NXT 3400			
Air Motor Effective Diameter	7.5 in (191 mm)	10.4 in (264 mm)	7.5 in (191 mm)			
Pump Lower	L500CS	L500CS	L250CS			
Maximum Fluid Working Pressure	1,400 psi (97 bar / 9.7 MPa)	2,600 psi (179 bar / 17.9 MPa)	2,900 psi (200 bar / 20 MPa)			
Output per Cycle	15.4 oz (435 g)	15.4 oz (435 g)	7.7 oz (218 g)			
Air Inlet	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)			
Fluid Outlet	1-1/2 in NPT(M)	1-1/2 in NPT(M)	1 in NPT(F)			
Air Operation Range	0 psi to 100 psi (0 bar 7 bar)	0 psi to 100 psi (0 bar to 7 bar)	0 psi to 100 psi (0 bar to 7 bar)			
Max Recommended Pump Speed	20 cpm	20 cpm	20 cpm			
Cycles per Pound	1.0 cpp	1.0 cpp	2.1 cpp			
Cycles per Kg	2 cpk	2 cpk	5 cpk			
Wetted Parts	303, 304, 316 and 17-4PH grades of stainless steel; ductile iron and carbon steel, electroless nickel plated; carbon steel, zinc and electroless nickel plated; E52100 and ETD 150 alloy steel; PTFE; UHMWPE; carbon-filled PTFE; acetal	303, 304, 316 and 17-4PH grades of stainless steel; ductile iron and carbon steel, electroless nickel plated; carbon steel, zinc and electroless nickel plated; E52100 and ETD 150 alloy steel; PTFE; UHMWPE; carbon-filled PTFE; acetal	ETD 150, 41L40, and 4140 alloy steel; 304, 316, 17-4PH and 440C grades of stainless steel; acetal; carbon-filled PTFE; carbon steel; ductile iron; electroless nickel, zinc and chrome plating; PTFE; UHMWPE			
Sound Pressure Level	77 dB(A)	80 dB(A)	77 dB(A)			
Sound Power Level	87 dB(A)	90 dB(A)	87 dB(A)			
Approximate Weight	152 lb (69 kg)	169 lb (77 kg)	128 lb (58 kg)			
System – 312863 Pump – 312376 Pump Lower – 312375 Air Motor – 311238		System – 312863 Pump – 312376 Pump Lower – 312375 Air Motor – 311238	System — 312863 Pump — 312376 Pump Lower — 312375 Air Motor — 311238			



#### **Pump Performance**










TEST FLUID: No. 10 Weight Oil


#### **NXT 55:1 Check-Mate Pumps**

## 55:1 (E) Check-Mate Pumps cycles/min 6000 (42.0, 420) Fluid Pressure in psig (MPa, page (4570, 450) (MPa, page (4570, 450) (1470, 140) (1470, 140) (A) Flow in SCFM (m3/min) **B**

#### **NXT 63:1 Check-Mate Pumps**



#### **NXT 68:1 Check-Mate Pumps**



echnical Specifications						
	NXT Check-Mate 55:1	NXT Check-Mate 63:1	NXT Check-Mate 68:1			
Fluid Pressure Ratio	55:1	63:1	68:1			
Air Motor Effective Diameter	10.4 in (264 mm)	7.5 in (191 mm)	10.4 in (264 mm)			
Maximum Fluid Working Pressure	5,500 psi (379 bar / 37.9 MPa)	4,500 psi (310 bar / 31 MPa)	5,300 psi (366 bar / 36.6 MPa)			
Output per Cycle	7.7 oz (218 g)	3.1 oz (87 g)	6.1 oz (174 g)			
Air Inlet	3/4 in NPT(F)	3/4 in NPT(F)	3/4 in NPT(F)			
Fluid Outlet	1 in NPT(F)	3/4 in NPT(M)	1 in NPT(F)			
Air Operation Range	0 psi to 100 psi (0 bar to 7 bar)	0 psi to 72 psi (0 bar to 4.9 bar)	0 psi to 78 psi (0 bar to 5.4 bar)			
Max Recommended Pump Speed	20 cpm	20 cpm	20 cpm			
Cycles per Pound	2.1 cpp	5.2 cpp	2.6 cpp			
Cycles per Kg	5 cpk	11 cpk	6 cpk			
Wetted Parts	ETD 150, 41L40 and 4140 alloy steel; 304 and 17-4PH grades of stainless steel; acetal; carbon- filled PTFE; CS; ductile iron; eNi, Zn and chrome plating; UHMWPE	ETD 150, 41L40 and 4140 alloy steel; 304 and 17-4PH grades of stainless steel; acetal; carbon- filled PTFE; CS; ductile iron; eNi, Zn and chrome plating; UHMWPE	ETD 150, 41L40 and 4140 alloy steel; 304, 316 and 17-4PH grades of stainless steel; acetal; carbon-filled PTFE; CS; ductile iron; eNi, Zn and chrome plating; PTFE; UHMWPE			
Sound Pressure Level	80 dB(A)	87 dB(A)	80 dB(A)			
Sound Power Level	90 dB(A)	87 dB(A)	90 dB(A)			
Approximate Weight	145 lb (66 kg)	101 lb (46 kg)	145 lb (66 kg)			
System – 312863 Pump – 312376 Pump Lower – 312375 Air Motor – 311238		System — 312863 Pump — 312376 Pump Lower — 312375 Air Motor — 311238	System — 312863 Pump — 312376 Pump Lower — 312375 Air Motor — 311238			



# **Pump Packages with DataTrak**

Package Number	247973	247976	247974	247977	247975	247978
Ratio	14:1	26:1	29:1	55:1	63:1	68:1
Pump with DataTrak	P14MCS	P26MCS	P29MCS	P55MCS	P63MCS	P68MCS
Mounting Type	Floor Standing					
Mounting Number	223952	223952	223952	223952	223952	223952
3/4 in x 6 ft Air Hose	208610	208610	208610	208610	208610	208610
1 in x 6 ft Fluid Hose	115042	244657	244657	244657	244657	244657

# **Pump Packages without DataTrak**

Package Number	24E006	24E007	24E008	24E009	24E010	24E011
Ratio	14:1	26:1	29:1	55:1	63:1	68:1
Pump without DataTrak	P14DCS	P26DCS	P29DCS	P55DCS	P63DCS	P68DCS
Mounting Type	Floor Standing					
Mounting Number	223952	223952	223952	223952	223952	223952
3/4 in x 6 ft Air Hose	208610	208610	208610	208610	208610	208610
1 in x 6 ft Fluid Hose	115042	244657	244657	244657	244657	244657





# **RAM Pump Packages with DataTrak**

Package Number	247979	247980	247981
Ratio	14:1	63:1	68:1
RAM System	CM53BN	CM17BN	CM2RBN
3/4 in x 6 ft Air Hose	208610	208610	208610
1 in x 6 ft Fluid Hose	115042	244657	244657

# **RAM Pump Packages without DataTrak**

Package Number	24E780	24E781	24E782
Ratio	14:1	63:1	68:1
RAM System	CM515N	CM155N	CM2L5N
3/4 in x 6 ft Air Hose	208610	208610	208610
1 in x 6 ft Fluid Hose	115042	244657	244657





# Accessory Ordering Information

#### **Drum Covers**



Part Number	Description
200326	Cover for open-head 400 lb (180 kg) drums
204574	SD Cover for open-head 70 lb (32 kg) or 120 lb (55 kg)
24R350	LD Cover for open-head 35 lb (16 kg), 70 lb (32 kg) or 120 lb (55 kg) drums





# Field-Proven, Energy-Efficient

Hydraulic Dyna-Star pumps provide reliable, quiet, ice-free performance at maximum pressure and low-flow rates and are up to three times more energy efficient than comparable compressed-air systems.

#### **Built-In Reliability**

Self-lubricating vertical design for long life and reliable operation in high-vibration environments.

# Quiet Hydraulic Motor

No need for add-on mufflers.

## High-Efficiency Motor

Uses less hydraulic oil.

### **Typical Applications**

- Service shops
- · Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2

chnical Specifications		
Fluid Pressure Ratio	5:1	10:1
Pump Number	224912 – 35 lb (16 kg) 224751 – 120 lb (55 kg) 224752 – 400 lb (180 kg)	247540 - 60 lb (27 kg) 247443 - 120 lb (55 kg) 247450 - 400 lb (180 kg)
Applications	Grease Dispensing	Grease Dispensing
Maximum Input Pressure	1,500 psi (102 bar)	600 psi (41 bar)
Maximum Fluid Input Volume	3 gpm (11.4 lpm)	3 gpm (11.4 lpm)
Maximum Output Flow Rate	4 lb/min (1.8 kg)	1.1 lb/min (0.5 kg)
Maximum Recommended CPM	60	60
Maximum Fluid Output Pressure	7,500 psi (517 bar)	7,500 psi (517 bar)
Hydraulic Supply Inlet	3/8 in NPT	3/4 to 16 in JIC (37° Flare)
Hydraulic Return Outlet	3/4 in NPT	3/4 in NPT
Fluid Outlet	1/2 in NPT	1/2 in NPT
Maximum Incoming Fluid Temp.	130°F (54°C)	200°F (93°C)
Wetted Parts	Steel, copper, polyurethane, Buna-N, polyester elastomer	Steel, copper, polyurethane, Buna-N, polyester elastomer
Sound Pressure Level	77 dB(A)	77 dB(A)
Approximate Weight	224912 – 32.5 lb (14.7 kg) 224751 – 37.5 lb (17 kg) 224752 – 42 lb (19.1 kg)	247540 – 41 lb (18.6 kg) 247443 – 43.5 lb (19.7 kg) 247450 – 48 lb (21.8 kg)
Instruction Manual	308156	312350



# **Dyna-Star Hydraulic Pumps**

Part Number	Description
224912	5:1 Grease pump for 35 lb (16 kg) pails
224751	5:1 Grease pump for 120 lb (55 kg) drum
224752	5:1 Grease pump for 400 lb (180 kg) drum
247450	10:1 Grease pump for 35 lb (16 kg) pails
247443	10:1 Grease pump for 120 lb (55 kg) drum
247450	10:1 Grease pump for 400 lb (180 kg) drum

#### **Accessories**

#### **Drum Covers**



Part Number	Description
224915	Cover for 35 lb (16 kg) pail
204574	Cover for 120 lb (55 kg) drum
200326	Cover for 400 lb (180 kg) drum

#### **Follower Plates**



Part Number	Description
224916	Follower plate for 35 lb (16 kg)
223700	Follower plate for 120 lb (55 kg)
223701	Follower plate for 400 lb (180 kg)

# **Hydraulic Fluid Controls**

Required for each pump



Part Number	Description
236864	Dyna-Star Fluid Controls [1,500 psi (102 bar); 3 gpm (11.4 lpm)]. Includes manifold with pressure-reducing valve, flow control valve, pressure gauge, shut-off ball valves, and 3 ft (0.9 m) supply and return hoses. Instruction manual 308395.

## **Tie-Down Covers**



Part Number	Description
222060*	Dyna-Star, 5:1 tie-down cover for 120 lb (55 kg)
207366**	Dyna-Star, 5:1 tie-down cover for 400 lb (180 kg)

<sup>\*</sup>Use with hold-down kit 222061. \*\*Use with hold-down kit 207361.





# Field-Proven, Energy-Efficient

When paired with any of Graco's priming piston pumps, the Viscount II hydraulic motor offers exceptional cost savings by operating on 20% of the energy used by a pneumatic motor.

#### **Built-In Reliability**

Self-lubricating vertical design for long life and reliable operation in high-vibration environments.

#### **Quiet Hydraulic Motor**

# No need for add-on mufflers.

## **High-Efficiency Motor**

Uses less hydraulic oil.

## Typical Applications

- · Service shops
- · Heavy-duty dealerships
- Fleet services facilities
- In-plant
- · Lube trucks
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2

echnical Specifications		
Fluid Pressure Ratio	2.4:1	
Pump Number	222902 - 400 lb (180 kg)	
Applications	Grease Dispensing	
Maximum Input Pressure	1,500 psi (103.5 bar)	
Maximum Fluid Input Volume	12 gpm (45.4 lpm)	
Maximum Output Flow Rate	7.5 gpm (28.5 lpm)	
Maximum Recommended CPM	60	
Maximum Fluid Output Pressure	2,300 psi (159 bar)	
Hydraulic Supply Inlet	3/4 in NPT	
Hydraulic Return Outlet	1 in NPT	
Fluid Outlet	1-1/2 in NPT	
Maximum Incoming Fluid Temp.	130°F (54°C)	
Wetted Parts	Carbon steel; chrome, zinc and electroless nickel plating; 304 and 17-4 PH grades of stainless steel; E52100 alloy steel; ductile iron; acetal; PTFE; ultra-high-molecular weight polyethylene	
Sound Pressure Level	< 70 dB(A)	
Approximate Weight	196 lb (89 kg)	
Instruction Manual	308149	

# **Viscount® II Pumps**



# >>> Ordering Information

# **Viscount II Pumps**

Part Number	Description
222902	2.4:1 Grease Pump for 400 lb (180 kg) drum

#### **Accessories**

# **Hydraulic Fluid Controls**

Required for each pump



Part Number	Description
236865	Viscount II Fluid Controls [1,500 psi (102 bar); 3 gpm (11.4 lpm)]. Includes manifold with pressure-reducing valve, flow control valve, pressure gauge, shut-off ball valves, and 3 ft (0.9 m) supply and return hoses. Instruction manual 308395.



# **Manual Dispense from Bulk Containers**



<sup>\*</sup> Delivers 1/4 oz (0.7 grams) of grease per stroke at pressures to 3,000 psi (207 bar). Can service fittings directly or be used to charge a booster gun for more efficiency at higher pressures.

\*\* Fills all three-way loading grease guns equipped with filler fittings.

\*\*\* Dispense kit 203703 can be used for direct greasing applications (must be ordered separately).

# **Graco Dispense Valves and Guns Selection Guide**



#### **Grease Valves**

uitase vaives					1		
	Fluid	Type	Maximum Working Pressure	Maximum Flow Rate	Intended Use	Warranty	Reference Pages
Accu-Shot™	NLGI #2	Metered	8,000 psi (552 bar)	2 lb/min 1 kg/min	Indoor/ Outdoor	1 year	153
Pro Shot™	Grease up to NLGI #2	Non- Metered	8,000 psi (552 bar)	2 lb/min 1 kg/min	Indoor/ Outdoor	1 year	154
Power Shot™	Grease up to NLGI #2	Booster	Supply 5,000 psi (345 bar) Output 18,000 psi (1,242 bar)	N/A	Indoor/ Outdoor	1 year	155

Grease Guns							
	Fluid	Style	Maximum Working Pressure	Loading	Intended Use	Warranty	Reference Pages
Manual	Grease up to NLGI #2	Lever	6,000 psi to 10,000 psi (414 bar to 690 bar)	Cartridge/ bulk fill/ loader fill/ suction	Indoor/ Outdoor	1 year	156
Pneumatic	Grease up to NLGI #2	Pistol	6,000 psi (414 bar)	Bulk fill/ loader fill	Indoor/ Outdoor	1 year	156
Booster	Grease up to NLGI #2	Pistol	10,000 psi (690 bar)	Loader fill	Indoor/ Outdoor	1 year	156





- Fleet services facilities
- · Heavy-duty dealerships
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2

Tec	Technical Specifications					
	Maximum Working Pressure	5,000 psi (345 bar)				
	Metering System	Oval gears				
	Accuracy	± 3% with grease consistency (grade NLGI) 2/3				
	Repeatability (typical)	± 1% with grease consistency (grade NLGI) 2/3				
	Storage Temperature Range	-4°F to 158°F (-20°C to 170°C)				
	Operating Temperature Maximum	95 (%RU)				
	Battery	Standard alkaline batteries 2 x 1.5 Volt Size AA				
	Battery Life	18 to 24 months (depends on usage)				
	Dimensions (without extension)	8.8 in L x 1.8 in W x 4.4 H (22.4 cm L x 4.6 cm W x 11.2 cm H)				
	Weight	2.2 lb (1.0 kg)				
	Warranty	One year				

309454

#### Ordering Information

Part Number	Description	Includes	
233807	U.S. measurement, includes extension and hydraulic coupler	Standard nozzle extension (200389) and 1/4 in NPT inlet	
233933	Metric measurement, includes extension and hydraulic coupler		

Instruction Manual



# For Heavy-Duty Applications

Designed to perform in heavy-equipment shops, fleet maintenance shops, municipal garages and higher-volume in-plant applications with longer plumbing runs and larger fluid usage.



# **Adjustment Nut**

Protected by rigid guard.

Pressure-Assisted Trigger

For ease of operation.

Easy Top Adjustment

With locking nut.

Rugged Design

For harsh environments.

#### **Typical Applications**

- · Fleet services facilities
- · Heavy-duty dealerships
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2

Tecl	Technical Specifications					
	Maximum Working Pressure	8,000 psi (552 bar)				
	Inlet Size	1/4 in or 3/8 in				
	Wetted Parts	Chrome vanadium, polyurethane, brass, carbon steel, alloy steel				
	Warranty	One year				
	Instruction Manual	309032				

#### Ordering Information

	Description	NPT		
	Description	1/4 in	3/8 in	
1	Non-metered grease valve with standard nozzle extension (200389)	242056	242058	
1	Bare non-metered grease valve only	242055	242057	
1	Non-metered grease valve package. Includes Grease Valve (242056), Z-Swivel (202577) and Whip Hose (109148).			
1	Non-metered grease valve package. Includes Grease Valve (242055), coupler (200325) and Whip Hose (109145).	26C184	-	





- Fleet services facilities
- · Heavy-duty dealerships
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

• Grease up to NLGI #2

Тес	Technical Specifications					
	Maximum Input Pressure	5,000 psi (34 MPa, 345 bar)				
	Maximum Delivery Pressure	Up to 18,000 psi (124 MPa, 1241 bar)				
	Inlet Size	1/8 NPT female				
	Wetted Parts	Alloy steel, carbon steel, chrome alloy, copper, leather				
	Weight	3 lb (1.4 kg)				
	Height	7 in (178 mm)				
	Length	11.675 in (296 mm)				
	Warranty	One year				
	Instruction Manual	306271				

# Ordering Information

Part Number	Description
202600	1/8 NPT(F) Power Shot booster Valve. Includes nozzle (200389)

#### **Accessories**

Part Number	Description
202579	Hose swivel (must be ordered separately)





# Lever-Action and Pistol-Style Grease Dispensing Guns

Durable design for years of trouble-free use in demanding environments. Reduces downtime and is easy to load - two- or three-way loading capability makes it easy to keep on greasing.



# **Ordering Information**

	Part Number	Style	Gun Type	Pressure psi (bar)	Loading	Includes				
	112196	Pneumatic	Pistol	6,000 (414)	Bulk fill/ loader fill	Rigid extension and hydraulic coupler				
	203697	Booster	Pistol	10,000 (690)	Loader fill	Rigid extension				
	110218		Lever -	6,000 (414)	Cartridge/bulk fill	Rigid extension and hydraulic coupler				
	110216					Rigid extension, hydraulic coupler and air bleeder valve				
K	110203	Manual		Pistol	Pistol	Pictol	Pietol	10,000 (690)	Cartridge/ bulk fill/ loader fill	Rigid extension, hydraulic coupler and air bleeder valve
2	110202							12 in (30.4 cm) flexible extension, hydraulic coupler and air bleeder valve		
-	110201		Suction	-	Suction	12 in (30.4 cm) clear plastic hose				

#### **Accessories**


Part Number	Description	
109145	12 in (30.4 cm) clear plastic hose without coupler	
112255	18 in (45.8 cm) clear plastic hose without coupler	



#### **Z-Swivels**

	Maximum Working Pressure psi (bar)	Inlet	Outlet	Thread	Part Number
	6,500 (450)	1/8 in	1/4 in	NPT	202579
	6,500 (450)	1/4 in	1/4 in	NPT	202577
	6,500 (450)	3/8 in	3/8 in	NPT	224569
	6,000 (414)	1/2 in	1/2 in	NPT	207948

# **Straight Swivels**



#### 360° Swivels



Part Number	Includes	
Fait Number	Fitting	Coupler
203597	203198	200325
203198	203198	_

#### **Nozzles**

Part Number	Description	
200389	Standard nozzle. Includes straight 6 in (15.2 cm), 1/8 NPT(M) extension tube (197471) and tapered nose coupler (200325).	
204072	Swivel nozzle. Includes straight 6 in (15.2 cm), 1/8 NPT(M) extension tube (197471) and tapered nose coupler (200325). Coupler has 360° swivel adapter (203198) for added convenience.	
204897	vivel nozzle. Includes straight 12 in (30.4 cm), 1/8 NPT(M) extension tube (155836) and tapered nose coupler 00325). Coupler has 360° swivel adapter (203198) for added convenience.	
204204*	Flexible 12 in (30.4 cm) hose nozzle. 1/8 NPT(M) includes tapered-nose coupler (200325).	
203504*	lexible 12 in (30.4 cm) hose nozzle. 1/8 NPT(M) includes tapered-nose coupler (200325) and lock-sleeve onnector (203497) for quick connection to any grease nozzle having tapered-nose coupler.	
109145	2 in (30.4 cm) hose nozzle without coupler.	
112255	18 in (45.8 cm) hose nozzle without coupler.	
109148*	30 in (76.2 cm) hose nozzle without coupler, has 1/8 NPT(M) both ends. Use as alternate for rigid nozzle with tapered-nose coupler 200325.	







# **Couplers**

Part Number	Description	
200325 1/8 NPT(F) inlet standard tapered-nose coupler. Hardened jaws grip grease fittings through wide-sealing angle, but release easily. Maximum working pressure 8,000 psi (551 bar).		
202650	202650 1/8 NPT(F) inlet standard straight-nose grease coupler for manual operated grease guns only.  Maximum working pressure 3,000 psi (206 bar).	
200020	1/8 NPT(F) inlet standard button-head coupler. Gives fast, positive seal on button-head fittings.	
200021	1/8 NPT(F) inlet giant button-head coupler. Gives fast, positive seal on larger button-head fittings.	





#### **Adapters**

Adapters have lock-sleeve quick-connector; works with any grease nozzle with a tapered-nose coupler.

Part Number	Description	
201881	Hydraulic-to-push adapter. Used for U-joints and low-pressure service.	
205532	Hydraulic-to-steel needle adapter. Used for flush fittings. 250 psi (17 bar) max. Not for air grease applications or guns.	
205582	Hydraulic-to-nylon needle adapter. Used for removable plugs. 250 psi (17 bar) max. Not for air grease applications or guns.	
223187	90° hydraulic-to-push adapter (K-car). Refer to instruction manual 306708.	
203497	Lock-sleeve connector. 1/8 NPT(F) outlet. Allows for quick connection to tapered-nose coupler. Inlet is standard grease fitting with sleeve to lock connector in place.	
236171	Easy-fill valve. For faster loading of Graco hand grease guns with gun loaders. Replaces hydraulic fittings on all grease guns with 1/8 NPT(F).	
204929	Grease loader valve. For use with lever-operated, high-volume grease pumps. Permits quick bulk filling of hand-operated grease lever guns equipped with easy-fill valve 236171.	
205592	Hydraulic adapter assortment package. Contains needle adapter (205568), plug adapter (205554), push adapter (201881), nylon needle adapter (205582), hydraulic-to-steel needle adapter (205532) and whip hose nozzle connector (203504).	





205582





# Tapered Thread Grease Fittings, 10,000 psi (690 bar) (steel; ball check)

Part Number	Shank	Description
100054	9/32	1/8 NPT straight
101277	1-9/32	1/8 NPT straight
100970	9/32	1/8 NPT 30° angle
100834	9/32	1/8 NPT 45° angle
100971	9/32	1/8 NPT 65° angle
100833	9/32	1/8 NPT 90° angle
100848	3/8	1/4 NPT 67° angle
100846	3/16	1/4-28 tapered SAE-LT straight
100847	13/64	1/4-28 tapered SAE-LT 45° angle
101283	3/16	1/4-28 tapered SAE-LT 90° angle
101281	11/32	1/4-28 tapered SAE-LT straight
110702	19/64	1/4-28 tapered SAE-LT 65° angle
100835	12/32	1/4 NPT straight













# 1/4 in Tapered Thread-Forming Grease Fittings, 10,000 psi (690 bar) (steel; ball check)

Part Number	Shank	Description
110703	13/64	1/4-28 straight
110705	13/64	1/4-28 90° angle

## **Drive-Type Grease Fittings (steel)**

Part Number	Shank	Description
110706	3/32	3/16 drill straight
110709	7/32	3/16 drill 65° angle
110713	1/4	3/16 drill straight without ball check
101312	7/32	3/16 drill straight with ball check
110710	1/4	5/16 drill straight with ball check
101287	17/64	1/4 drill straight without ball check



## **Standard Button-Head Grease Fitting (steel)**

1/4 in Tapered Thread Grease Fittings (steel; ball check)

Part Number	Shank	Description
100837	7/16	1/4 NPT straight
101297	33/64	3/8 NPT straight
110711	35/64	1/2 NPT straight



# **Giant Button-Head Grease Fitting (steel)**

Part Number	Shank	Description
110712	9/16	3/8 NPT straight
100854	1/2	1/4 NPT straight



#### **Easy-Outs**

Part Number	Description
101604	3/8 NPT straight
101605	1/4 NPT straight




#### **Grease Accessory Packages**

Convenient storage box contains the following threaded fittings in the quantities listed:

Part Number	Package Includes			
	Quantity	Grease Fitting No.	Shank	Description
	30	100054	9/32	1/8 NPT straight
202654	10	100970	9/32	1/8 NPT 30° angle
	10	100833	9/32	1/8 NPT 90° angle
	20	100846	3/16	1/4-28 straight
	10	100847	13/64	1/4-28 45° angle



Notes	
	······································



# Flexible Installation – Solutions for Every Application

Choose from configured packages or build a custom DEF system specific to your application with individual pumps and components. From the economical hand pumps to the high-performance electric or air-operated double diaphragm (AODD) packages, Graco has you covered. Every solution is designed with the highest-quality components for trouble-free operation.







# **How to Choose Your Graco DEF Solution:**



# **Identify your power supply**

Choose the pump that's right for your application. Choose the lightweight and reliable manual hand pump for small applications. The LD Blue electric pumps are recommended for applications up to 50 ft, or upgrade to the SD Blue AODD pump for longer applications, up to 200 ft.







# **Determine your container size**\*

Whether dispensing from a drum or a tote container, Graco has the package that fits your needs. Fifty-five gallon drums are ideal for one or two truck operations, and for larger fleets choose 275 or 330 gallon IBC totes.

\*Tote and drum not for sale from Graco



# **Choose your accessories**

Graco offers a full line of high-quality DEF accessories to complement your installation. Select from automatic or manual dispense nozzles, closed-system couplers, in-line meters, hose reels, mounting brackets, fittings, and dispense and suction hoses.



reducing the need for maintenance.



# A Reliable Industrial Pump with Self-Priming Capabilities

Whether you own a small garage, large dealership or heavy equipment maintenance facility, Graco has a complete line of diesel exhaust fluid (DEF) products for every application. Our electric, pneumatic or manual products are engineered specifically for the advanced needs of DEF fluid and are designed to minimize downtime and dispense materials quickly without compromising chemical integrity.



## **Built-In Safety and Reliability**

Automatic shut-off timer (6.5 min) incorporated into the 120V pump. Prevents the pump from running past the duty cycle and maximizes the life of the pump.

#### Stay Up and Running Longer

Reduce downtime and get more work done with the LD Blue systems – up to twice the life of competitive pumps.



## **Typical Applications**

- · Automotive and heavy-duty dealerships
- Agriculture
- · Service and fast lube centers
- · Fleet service facilities

#### Typical Fluids Handled

Diesel exhaust fluid

Tecl	Technical Specifications				
		120V	12V		
	Maximum Flow Rate	9 gpm	9.5 gpm		
	Maximum Fluid Pressure	50 psi	50 psi		
	RPM	1,750	2,600		
	Watts	500	260		
	Voltage	120V / 60hz	12V		
	Maximum Amperage	4.5A	22A		
	Duty Cycle	20 min ON/OFF	20 min ON/OFF		
	Listings	Approved to US and Canadian Standards	CE		

# >>> Ordering Information

#### **Pump Only**

Part Number	Part Number Description	
127642	120V AC electric pump, 3/4 in barbed hose tail	
127643	12V DC electric pump, 3/4 in barbed hose tail	



# **LD Blue Electric Pump Packages**





# **LD Blue Electric Pump Packages**







Package 24V646 installed on tote (not included in package).



# **Superior-Performing AODD Pump** Capable of Higher Output Over Longer Runs

Whether for a small garage, large dealership or heavy equipment maintenance facility, our pneumatic pumps are engineered specifically for the advanced needs of DE fluid and are designed to minimize downtime and dispense materials quickly without compromising chemical integrity.

#### Modular Air Valve

Stall-free, low-pulsation air valve provides smooth and rapid changeover for increased efficiency and minimizes downtime.

#### Robust Design

Bolt-through fluid cover design eliminates leaks and provides better safety and more reliability.

#### Versatility

The Husky 515 pump delivers up to 15 gpm and works on as little as 30 psi.

# Rugged Construction

Resists corrosion for reliable performance and long life.

#### **Typical Applications**

- · Automotive and heavy-duty dealerships
- · Service and fast lube centers
- Fleet service facilities
- In-plant
- Lube trucks

#### Typical Fluids Handled

Diesel exhaust fluid

Technical Specifications	
Maximum Flow Rate	15 gpm
Maximum Fluid Pressure	50 psi
Air Operating Range	30-50 psi
Air Inlet	1/4 in NPT(F)
Pump Inlet	3/4 in BSPP(F)
Hose Inlet	3/4 in BSPP(F)
Pump Outlet	3/4 in BSPP(F)
Maximum Air Consumption	28 scfm

# Ordering Information

Part Number	Description	Inlet/Outlet
24G745	SD Blue Husky 515 pump	3/4 in BSPP



166



# **SD Blue Pump Tote Packages**









	Deluxe		Standard	
Package Number	24F531	24F878	24V677	24V678
Mount Type	Tote/Wall	Tote/Wall	Tote/Wall	Tote/Wall
Type of Nozzle	Automatic	Automatic	Automatic	Automatic
Air-Operated Pump	24G745	24G745	24G745	24G745
Mounting Bracket	24F870	24F870	24W186	24W186
Valve/Nozzle	24F529	24F529	127649	127649
Meter	24G738	-	127663	-
Drum Quick Connect Kit	24F532	24F532	-	-
Air Regulator and Gauge	110147	110147	-	-
Air Shut-Off Ball Valve, Vented	110223	110223	-	-
50 psi Air Safety Valve	124963	124963	116306	116306
Dispense Hose	124603	124603	24W161	24W161
Dispense Hose Length	20 ft	20 ft	20 ft	20 ft
Suction Hose	124581	124581	24W149	24W149
Suction Hose Length	6 ft	6 ft	5 ft	5 ft
Fittings (2)	3/4 in BSPP(MBE)	3/4 in BSPP(MBE)	SST Clamps	SST Clamps

Package 24V677 installed on a 275 gallon tote (tote and coupler not included in package).





# **SD Blue Pump Drum Packages**









	Deluxe		Standard	
Package Number	24F947	24M499	24V679	24V686
Mount Type	Drum	Drum	Drum	Drum
Type of Nozzle	Manual	Automatic	Manual	Automatic
Air-Operated Pump	24G745	24G745	24G745	24G745
Mounting Bracket	24F679	24F679	24W185	24W185
Valve/Nozzle	125078	24F529	125078	127649
Meter	-	24H293	-	127663
Drum Quick Connect Kit	24F532	24F532	-	_
Air Regulator and Gauge	110147	110147	-	-
Air Shut-Off Ball Valve, Vented	110223	110223	-	-
50 psi Air Safety Valve	124963	124963	116306	116306
Dispense Hose	125079	124671	24W154	24W154
Dispense Hose Length	12 ft	12 ft	12 ft	12 ft
Suction Hose	124875	124875	24W148	24W148
Suction Hose Length	2 ft	2 ft	2 ft	2 ft
Fittings (2)	3/4 in BSPP(M)	3/4 in BSPP(M)	SST Clamps	SST Clamps

Package 24V686 installed on 55 gallon drum (not included in package).







## **Features and Benefits**

- Lightweight, reliable and cost-effective solution for dispensing DEF from 55 gallon drums
- Quick drum installation and change-out with integrated 2 inch bung adapter
- Fast delivery capable of 11 oz per stroke
- Adjustable telescoping downtube

## Typical Applications

- · Automotive and heavy-duty dealerships
- Agriculture
- Service and fast lube centers
- · Fleet service facilities
- In-plant

#### Typical Fluids Handled

· Diesel exhaust fluid

#### **Technical Specifications**

Maximum Flow Rate

11 oz per stroke

# >>> Ordering Information

	Part Number	Description
	127647	DEF hand pump with drum-length adjustable downtube (125479)
24G636 DEF hand pump (127647), 6 ft dispense hose with ball valve (125478), drum length adjustable downtube (125479)		DEF hand pump (127647), 6 ft dispense hose with ball valve (125478), drum length adjustable downtube (125479)
	127875	DEF hand pump (127647), 6 ft dispense hose with ball valve (125478), drum length adjustable downtube (125479), LD manual nozzle (125078)

#### **Accessories**

Part Number	Description
125479	Drum length adjustable downtube for hand pump
125478	6 ft dispense hose with ball valve





- Automotive and heavy-duty dealerships
- Mining
- Service and fast lube centers
- · Fleet service facilities
- In-plant
- Lube trucks

#### Typical Fluids Handled

· Diesel exhaust fluid

## **Features and Benefits**

- Tracks totals in two modes reset for periodic history and non-reset for meter life
- Durable design for rugged use
- Easy to use dispenses pints, quarts, liters or gallons
- 0.5 gpm to 15 gpm flow rate
- 1500 psi maximum pressure, 1/2 in NPT inlet

Technical Specifications		
Flow Range	0.5 gpm to 15 gpm (1.9 lpm to 57 lpm)	
Maximum Working Pressure	1,500 psi (103 bar)	
Units of Measure	Quarts, pints, gallons, liters (factory-set to quarts)	
Weight	1.8 lb (0.8 kg)	
Accuracy	± 2.5%	
Inlet/Outlet	1/2 in BSPP	
Maximum Totalizer	99,999	
Maximum Recorded Dispense	999.99	
Operating Temperature Range	-4°F to 122°F (-20°C to 50°C)	
Storage Temperature Range	-13°F to 122°F (-25°C to 50°C)	
Outdoor Use	No	
Battery	2 AA alkaline	
Wetted Parts	Stainless steel, PBT (polybutylene terephthalate), nickel, fluoroelastomer	
Meter Pressure Loss	22 psi (1.5 bar) @ 14 gpm (53 lpm)	
Instruction Manual	313048	

# Ordering Information

Part Number	Description	
24G738	SDI15 DEF meter, 1/2 in BSPP(F/F), 1,500 psi, 0.5 to 15 gpm	
24H293	SDI15 meter kit with fittings for SST auto nozzle. Includes SDI15 Meter (24G738), Swivel (124964), Nipple Fitting (24H292), Adapter Fitting (16G760) and Elastomeric Seal (124965).	

170





- · Automotive and heavy-duty dealerships
- Service and fast lube centers
- · Fleet service facilities
- In-plant

#### Typical Fluids Handled

• Diesel exhaust fluid

# **Features and Benefits**

- Easy to install use in-line or at the end of the dispense hose
- Impulse signals single channel or reed switch
- 1.3 gpm to 26.4 gpm flow rate
- Rotatable display 4 positions
- 1 in BSPP(M) inlet and outlet. Includes 1 in BSPP(F) coupler.

Technical Specifications		
Flow Range	1.3 gpm to 26.4 gpm (4.9 lpm to 100 lpm)	
Maximum Working Pressure	145 psi (10 bar)	
Units of Measure	Quarts, pints, gallons, liters (factory-set to quarts)	
Weight	0.6 lb (0.25 kg)	
Accuracy	± 1.0%	
Inlet/Outlet	1 in BSPP(M)	
Maximum Totalizer	99,999	
Maximum Recorded Dispense	999.99	
Operating Temperature Range	14°F to 122°F (-10°C to 50°C)	
Storage Temperature Range	-4°F to 158°F (-20°C to 70°C)	
Outdoor Use	No	
Battery	2AAA alkaline	
Wetted Parts	SST, plastic, rubber	
Meter Pressure Loss	5 psi (0.3 bar) @ 26.4 gpm (100 lpm)	
Instruction Manual	333467	

# >>> Ordering Information

Part Number	Description
127663	LD digital in-line turbine meter, LCD display

#### **Accessories**

Part Number	Description
127800	Adapter – SD auto nozzle connection to LD meter







- Easy break-away system for low-cost repairs if the spout becomes detached
- · Choose with or without built-in meter
- 4 gpm to12 gpm flow rate
- 50 psi maximum pressure
- 3/4 in BSPP inlet to transform nozzle into optional mis-filling system to prevent mis-fills
- · Stainless steel spout

Te	Technical Specifications		
		Automatic Shut-Off Nozzle	Automatic Shut-Off Nozzle with Meter
	Flow Range	4 gpm to 12 gpm (15 lpm to 45 lpm)	4 gpm to 12 gpm (15 lpm to 45 lpm)
	Maximum Working Pressure	50 psi (3.5 bar)	50 psi (3.5 bar)
	Units of Measure	_	Quarts, pints, gallons, liters (factory-set to quarts)
	Weight	1.3 lb (0.6 kg)	1.8 lb (0.8 kg)
	Accuracy	_	± 1%
	Inlet	1 in BSP	1 in BSP
	Maximum Totalizer	_	999,999
	Maximum Recorded Dispense	-	99,999
	Operating Temperature Range	-4°F to 130°F (-20°C to 55°C)	14°F to 122°F (-10°C to 50°C)
	Storage Temperature Range	-40°F to 140°F (-40°C to 60°C)	-4°F to 158°F (-20°C to 70°C)
	Outdoor Use	Yes	No
	Battery	-	2AA alkaline
	Wetted Parts	SST, rubber, plastic	SST, rubber, plastic
	Meter Pressure Loss	13 psi (0.9 bar) @ 9.3 gpm (35 lpm)	13 psi (0.9 bar) @ 9.3 gpm (35 lpm)
	Instruction Manual	333468	333469

- Automotive and heavy-duty dealerships
- Service and fast lube centers
- Fleet service facilities
- In-plant

#### Typical Fluids Handled

· Diesel exhaust fluid

# **Ordering Information**

Part Number	Description
127649	LD automatic nozzle with stainless steel breakaway spout
127650	LD automatic nozzle with built-in electronic turbine meter, with stainless steel breakaway spout

#### **Accessories**

	Part Number	Description
	127651	Spout replacement kit for LD nozzles 127649 and 127650
	127652	Magnetic mis-fill spout kit for LD automatic nozzles
0	127654	Magnetic adapter for mis-fill kit





#### **Features and Benefits**

- · Heavy-duty design
- Automatic shut-off valve with stainless steel nozzle
- 11 gpm flow rate
- 50 psi maximum pressure
- 3/4 in BSPP inlet

#### **Typical Applications**

- Automotive and heavy-duty dealerships
- Minir
- · Service and fast lube centers
- · Fleet service facilities
- In-plant
- Lube trucks

## Typical Fluids Handled

· Diesel exhaust fluid

# >>> Ordering Information

Part Number	Description
124398	SD automatic shut-off SST nozzle without swivel, 3/4 in BSPP(F)
24F529	SD automatic shut-off SST nozzle with swivel, 3/4 in BSPP(F)
127655	SD automatic shut-off SST nozzle, 3/4 in hose barb

# **LD Blue Manual Nozzle**

#### **Typical Applications**

- Automotive and heavy-duty dealerships
- · Service and fast lube centers
- Fleet service facilities
- In-plant

#### Typical Fluids Handled

• Diesel exhaust fluid

#### **Features and Benefits**

- Manual shut-off valve with stainless steel nozzle
- High 20 gpm flow rate
- 50 psi maximum pressure
- 3/4 in BSPP inlet
- Lightweight under 1 lb

>>> Ordering	Information

Part Number	Description
125078	LD manual DEF nozzle with SST spout







# **Features and Benefits**

- For use with SD and LD pumps (LD pump with manual nozzle only)
- Stainless steel fluid section with open porting ensures high fluid flow with minimal pressure loss
- Flexible positioning of guide arm for mounting on bench, ceiling, wall, tote or utility truck
- 50 psi maximum pressure
- 3/4 in x 50 ft inlet hose with 3/4 in BSPP(M) swivel connection to provide leak-free connection

#### **Typical Applications**

- · Automotive and heavy-duty dealerships
- · Service and fast lube centers
- · Fleet service facilities
- In-plant
- Lube trucks

#### Typical Fluids Handled

· Diesel exhaust fluid

Technical Specifications		
Operating Temperature Range	12°F to 140°F (-11°C to 60°C)	
Maximum Working Pressure	50 psi (3.5 bar)	
Wetted Parts (Bare Reel Only)	Zinc plated steel, polyurethane, steel	
Weight (Without hose)	98 lb (44.5 kg)	
Sound Pressure Level	85.8 dB (A)	
Sound Power Level	94.9 dB (A)	
Instruction Manual	3A0138	

# Ordering Information

#### **Hose Reels**

Part Number	Description
HSDD5A	XD 30 DEF hose reel, 3/4 in x 50 ft, white, BSPP
HSDD5B	XD 30 DEF hose reel, 3/4 in x 50 ft, blue, BSPP
HSDD5F	XD 30 DEF hose reel, 3/4 in x 50 ft, yellow, BSPP
HSDDDA	XD 30 DEF hose reel, bare, white, BSPP
HSDDDB	XD 30 DEF hose reel, bare, blue, BSPP
HSDDDF	XD 30 DEF hose reel, bare, yellow, BSPP

#### **Hose Reel Inlet Kits**

A hose inlet kit is required when ordering an XD reel.

Part Number	Description
24W250	2 ft DEF inlet hose kit for XD 30 reels. 3/4 in BSPP(F) x cut end and 90° elbow.
24W251	6 ft DEF inlet hose kit for XD 30 reels. 3/4 in BSPP(F) x cut end and 90° elbow.
124875	2 ft DEF hose, 3/4 in BSPP(M) x cut end (inlet hose)
124581	6 ft DEF hose, 3/4 in BSPP(M) x cut end (inlet hose)




#### **Mounting Brackets**



Part Number Description		Description
	24F870	AODD tote/wall mounting bracket with nozzle holder
	24F679	AODD drum mounting bracket with nozzle holder
124541		AODD nozzle bath holder

#### **Dispense and Suction Hoses**



## **Pump Handle**

Part Number	Description
127646	Black handle for 12V DC pump



# **Fittings**

rittings	Part Number	Description		
	127656	1 in BSP(F) elbow fitting, black		
8	127657	1 in BSP(F) x 3/4 in barb hose tail, black		
00	127720	1 in BSP(F) x 1 in BSP(F) linear socket, black		
	127804	3/4 in x 1 in BSPP(F) swivel fitting with seals		
anne o	127805	1 in BSPP(F) x 1 in BSPP(F) coupler		
	127806	1 in BSPP(M/F) swivel, white		
	127815	3/4 in BSP x 3/4 in barb SST swivel hose tail		
	127823	1 in BSP x 3/4 in barb elbow, white		
	116306	1/4 in NPT, 50 psi air safety valve for Standard AODD pump packages		
-0	124963	1/8 in NPT, 50 psi air safety valve for Deluxe AODD pump packages		
8	24F524	3/4 in BSPP(M) x 3/4 in BSPP(F) SST swivel		



Maintaining fluid purity is essential to the longevity of your equipment and maintaining selective catalytic reduction (SCR) engines. With a closed-system design you can minimize fluid contamination and prevent spills. Choose from a variety of industry-accepted closed-system inlet kits to best suit your needs.

#### Colder

DrumQuick® PRO Quick Connect Coupler System. Economical polypropylene assembly can withstand thousands of quick and fast connections.

Part Number		Description	
	24F532	Colder closed-system coupler kit – includes drum coupler (124548), drum insert (124549) and downtube (124550)	
	124548	Colder closed-system drum coupler	
	124549	Colder closed-system drum insert	
	125014	Colder closed-system drum insert with buttress thread	
	124550	Colder closed-system 47 in downtube	

DrumQuick® is a registered trademark of Colder Products Company.

# **Closed-System Coupler Accessories**



# >>> Ordering Information

#### **Micro Matic**

Reusable Stainless Valve (RSV) is ideal for multi-use applications and is simple to integrate with drums, totes and custom packages.

Economic Plastic Valve (EPV<sup>™</sup>) is designed for one-way, single-use applications. Engineered for use when operations require the container package to be used once, emptied and recycled.

	Part Number	Description
	17C907	Micro Matic EPV dispense coupler, 3A orange, 3/4 in barbed outlet, EPDM seals
	127634	Micro Matic EPV container valve, 3A orange, 2.5 in x 5 buttress, EPDM Seals
	127793	Micro Matic EPV downtube for 55 gal drum
	127794 Micro Matic EPV center downtube for 275 gal IBC tote	
	127635	Micro Matic EPV center downtube for 330 gal IBC tote
	17C908	Micro Matic RSV dispense coupler, 3/4 in barbed outlet, 4 pin, stainless steel
	127637	Micro Matic RSV container valve, 2.5 in x 5 in, 4 cam, stainless steel valve, EPDM seals
	127795	Micro Matic RSV downtube for 55 gal drum
Ů	127796	Micro Matic RSV center downtube for 275 gal IBC tote
Ť.	127639	Micro Matic RSV center downtube for 330 gal IBC tote
	127640	Micro Matic RSV fill coupler, 1 in NPT(M) inlet x 1/4 in NPT(F) outlet, 4 pin, stainless steel

EPV<sup>™</sup> is a trademark of Micro Matic USA, Inc.






# **Micro Matic Packages**

Includes coupler, valve and downtube.

 cludes couplet, valve and downtube.			
Part Number	Description		
24W142	Micro Matic EPV suction package – coupler (17C907), container valve (127634), 55 gal downtube (127793)		
24W141	Micro Matic EPV suction package – coupler (17C907), container valve (127634), 275 gal downtube (127794)		
24W140	Micro Matic EPV suction package – coupler (17C907), container valve (127634), 330 gal downtube (127635)		
24W145	Micro Matic RSV suction package – coupler (17C908), container valve (127637), 55 gal downtube (127795)		
24W144	Micro Matic RSV suction package – coupler (17C908), container valve (127637), 275 gal downtube (127796)		
24W143	Micro Matic RSV suction package – coupler (17C908), container valve (127637), 330 gal downtube (127639)		

Notes		



# **Diaphragm Pump Selection Guide**











Husky 307  Husky 515	D31255	Husky 307 Acetal – 3/8 in Acetal/TPE	<ul><li>Oil evacuation</li><li>Oil transfer</li><li>Water</li><li>Anti-freeze</li><li>Windshield wash fluid</li></ul>	-	100 psi (6.9 bar)	185
Husky 515	243669					
		Husky 515 Acetal Split Inlet – 3/4 in Acetal/Buna Dual Inlet	50/50 windshield wash solution     Water     Anti-freeze	-	100 psi (6.9 bar)	186
Husky 716	241906	Husky 716 Aluminum – 3/4 in Aluminum/Buna-N	Oil evacuation Oil transfer Water Anti-freeze Windshield wash fluid	-	100 psi (6.9 bar)	187
Husky 1050	647016	Husky 1050 Aluminum – 1 in Aluminum/TPE	Water     Anti-freeze     Fuel transfer     Gasoline (up to 10% ethanol)	UL	100 psi (6.9 bar)	183-184
Husky 1050	647731	Husky 1050 Aluminum – 1 in Aluminum/Buna-N	Oil evacuation     Oil transfer	UL	100 psi (6.9 bar)	183-184
Husky 1050	647648	Husky 1050 Aluminum – 1 in Aluminum/TPE	Fuel dispense     Gasoline (up to 10% ethanol)	UL	50 psi (3.5 bar)	183-184
Husky 1590	DB3525	Husky 1590 Aluminum – 1.5 in Aluminum/TPE	Oil evacuation Oil transfer Water Anti-freeze	-	120 psi (8.3 bar)	188
Husky 2150	DF3525	Husky 2150 Aluminum – 2 in Aluminum/TPE	Oil evacuation Oil transfer Water Anti-freeze	-	120 psi (8.3 bar)	189
Husky 3300	652002	Husky 3300 Aluminum – 3 in Aluminum/TPE	Oil evacuation Oil transfer Water Anti-freeze	-	125 psi (8.6 bar)	190













# Efficiency, Performance and Best-in-Class Engineering

Husky pneumatic double-diaphragm pumps feature a stall-free, low-pulsation air valve, which provides a smooth and rapid changeover. Typical applications include oil transfer and evacuation, fuel dispense and transfer, windshield wash solution dispense, and water and anti-freeze dispense. Some models UL-approved for use in pumping gasoline and gasoline/alcohol blends up to 10% ethanol, diesel fuel, fuel oil and lubricating oil.



#### Modular Air Valve

Stall-free, low-pulsation operation provides smooth and rapid changeover

#### One-Piece Center Section

Eliminates air leaks for more efficient operation

### Longer Diaphragm Life

Up to 5x longer diaphragm life for less maintenance and downtime

#### Four-Bolt Joint Design

Bolted design provides even sealing pressure for leak-free operation

### Multiple Ports

Increased number of ports for installation flexibility


#### **Typical Applications**

- · Automotive dealerships
- Fast lube centers
- · Service shops
- · Heavy-duty dealerships
- Fleet services facilities
- In-plant
- Lube trucks
- Mining

#### Typical Fluids Handled

- 0il
- Fuel
- Water
- Anti-freeze
- Washer fluid

#### **Pump Performance**



AIR PRESSURE (A) = at 125 psi (8.3 bar, 0.83 MPa) (B) = at 100 psi (7 bar, 0.7 MPa) (C) = at 70 psi (4.8 bar, 0.48 MPa) (D) = at 40 psi (2.8 bar, 0.28 MPa) LEGEND Air Consumption • • • • • Fluid Pressure

**G** graco.com

# **Husky 1050 AODD Pump**











Maximum fluid working pressure	
Transfer Pump	100 psi (6.9 bar, 0.69 MPa)
Fuel Dispense Pump	50 psi (3.5 bar, 0.35 MPa)
Air pressure operating range	
Transfer Pump	20 psi to 100 psi (1.4 bar to 6.9 bar, 0.14 MPa to 0.69 MPa)
Fuel Dispense Pump	0 psi to 50 psi (1.4 bar to 3.5 bar, 0.14 MPa to 0.35 MPa)
Air consumption at 70 psi (0.48 MPa, 4.8 bar), 20 gpm (76 lpm)	25 scfm
Air consumption at 50 psi (0.35 MPa, 3.5 bar), full flow	25 scfm
Fluid displacement per cycle	0.17 gal (0.64 l)
Maximum values with water as media under submerged inlet conditions at ambient temperature:	
Maximum air consumption	64 scfm
Maximum free-flow delivery	
Transfer Pump	50 gpm (189 lpm)
Fuel Dispense Pump	38 gpm (144 lpm)
Maximum pump speed	
Transfer Pump	275 cpm
Fuel Dispense Pump	210 cpm
Maximum suction lift (varies widely based on ball/seat selection and wear, operating speed, material properties and other variables)	16 ft (4.9 m) dry, 29 ft (8.8 m) wet
Maximum-size pumpable solids	1/8 in (3.2 mm)
Recommended cycle rate for continuous use	93 cpm to 140 cpm
Recommended cycle rate for circulation systems	20 cpm
Sound Power*	
at 70 psi (0.48 MPa, 4.8 bar) and 50 cpm	78 dB(A)
at 100 psi (0.7 MPa, 7.0 bar) and full flow	90 dB(A)
Sound Pressure**	
at 70 psi (0.48 MPa, 4.8 bar) and 50 cpm	84 dB(A)
at 100 psi (0.7 MPa, 7.0 bar) and full flow	96 dB(A)
Operating temperature range	10°F to 150°F (-12°C to 65°C)
Air inlet size	1/2 in NPT(F)
Fluid inlet size	1 in NPT(F)
Fluid outlet size	1 in NPT(F)
Weight	23 lb (10.5 kg)
Wetted parts	Aluminum, TPC-ET, acetal, PTFE, Buna-N
Non-wetted external parts	Aluminum, coated carbon steel
Instruction manual	313597

<sup>\*</sup>Sound power measured per ISO-9614-2.

# >>> Ordering Information

# **Husky 1050 AODD Pumps**

Part Number	Description	Maximum Fluid Working Pressure	Fluids Handled
647016 Husky 1050 Aluminum Pump – 1 in, Aluminum/TPE		100 psi (6.9 bar)	Water / anti-freeze / fuel transfer
647731	Husky 1050 Aluminum Pump – 1 in, Aluminum/Buna-N	100 psi (6.9 bar)	Oil evacuation / oil transfer
647648 Husky 1050 Aluminum Pump – 1 in, Aluminum/TPE		50 psi (3.5 bar)	Fuel dispense

<sup>\*\*</sup>Sound pressure was tested 3.28 ft (1 m) from equipment.













### **Husky 307 AODD Pump**

- 3/8 in fluid connections
- Fluid delivery up to 7 gpm (26.5 lpm)
- Operate as low as 20 psi up to 100 psi for max flow
- Maximum working pressure of 100 psi for long line runs
- End porting available
- High-efficiency air valve operates at maximum of 6 scfm
- Groundable to reduce risk of static and electric shock


Technical Specifications		
Maximum fluid working pressure	100 psi (6.9 bar, 0.69 MPa)	
Maximum free-flow delivery*	7.0 gpm (26.5 lpm)	
Maximum pump speed	330 cpm	
Fluid displacement per cycle**	0.02 gal (0.076 l)	
Maximum suction lift	12 ft (3.7 m) dry	
Maximum-size pumpable solids	0.06 in (1.5 mm)	
Maximum ambient operating temperature***	180°F (82.2°C)	
Maximum diaphragm operating temperature***	150°F (65.6°C)	
Typical sound level at 50 psi (3.5 bar, 0.35 MPa) air @ 50 cpm	75 dB(A)	
Maximum air consumption	6 scfm (0.17 m³/min)	
Air pressure operating range	20 psi to 100 psi (1.4 bar to 6.9 bar, 0.14 MPa to 0.69 MPa)	
Air inlet size	1/4 NPT(F) or BSPT(F)	
Fluid inlet size	3/8 NPT(F)	
Fluid outlet size	3/8 NPT(F)	
Weight	5.2 lb (2.4 kg)	
Wetted parts	Acetal with stainless steel fibers, PTFE	
Instruction manual	308553	
*Flow rates are with muffler and do not vary based on diaphragm materi	al **Displacement per suele mouvenu becod en quetien	

<sup>\*</sup>Flow rates are with muffler and do not vary based on diaphragm material. \*\*Displacement per cycle may vary based on suction condition, discharge head, air pressure and fluid type. \*\*\*Actual pump performance may be affected by prolonged usage at temperature.

# >>> Ordering Information

### **Husky 307 AODD Pump**

	<u>-</u>
Part Number	Description
D31255	Husky 307 Acetal Pump – 3/8 in, Acetal/TPE















#### **Husky 515 AODD Pump**

- 1/2 in fluid connections
- Fluid delivery up to 15 gpm (56.7 lpm)
- Operate as low as 30 psi up to 100 psi for max flow
- Maximum working pressure of 100 psi for long line runs
- Center and end porting options available
- High-efficiency air valve operates at maximum of 28 scfm
- Groundable to reduce risk of static and electric shock


echnical Specifications		
Maximum fluid working pressure	100 psi (6.9 bar, 0.69 MPa)	
Maximum free-flow delivery*	15 gpm (57 l/min)	
Maximum pump speed	400 cpm	
Fluid displacement per cycle**	0.04 gal (0.15 l)	
Maximum suction lift	15 ft (4.5 m) dry, 25 ft (7.6 m) wet	
Maximum-size pumpable solids	3/32 in (2.5 mm)	
Maximum ambient operating temperature***	180°F (82.2°C)	
Maximum diaphragm operating temperature***	180°F (82.2°C)	
Typical sound level at 70 psi (4.8 bar, 0.48 MPa) air @ 50 cpm	77 dB(A)	
Maximum air consumption	28 scfm (0.672 m³/min)	
Air pressure operating range	30 psi to 100 psi (2.1 bar to 6.9 bar, 0.21 MPa to 0.69 MPa)	
Air inlet size	1/4 NPT(F)	
Fluid inlet size	3/4 in NPT(F)	
Fluid outlet size	1/2 and 3/4 in NPT(F)	
Weight	7.8 lb (3.5 kg)	
Wetted parts	Groundable acetal, Buna-N, PTFE	
Instruction manual	309204	
*F1	1.4401 1 1 1 1	

\*Flow rates are with muffler and do not vary based on diaphragm material. \*\*Displacement per cycle may vary based on suction condition, discharge head, air pressure and fluid type. \*\*\*Actual pump performance may be affected by prolonged usage at temperature.

# Ordering Information

# **Husky 515 AODD Pump**

Part Number	Description
243669	Husky 515 Acetal Split Inlet – 3/4 in, Acetal/Buna Dual Inlet


















- 3/4 in fluid connections
- Fluid delivery up to 16 gpm (60.6 lpm)
- Operate as low as 30 psi up to 100 psi for max flow
- Maximum working pressure of 100 psi for long line runs
- Center and end porting options available
- High-efficiency air valve operates at maximum of 28 scfm
- · Groundable to reduce risk of static and electric shock


chnical Specifications	
Maximum fluid working pressure	100 psi (6.9 bar, 0.69 MPa)
Maximum free-flow delivery*	16 gpm (61 l/min)
Maximum pump speed	400 cpm
Fluid displacement per cycle**	0.04 gal (0.15 l)
Maximum suction lift	15 ft (4.5 m) dry, 25 ft (7.6 m) wet
Maximum-size pumpable solids	3/32 in (2.5 mm)
Maximum ambient operating temperature***	180°F (82.2°C)
Maximum diaphragm operating temperature***	180°F (82.2°C)
Typical sound level at 70 psi (4.8 bar, 0.48 MPa) air @ 50 cpm	77 dB(A)
Maximum air consumption	28 scfm (0.672 m³/min)
Air pressure operating range	25 psi to 100 psi (1.8 bar to 6.9 bar, 0.18 MPa to 0.69 MPa)
Air inlet size	1/4 NPT(F)
Fluid inlet size	3/4 in NPT(F)
Fluid outlet size	3/4 in NPT(F)
Weight	8.5 lb (3.9 kg)
Wetted parts	Buna-N, acetal, aluminum, stainless steel, PTFE, zinc-plated steel
Instruction manual	308573
*Flow rates are with muffler and do not vary based on diaphragm materia	al. **Displacement per cycle may vary based on suction

condition, discharge head, air pressure and fluid type. \*\*\*Actual pump performance may be affected by prolonged usage at temperature.

# **Husky 716 AODD Pump**

Part Number	Description
241906	Husky 716 Aluminum – 3/4 in, Aluminum/Buna-N















#### **Husky 1590 AODD Pump**

- 1-1/2 in fluid connections
- Fluid delivery up to 90 gpm (340.7 lpm)
- Operate as low as 20 psi up to 120 psi for max flow
- Maximum working pressure of 120 psi for long line runs
- End porting available
- High-efficiency air valve operates at maximum of 125 scfm
- · Groundable to reduce risk of static and electric shock


echnical Specifications		
Maximum fluid working pressure	120 psi (8.4 bar, 0.84 MPa)	
Maximum free-flow delivery*	100 gpm (378.5 l/min)	
Maximum pump speed	200 cpm	
Fluid displacement per cycle**	0.5 gal (1.96 l)	
Maximum suction lift	20 ft (6.1 m) dry	
Maximum-size pumpable solids	0.19 in (4.8 mm)	
Maximum ambient operating temperature***	150°F (65.5°C)	
Maximum diaphragm operating temperature***	150°F (65.5°C)	
Typical sound level at 70 psi (4.8 bar, 0.48 MPa) air @ 125 cpm	77 dB(A)	
Maximum air consumption	125 scfm (3.5 m³/min)	
Air pressure operating range	20 psi to 100 psi (1.4 bar to 6.9 bar, 0.14 MPa to 0.69 MPa)	
Air inlet size	1/2 NPT(F)	
Fluid inlet size	1-1/2 NPT(F) or BSPT(F)	
Fluid outlet size	1-1/2 NPT(F) or BSPT(F)	
Weight	33.5 lb (15.2 kg)	
Wetted parts	Acetal, aluminum, TPE, PTFE	
Instruction manual	308441	

<sup>\*</sup>Flow rates are with muffler and do not vary based on diaphragm material. \*\*Displacement per cycle may vary based on suction condition, discharge head, air pressure and fluid type. \*\*\*Actual pump performance may be affected by prolonged usage at temperature.

# Ordering Information

#### **Husky 1590 AODD Pump**

Part Number	Description
DB3525	Husky 1590 Aluminum – 1.5 in, Aluminum/TPE















#### **Husky 2150 AODD Pump**

- 2 in fluid connections
- Fluid delivery up to 150 gpm (567.8 lpm)
- Operate as low as 20 psi up to 120 psi for max flow
- Maximum working pressure of 120 psi for long line runs
- End porting available
- High-efficiency air valve operates at maximum of 175 scfm
- · Groundable to reduce risk of static and electric shock


echnical Specifications		
Maximum fluid working pressure	120 psi (8.4 bar, 0.84 MPa)	
Maximum free-flow delivery*	150 gpm (568 l/min)	
Maximum pump speed	145 cpm	
Fluid displacement per cycle**	1.03 gal (3.9 l)	
Maximum suction lift	20 ft (6.1 m) dry	
Maximum-size pumpable solids	0.25 in (6.3 mm)	
Maximum ambient operating temperature***	150°F (65.5°C)	
Maximum diaphragm operating temperature***	150°F (65.5°C)	
Typical sound level at 70 psi (4.8 bar, 0.48 MPa) air @ 125 cpm	78 dB(A)	
Maximum air consumption	175 scfm (4.9 m³/min)	
Air pressure operating range	20 psi to 120 psi (1.4 bar to 8.4 bar, 0.14 MPa to 0.84 MPa)	
Air inlet size	1/2 NPT(F)	
Fluid inlet size	2 in NPT(F)	
Fluid outlet size	2 in NPT(F)	
Weight	58 lb (26.3 kg), 62 lb (28.1 kg) – Extended	
Wetted parts	Acetal, aluminum, TPE, PTFE	
Instruction manual	308368	
*Flow rates are with muffler and do not very based on disphragm materi	1 ##B': -1	

<sup>\*</sup>Flow rates are with muffler and do not vary based on diaphragm material. \*\*Displacement per cycle may vary based on suction condition, discharge head, air pressure and fluid type. \*\*\*Actual pump performance may be affected by prolonged usage at temperature.

# Ordering Information

#### **Husky 2150 AODD Pump**

Part Number	Description
DF3525	Husky 2150 Aluminum – 2 in, Aluminum/TPE















#### **Husky 3300 AODD Pump**

- 3 in fluid connection
- Fluid delivery up to 300 gpm (1,135.6 lpm)
- Operate as low as 20 psi up to 125 psi for max flow
- Maximum working pressure of 125 psi for long line runs
- Rotatable center porting available
- High-efficiency air valve operates at maximum of 335 scfm
- · Groundable to reduce risk of static and electric shock

Fechnical Specifications				
Maximum fluid working pressure	125 psi (8.4 bar, 0.84 MPa)			
Maximum free-flow delivery*	300 gpm (1,135 l/min)			
Maximum pump speed	103 cpm			
Fluid displacement per cycle**	2.9 gal (11 l)			
Maximum suction lift	8 ft (2.4 m) dry, 28 ft (8.5 m) wet			
Maximum-size pumpable solids	0.5 in (13 mm)			
Maximum ambient operating temperature***	150°F (65.5°C)			
Maximum diaphragm operating temperature***	150°F (65.5°C)			
Typical sound level at 50 psi (3.4 bar, 0.34 MPa) air @ 50 cpm	92 dB(A)			
Maximum air consumption	335 scfm (9.5 m³/min)			
Air pressure operating range	20 psi to 125 psi (1.4 bar to 8.6 bar, 0.14 MPa to 0.86 MPa)			
Air inlet size	3/4 NPT(F)			
Fluid inlet size	3 in (76.2 mm) NPT or BSPT with ANSI/DIN flange			
Fluid outlet size	3 in NPT(F) or BSPT(F)			
Weight	150 lb (68 kg)			
Wetted parts	Acetal, aluminum, carbon-coated steel, TPE			
Instruction manual	3A0410			

<sup>\*</sup>Maximum values with water as media at ambient temperature. Water level is approximately 3 ft above pump inlet.


# Ordering Information

### **Husky 3300 AODD Pump**


Part Number	Description
652002	Husky 3300 Aluminum – 3 in, Aluminum/TPE

#### **Pump Performance**

#### Husky 3300 Performance



(Pump tested in water with inlet submerged)



<sup>\*\*</sup>Startup pressures and displacement per cycle may vary based on suction condition, discharge head, air pressure and fluid type.

\*\*\*Sound power measured per ISO-9614-2. Sound pressure was tested 3.28 ft (1 m) from equipment.





# **Pre-Mixed Windshield Wash Solvent and Coolant Dispense**



	Package Number	237161
	Pump Type	Husky 307
	Pump	D31255
	Installation Kit	237160
	Air Filter	110146
sapr	Air Gauge	108190
Indu	Air Regulator	110318
n Kit	Fluid Connect Hose – 4 ft	220596
Installation Kit Includes	Air Connect Hose – 6 ft	109125
Inst	Mounting Bracket	190125
	Suction Kit	223888
	Wall Bracket Kit	224835
	Instruction Manual	308426
		·







# **Bulk Anti-Freeze and Windshield Solvent Transfer Packages**









Package Number 244679		244680	244681	244682
Pump Type Husky 1050 – Dual Inle		Husky 1050 – Single Inlet	Husky 515 – Dual Inlet	Husky 716 – Single Inlet
Pump	647016	647016	243669	241906
Air Regulator	244844	244844	110147	110147
Fluid Connect Hose	115042	115042	109105	109105
Air Connect Hose	205418	205418	109125	109125
Air Shut-Off Valve	110225	110225 110223		110223
Wall Mount Bracket	24C637	24C637	24C637 224835	
Dual Inlet Manifold	24D147	-	_	-
Suction Kit	(2) 236054	236054	(2) 236054	236054
Thermal Relief Kit	238428	238428	238428	238428
Instruction Manual	309353	309353	309353	309353

#### **Air Line Filters**

2	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	110146	110146	106148	106149	106150	106150

# **Air Regulator and Gauge**

<b>6</b>	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	110147	110147	246946	202858	206199	207651

# **Air Quick-Connect Coupler**

	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	208536	208536	110199	110199	110199	110200

# **Air Quick-Connect Nipple**

Allien	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	169970	169970	110196	110196	110196	110197

# **Bleed-Type Air Valve**

0 0	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	110223	110223	110224	110225	110225	110226

#### **Dual-Inlet Manifold**

	Husky Pump	307	515	1050	1590	2150	3300
ALC: NO.	Part Number	237211	194347	24D205	-	-	-

# **Grounding Wire and Clamp**


Husky Pump	307	515/716	1050	1590	2150	3300
Part Number	222011	222011	238909	222011	238909	238909

# **Suction Hose Kit**


D	Husky Pump	307	515/716	1050	1590	2150	3300
	Part Number	236054	236054	236054	222916	222916	-

# **Diaphragm Pump Accessories**

#### **Thermal Relief Kit**



# Thermal Relief Valves - 150 psi (10.3 bar)



# **Wall Bracket**

Husky Pump	307	515/716	1050	1590	2150	3300
Part Number	224835	224835	24C637	-	-	-

# Air-Operated Double-Diaphragm Transfer Pumps Replacement Parts

			N						
Pump Number	D31255	243669	241906	647016	647731	647648	DB3525	DF3525	652002
Air Valve Replacement Kit	239952	241657	241657	24B768	24B768	24B768	236273	236273	24K860
Seats	D03200	D05200	D05200	24B634	24B632	24B634	D0B500	D0F500	24K932
Balls	D03050	D05070	D05070	24B639	24B639	24B639	D0B020	D0F020	24K937
Diaphragm Kit	D03005	D05007	D05007	24B624	24B624	24B624	D0B005	D0F005	24K901
Fluid Repair Kit (Ball, Seats, Diaphragm)	D03255	D05277	D05277	25A857	_	25A857	D0B525	D0F525	25A874





# Ideal for Undercoating and Rustproofing Application in Medium-Sized Shops

Utilizing the durable Fire-Ball® 300 pump, these kits are designed for use in medium-volume undercoating and rustproofing dispense applications. A three-inch differential air motor ensures smooth pumping, and the double-acting pump design provides reliable material flow and accurate dispense.



Thick cast aluminum air motor housing offers unmatched durability.

#### Superior Material Handling

Double-acting pump ensures smooth fluid flow.

#### Extended Seal Life

In-line pump design aligns the air motor piston and fluid piston rods to maximize seal life.

#### Wetted-Parts Options

Available in carbon steel for petroleum-based or SST for water-based materials.

#### Corrosion-Resistant

Corrosion-resistant design utilizes liquid nitriding, nickel plating, stainless steel, aluminum and chrome on key components for longer life.

#### **Typical Applications**

- Undercoating, rustproofing and sound-deadening materials
- Automotive and heavy-duty vehicle dealerships
- Fast lube centers and service shops
- · Fleet service facilities

#### Typical Fluids Handled


 Undercoating and rustproofing (Verify chemical compatibility for pump's wetted components with undercoating material supplier or contact Graco directly at 1-800-533-9655)

# **Undercoating and Rustproofing Pumps**



# Pump Performance

# Fire-Ball 300 15:1 Pumps



Fluid Pressure Ratio	15:1
Air Motor Effective Diameter	3 in (76.2 mm)
Annual Usage	Up to 10,000 lb (4,535 kg)
Maximum Fluid Working Pressure	2,700 psi (186 bar / 18.6 MPa)
Approximate Free-Flow Rate @ 100 psi	7.5 lb/min (3.4 kg/min)
Output per Cycle	1.29 oz (36.6 g)
Continuous-Duty Flow Rate	0.7 lb/min (0.32 kg/min)
Approximate Air Use and Flow @ 100 psi (80 cpm)	14 @ 6.5 lb/min (0.40 @ 2.9 kg/min
Air Inlet	3/8 in NPT(F)
Fluid Outlet	1/4 in NPT(F)
Air Operation Range	40 psi to 180 psi (2.8 bar to 12.5 bar
Max Recommended Pump Speed	66 cpm
Cycles per Pound	12.4 cpp
Cycles per Kg	27 cpk
Wetted Parts	CS, AL, leather, PTFE, rubber
Sound Pressure Level	77.8 dB(A)
Sound Power Level	85.6 dB(A)
Approximate Weight	22 lb (10 kg)
Instruction Manual	306531

25 ft (7.6 m)

200326

307879



# Ordering Information

Ratio

Tip

Hose Length

Drum Cover

Portable Base Instruction Manual

# **Undercoating Packages**



15 ft (4.6 m)

204574

204144

307879

15 ft (4.6 m)

222058

307879

<sup>\*</sup>Dispense kit includes Air Regulator (110234), Air Gauge (100960), Spray Gun (234237)

# **Undercoating and Rustproofing Pump Packages**



>>> Ordering Information

# **Spray Masking Package**



Package Number	224826
Type of Package	Bung Mounted Stationary
Ratio	15:1
Container Size	400 lb (180 kg)
Pump Part Number	224825 (SST pump)
Flexible Downtube	224022*
Dispense Kit**	224023
Tip	286211/286621
Hose Length	25 ft (7.6 m)
Instruction Manual	308069

\*224022 is long enough for 400 lb (180 kg) container, but can be trimmed to accommodate smaller containers. \*\*Dispense kit includes Flex Plus™ spray gun (235457).



# **Application Gun**

202	
<b>4</b>	
4	

Part Number	Description
234237	Four-finger silver gun with tip guard 243161 and tip 286517. 4,500 psi (310 bar) x 3/8 NPT(f) inlet. Must order 155570 adapter and 239663 straight swivel to accommodate gun to 1/4 in (mbe) hose.

### **Bung Adapter**



Part Number	Description
239966	Bung adapter compatible with Fire-Ball 300, 15:1 pump

# **Filter**



Part Number	Description
214570	60-mesh aluminum filter, 3/8 NPT(F) inlet, 1/4 NPT(F) outlet. Maximum working pressure 3,000 psi (210 bar).

# **Nozzle Extension**



	Part Number	Description
*	206496	Nozzle extension delivers 360° coating fan into blind areas. Length 30-3/4 in (99 cm) x 7/8-14(f) end. Tip 206502, size .043.

# **Replacement Screen Elements (SST)**

	Part Number					
	30 Mesh	60 Mesh	100 Mesh			
3-Pack	224458	224459	224469			
25-Pack	238436	238438	238440			

#### **Swivel**



Part Number	Description		
202577	Z-swivel allows non-binding movement for hard-to-reach locations.  Order 155570 adapter separately to accommodate 234237 gun.		











# **Reliable Operation in the Harshest Environments**

With its efficient, large-ported air valve, the Bulldog 43:1 air-powered pump is the highest-performing in its class. Downtime is minimized by an air motor design that has been developed and tested for more than 10 million cycles of operation.



Grounded lug prevents static buildup.

### Easy Installation

Compact, low-profile design makes installation easier.

#### Corrosion-Resistant

Lightweight aluminum construction.

### **Built-In Reliability**

Tested to 10 million cycles without failure.

#### **Typical Applications**


· Supplies hydraulic oil to accumulators in oil rig blowout prevention systems.

#### Typical Fluids Handled

Hydraulic oil

#### **Pump Performance**

#### **Bulldog 43:1 Pumps**











Technical Specifications					
Fluid Pressure Ratio	43:1				
Maximum Fluid Working Pressure	4,300 psi (301 bar / 30.1 MPa)				
Maximum Air Input Pressure	100 psi (7 bar)				
Air Inlet	3/4 in NPSM(F)				
Fluid Inlet	1 in NPT(F)				
Fluid Outlet	3/4 in NPT(F)				
Wetted Parts	Carbon steel, stainless steel, chrome plating, zinc plating, nickel plating, brass, Buna-N				
Instruction Manual	309966				

# **Bulldog 43:1 Pumps**

Part Number	Description
218334	43:1 Bulldog hydraulic supply pump

# **Accessories**

# **Air Pressure Regulators**

Part Number	Description		
206197	1/2 in NPT inlet and outlet		
207755	3/4 in NPT inlet and outlet		

### **Air Line Filters**

Part Number	Description	
106149	1/2 in NPT inlet and outlet	
106150	3/4 in NPT inlet and outlet	

#### **Air Line Lubricators**

Part Number		Description
	214848	1/2 in NPT inlet and outlet
	214849	3/4 in NPT inlet and outlet

# **Grounding Clamp and Wire**

Part Number	Description	
103538	Grounding clamp	
222011	Ground wire	

# **Bleed-Type Master Air Valve**

Part Number	Description
107142	1/2 in NPT inlet and outlet

# **Repair Kits**

	Part Number	Description		
24U227 Pump lower repair kit		Pump lower repair kit		
24U228 Air motor repair kit		Air motor repair kit		
Ì	24W515	Pump and air motor repair kit		













# **Used for Low-Volume Dispense** of a Variety of Fluids

This air-operated piston pump is ideal for pumping various fluids and provides a continuous-duty flow rate of up to 5 gpm.

#### High-Quality Air Motor

Differential air motor ensures smooth pumping.

#### Lightweight Design

Allows for easy transport and drum insertion.

### Easily Controlled Flow Rate

Simple regulation of air supply controls flow rate.

#### Submersible Suction Tube

Stubby and drum length suction tubes eliminate the need for suction pipe or tube.

#### Corrosion Resistance

Available stainless steel models offer protection in harsh environments.

#### **Typical Applications**

- Low-pressure, high-volume transfer of low viscosity fluids
- · Automotive dealerships
- Heavy-duty dealerships
- · Fast lube centers
- · Fleet service facilities
- · Service shops
- In-plant
- Lube trucks
- Mining


#### Typical Fluids Handled

- Water
- Anti-freeze
- · Windshield wash fluid
- Used oil
- · Used anti-freeze

NOTE: Use Fast-Ball® 1:1 for petroleum-based products.

#### **Pump Performance**

#### **Fast-Flo 1:1 Pumps**











hnical Specifications					
Fluid Pressure Ratio	1:1				
Air Motor Effective Diameter	1.4 in (35.6 mm)				
Maximum Fluid Working Pressure	180 psi (12 bar/1.2 Mpa)				
Approximate Free-Flow Rate @ 100 psi (80 cpm)	5 gal/min (19 liters/min)				
Output per Cycle	151 cc				
Approximate Air Use and Flow @ 100 psi (80 cpm)	7 csfm @ 3.1 gpm (0.2 m³/mm @ 11.71 lpm)				
Air inlet	1/4 in NPT(F)				
Fluid Inlet	1-1/2 in NPT(F)				
Fluid Outlet	3/4 in NPT(F)				
Air Operations Range	40 psi to 180 psi (2.8 bar to 12 bar)				
Maximum Pump Speed	100 cpm				
Cycles per Gallon	25 cpg				
Cycles per Liter	6.6 cpl				
Wetted Parts	See ordering info				
Sound Pressure Level	72 dB(A)				
Sound Power Level	82 dB(A)				
Instruction Manual	307427				

### Fast-Flo 1:1 Pumps

Includes motor and pump lower assembly.

Fluid	Length	Tube Material	Seal Material	Approvals	Part Number
Anti-Freeze, Windshield	Drum	Stainless Steel	Polyethylene	ETL, CE, EX	226942
Washer Solvent, ATF, Oil	Universal	Stainless Steel	Polyethylene	ETL, CE, EX	226945
			Buna-N	CE	226947
			Buna-N	CE	226951*
		Carbon Steel	Leather	CE, EX	237133
	Drum	Carbon Steer	PTFE	CE, EX	237134
	Druill		Leather	ETL, CE, EX	226940
			Polyethylene	ETL, CE, EX	226941
		Stainless Steel	Buna-N	CE	226953
Oil			PTFE	CE, EX	237129
	Universal	Carbon Steel	Buna-N	CE	226948
			Leather	CE, EX	237130
			PTFE	CE, EX	237131
			Leather	ETL, CE, EX	226943
			Polyethylene	ETL, CE, EX	226944
		Stainless Steel	Buna-N	CE	226952
			PTFE	CE, EX	237132

<sup>\*</sup>Adjustable downtube length between 18 in (457 mm) and 46.4 in (1,180 mm)

# **Fast-Flo 1:1 Pump Accessories**

# >>> Ordering Information

# **Hose and Fitting Kits**

	Part Number	Description	Includes	
	rait Number	Description	Air Hose / Swivel Elbow	Fluid Hose / Swivel Elbow
133	222118	18 in (0.5 m) for connecting wall-mounted Fast-Flo 1:1 pumps to piping	109123 / 155541	109108 / 160327
	222119	6 ft (1.8 m) for use with drum-mounted Fast-Flo 1:1 pumps	109125 / 155541	109105 / 160327

# **Bung Adapters**

Part Number	Description
214583	Allows direct mounting of full-length Fast-Flo 1:1 pumps into standard 2 in NPT drum bung (included).
217359	Sealed bung adapter for Fast-Flo pumps; can be used with suction kit 236054.

### **Installation Kits**

	Part Number	Description
170	218316	Includes regulator (104815), gauge (104655) and fittings (169969/114558) as necessary for normal installation.
	210881	Wall mounting bracket for Fast-Flow 1:1 Pumps

# **Suction Kit**

g-	Part Number	Description	Includes		
<b>₽</b>	Fait Number		Bung Adapter	Bushing Pipe	6 ft Hose
	236054	6 ft (1.8 m) suction kit for 55 gal (200 l) drums. For use with Fast-Ball, Mini Fire-Ball and Fire-Ball universal pumps.	188845	101496	109105

# **Drum Covers**

	Part Number	Description
	204574	Drum cover for 10 gal (40 l) and 16 gal (60 l) sized containers. Drum cover mounts on top of an open drum with mounting house for a 1:1 pump. Includes thumb screws and a rubber gasket.
•	200326	Drum cover for a 55 gal (200 l) container. Drum cover mounts on top of an open drum, with mounting for a 1:1 pump.

# **Air Line Filter**

(min)	Part Number	Description
Ţ	106149	1/2 in NPT inlet and outlet

# **Air Line Lubricator**

*	Part Number	Description
	214848	1/2 in NPT inlet and outlet













# **Electric Gear Pumps for High-Volume Transfer**

At Graco, we provide durable pumping solutions for all your oil and fluid transfer applications. Our line of APEX pumps is available in AC and DC configurations to meet your fluid transfer needs.



# **APEX Transfer Pumps**

- Available with 12 VDC, 115 VAC and 230 VAC electric motors
- TENV electric motor to handle the dirtiest environments models 260105, 260106, 260108 and 260109
- Self-priming, positive displacement design
- Pumps petroleum- and synthetic-based lubricants up to 8 gpm (30 lpm)
- Built-in bypass valve
- · Transfer used oil with inlet suction screen
- System includes suction tube, fluid hose, dispense valve and bung adapter for models 260100, 260101, 260102 and 260104



# **APEX On-Demand Pumps**

- Available in 12 VDC and 115 VAC
- On-demand pressure-sensing system starts and stops the pump
- · TENV electric motor to handle the dirtiest environments
- · Extremely guiet pump operation
- · Output flow is continuous and non-pulsating
- · Low operating and installation costs
- Inlet and outlet check valves with thermal relief valves included
- · All units include bung adapter

#### **Typical Applications**

- · Filling bulk tanks from drums
- · Lubricant transfer from remote locations
- · Construction equipment
- · Agricultural equipment
- · Filling in-plant machinery
- · Evacuating used oil receivers
- Filling shop oil furnaces with new or used oil
- Automotive and truck service garages
- Fleet marine and personal boat service
- Aircraft maintenance

#### Typical Fluids Handled

- Synthetic oil
- Petroleum oil\*
- Used oil\*
- · Anti-freeze
- · Hydraulic fluids
- · Cutting oils
- Liquid soap
- Non-flammable oil-based solvents
- · Oil-based herbicide carriers

\*Not for food grade use.



















PART NUMBERS L	.EGEND
(A) = 260105, 260106	Relief valve
B = 260108	setting at 150 psi
© = 260109	(10.3 bar, 1.0 MPa)

# **APEX Pumps**

Part Number	260100	260101	260102	260104	260105	260106	260108	260109
Motor	12 VDC	115 VAC	115 VAC	230 VAC	115 VAC	115 VAC	115 VAC	115 VAC
Hertz	-	60 Hz	60 Hz	50/60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Horsepower	3/4	1	3/4	1/2	3/4	3/4	3/4	1
Maximum Current (Amps)	35	9.2	9.2	4	7.5	7.5	9	11
Maximum Flow Rate gpm (lpm)	5.8 (22)	4.25 (16)	8.0 (30)	4.25 (16)	3.0 (11)	3.0 (11)	4.2 (16)	7.9 (30)
Maximum Pressure psi (bar)	65 (4.5)	65 (4.5)	65 (4.5)	65 (4.5)		150	(10)	
Automatic Relief Setting psi (bar)	65 (4.5)	65 (4.5)	30 (2.1)	65 (4.5)		-	_	
Inlet				1 in	NPT			
Outlet		3/4 in NPT						
Wetted Parts		Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber, PVC, PVC cement		Carbon steel with zinc plating, stainless steel, galvanized steel aluminum, nitrile, rubber			anized steel,	
Weight Ib (kg)	34 (15)	25 (11)	25 (11)	25 (11)	25 (11)	25 (11)	25 (11)	30 (14)
Manual		311305				311	306	














# **APEX On-Demand Pumps**

Part Number	260110	260111	260113	260114	260112
Voltage	115 VAC	115 VAC	115 VAC	115 VAC	12 VDC
Hertz	Hertz 60 Hz		60 Hz	60 Hz	-
Horsepower	3/4	1	1-1/2	2	3/4
Bung Adapter	260061	260061	260061	260061	260061
Maximum Current (Amps)	10.6	13.6	18.0	21.0	62.0
Maximum Flow Rate gpm (lpm)	2.3 (9)	3 (11)	4 (15)	4 (15)	3 (11)
Maximum Pressure psi (bar)	370 (25)	550 (38)	470 (32)	650 (45)	400 (28)
Inlet	3/4 in NPT	3/4 in NPT	3/4 in NPT	3/4 in NPT	3/4 in NPT
Outlet	1/2 in NPT	1/2 in NPT	1/2 in NPT	1/2 in NPT	1/2 in NPT
Wetted Parts	Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber, PVC, PVC cement				eel,
Weight lb (kg)	27 (12)	32 (15)	41 (19)	52 (24)	27 (12)
Manual	311307				











### **Accessories**

Part Number	Description
260145	Wall mounting bracket, fits all models
260238	"Y" strainer with 3/4 in NPT female in-line strainer for used oil transfer
260306	Inlet suction screen assembly, required for used oil applications, 20 mesh screen
260124	55 in (1.3 m) PVC suction tube with inlet check valve
260125	Dispense valve kit
260300	Suction tube kit, 3/4 in PVC







# Graco piston hand pumps are designed for long life and smooth operation

#### **Features and Benefits**

- Lightweight die cast aluminum construction
- Corrosion-resistant design
- · High-quality piston seals are designed for long life and smooth operation
- Integrated nozzle holster helps prevent fluid contamination
- Adjustable bung adapter allows pump to be rotated
- One quart per stroke gives fast, efficient fluid transfer
- · Locking mechanism prevents unauthorized dispensing

Technical Specifications					
		260406	260407		
	Inlet	1 in NPT(F)	1 in NPT(F)		
	Outlet	3/4 in NPT(F)	3/4 in NPT(F)		
	Hose	3/4 in x 8 ft, EPDM	3/4 in x 8 ft, petroleum (buna)		
	Standpipe	34 in / 2 piece	34 in / 2 piece		
	Shaft and Piston Liner	SST	SST		
	Seals	Viton	Buna-N		
	Weight	12 lb (5 kg)	12 lb (5 kg)		
	Instruction Manual	311308	311308		

#### **Typical Applications**

- Construction equipment
- · Agricultural equipment

#### Typical Fluids Handled

- · Petroleum products and other fluids compatible with aluminum and buna-N seals.
- · Herbicides and other chemicals or fluids compatible with fluoroelastomer seals, aluminum, and EPDM.

# Ordering Information

Part Number	Description
260406	Chemical Piston Hand Pump
260407	Petroleum Piston Hand Pump



# **Graco Hose and Cord Reel Selection Guide**

	Typical Application	Typical Fluid	Hose/Cord Length Options	Enclosed	Reference Pages
• Small maintenance shops • Tire maintenance shops • Small fast lubes • Independent repair facilities • Industrial manufacturing facilities		Petroleum- and synthetic-based oils Air Water Grease Anti-freeze Windshield washer fluid	• 35 ft (11 m) • 45 ft (14 m) • 50 ft (15 m)	Yes	214-216
SD™ 10 / 20 Series	Car dealerships Light-/medium-duty truck dealers Fleet maintenance Public works garages Construction vehicle maintenance Light-utility service trucks	Petroleum- and synthetic-based oils Air Water Grease Anti-freeze Windshield washer fluid	• 35 ft (11 m) • 50 ft (15 m) • 65 ft (20 m)	Optional	217-224
SD™ Series Cord Reels	Automotive dealerships     Fast lube centers     Service shops     Heavy-duty dealerships     Fleet services facilities     In-plant     Lube trucks     Mining	-	• 35 ft (11 m) • 50 ft (15 m) • 95 ft (29 m)	Optional	224-227
XD™ 10 / 20 Series	Heavy-duty truck dealers     Fleet maintenance     Mining maintenance     Public works garage     Construction vehicle maintenance     Heavy-duty mobile service trucks     Mining     Lube trucks	Petroleum- and synthetic-based oils Air Water Grease Anti-freeze Windshield washer fluid	• 35 ft (11 m) • 50 ft (15 m) • 65 ft (20 m)	Optional	228-233
XD™ 30 Series	Heavy-duty truck dealers     Fleet maintenance     Mining maintenance     Public works garage     Construction vehicle maintenance     Heavy-duty mobile service trucks     Mining     Lube trucks	Petroleum- and synthetic-based oils Diesel fuel Air Water Grease Anti-freeze Windshield washer fluid Pressure wash Waste oil evacuation Diesel exhaust fluid (DEF)	• 35 ft (11 m) • 50 ft (15 m) • 65 ft (20 m) • 75 ft (23 m)	No	234-238
XD™ 40 / 50 Series	Heavy-duty truck dealers     Fleet maintenance     Mining maintenance     Public works garages     Construction vehicle maintenance     Heavy-duty mobile service trucks     Agriculture     Lube trucks	Petroleum- and synthetic-based oils Diesel fuel Air Water Anti-freeze Waste oil evacuation	• 35 ft (11 m) • 50 ft (15 m) • 75 ft (23 m) • 100 ft (30 m)	No	239-244
XD™ 60 / 70 / 80 Series	Heavy-duty truck dealers     Fleet maintenance     Mining maintenance     Public works garages     Construction vehicle maintenance     Heavy-duty mobile service trucks     Agriculture     Lube trucks	<ul> <li>Petroleum- and synthetic-based oils</li> <li>Diesel fuel</li> <li>Air</li> <li>Water</li> <li>Grease</li> <li>Waste oil evacuation</li> </ul>	• 50 ft (15 m) • 75 ft (23 m) • 100 ft (30 m) • 150 ft (46 m)	No	246-257



# **LD Series Enclosed Hose Reels**

















**Economical Enclosed Hose** Reels Get You Up and Running Fast

Reduce clutter and increase workplace safety with a Graco one-piece enclosed hose reel. Designed for light-duty applications in dealerships, service garages, collision repair and industrial manufacturing facilities.

# Large Fluid Porting

Maximizes fluid flow with minimal pressure drop

### Simple Spring Tension Adjustment

Ability to increase or decrease spring tension while reel is pressurized

# **Multiple Mounting Options**

Wall, ceiling bench, or tank configurations (wall mount pictured)

#### Full Enclosure

Tough, dent-proof, corrosion-resistant enclosure

#### **Typical Applications**


- Small maintenance shops
- Tire maintenance shops
- Small fast lubes
- · Independent repair facilities
- · Industrial manufacturing facilities

#### **Dimensions** Α 7.1 in (180 mm) В 23.0 in (585 mm) С 18.5 in (470 mm)

25.6 in (650 mm)

D





#### Typical Fluids Handled

- · Petroleum- and synthetic-based oils (motor, gear and ATF)
- Air
- Water
- Grease
- Anti-freeze
- · Windshield washer fluid

Technical Specifications							
Operating Temperature Range							
Air-Only Reels	14°F to 140°F (-10°C to 60°C)						
Water Applications	32°F to 140°F (0°C to 60°C)						
All-Other Applications	0°F to 140°F (-18°C to 60°C)						
Wetted Parts							
Air Only Reels	Aluminum, Buna-N rubber, PVC						
Air/Water/Anti-Freeze/Windshield Washer Fluid Reels	Aluminum, Buna-N rubber						
Oil Reels	Carbon steel, Buna-N rubber, PTFE						
Grease Reels	Carbon steel, Buna-N rubber						
Sound Pressure Level	69.3 dB(A)						
Sound Power Level	75.3 dB(A)						
Instruction Manual	313938						

















# **LD Series Reel Packages**

Includes hose with ball stop kit and hose guide, mounting bracket and hose inlet kit.

Type of	Fluid	Hose		Connection Size		Maximum	Package	Package Includes		
Mount		ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Reel Assembly	Mount Kit	Inlet Kit
		3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	250 (17.2)	24F737	24H657	24G866	
	Air/Water/ Anti-Freeze/	3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	250 (17.2)	24F738	24H658		
	Windshield Washer Fluid	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	250 (17.2)	24F739	24H659		24C44
G /4	Washioi Flaid	1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	250 (17.2)	24F740	24H660		
	Oil	3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	1,800 (124)	24F741	24H661		24053
	Oil	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	1,800 (124)	24F742	24H662		24053
Ceiling/Wall Swivel Mount	Grease	1/4 (6)	35 (11)	3/8 (10)	1/4 (6)	5,000 (345)	24F743	24H663		24053
	Air/Water/ Anti-Freeze/ Windshield Washer Fluid	3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	250 (17.2)	24F755	24H657	24G865	24C444
		3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	250 (17.2)	24F756	24H658		
		1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	250 (17.2)	24F757	24H659		
		1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	250 (17.2)	24F758	24H660		
	Oil	3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	1,800 (124)	24F759	24H661		24053
On Him or AMa II		1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	1,800 (124)	24F760	24H662		24050
Ceiling/Wall Stationary Mount	Grease	1/4 (6)	35 (11)	3/8 (10)	1/4 (6)	5,000 (345)	24F761	24H663		24053
		3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	250 (17.2)	24F773	24H657	24C772	24C444
	Air/Water/ Anti-Freeze/ Windshield Washer Fluid	3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	250 (17.2)	24F774	24H658		
		1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	250 (17.2)	24F775	24H659		
		1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	250 (17.2)	24F776	24H660		
C		3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	1,800 (124)	24F777	24H661		24053
	Oil	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	1,800 (124)	24F778	24H662		24053
Bench Swivel Mount	Grease	1/4 (6)	35 (11)	3/8 (10)	1/4 (6)	5,000 (345)	24F779	24H663		24053

# **LD Series Enclosed Hose Reels**

















Ordering Information

#### **LD Series Reel**

Includes hose. Mounting hardware and hose inlet kit sold separately.



Fluid	Hose		Connect	tion Size	Maximum Pressure	Part Number	Hose Inlet Kit	
Fluiu	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	psi (bar)	Fait Nullibei	(order separately)	
	3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	250 (17.2)	24H657	24C444	
Air/Water/ Anti-Freeze/	3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	250 (17.2)	24H658	24C444	
Windshield Washer Fluid	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	250 (17.2)	24H659	24C444	
washer ridid	1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	250 (17.2)	24H660	24C444	
Oil	3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	1,800 (124)	24H661	24C537	
Oii	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	1,800 (124)	24H662	24C538	
Grease	1/4 (6)	35 (11)	3/8 (10)	1/4 (6)	5,000 (345)	24H663	24C539	

#### **Hose Inlet Kits**

A hose inlet kit is included in LD reel packages but must be ordered separately with standalone LD reel assemblies.



	Fluid Type	Maximum Working Pressure psi (bar)	Size In (mm)	Inlet Configuration	Outlet Configuration	Part Number	Used with Hose Reel Model
•	Air Only		1/4 (6)	1/4 NPT(M)	1/4 NPT(M)	24C443	24H655 / 24H656
	Air/Water	250 (17.2)	3/8 (10)	1/2 NPT(M)	3/8 NPT(M)	24C444	24H657 / 24H658
	All/Walei		1/2 (13)	1/2 NPT(M)	1/2 NPT(M)	240444	24H659 / 24H660
	Oil	1,800 (124)	3/8 (10)	1/2 NPT(M)	1/2 NPT(M)	24C537	24H661
	UII		1/2 (13)	1/2 NPT(M)	1/2 NPT(M)	24C538	24H662
	Grease	5,000 (345)	1/4 (6)	1/4 NPT(M)	1/4 NPT(M)	24C539	24H663

















#### **Engineered for Everyday Use**

The SD line of hose reels feature Graco durability, performance and value built into every reel. With its durable metal spool and rigid pedestal frame, the compact SD Series is ideal for indoor and moderate outdoor exposure.



Maximize material flow with minimal pressure drop for faster fills to get more vehicles through your shop.

#### Adjustable Arm

Easily change to one of six arm positions to fit your application.

#### Large Hose Capacity with Small Profile

Compact pedestal and spool fits into tight spaces and can accommodate 35-65 foot (10.7-19.8 meters) hose (NPT air/water) capacity for a wide variety of applications.

#### **Durable Finish**

Baked-on enamel finish (five colors available) protects reel from corrosion.



Reel arm shown in tank/bench mount position.


#### **Typical Applications**

- Car dealerships
- Light-/medium-duty truck dealers
- Fleet maintenance
- Public works garages
- Construction vehicle maintenance
- Light-utility service trucks

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Air
- Water
- Grease
- Anti-freeze
- · Windshield washer fluid

Dime	Dimensions									
	SD 10	SD 20								
Α	7.0 in (177 mm)	7.0 in (177 mm)								
В	16.2 in (412 mm)	18.1 in (460 mm)								
С	21.0 in (533 mm)	23.4 in (594 mm)								
D	17.1 in (435 mm)	19.2 in (488 mm)								
Е	19.5 in (495 mm)	21.8 in (554 mm)								
F	22.5 in (571 mm)	25.2 in (640 mm)								



Technical Specifications				
Operating Temperature Range				
Air/Water/Anti-Freeze/Windshield Washer Fluid Reels	-20°F to 190°F (-28°C to 87°C)			
Oil Reels	-20°F to 190°F (-28°C to 87°C)			
Grease Reels	-40°F to 200°F (-40°C to 93°C)			
Wetted Parts				
Grease Reels	Zinc plated steel, polyurethane, steel			
All Other Reels	Zinc plated steel, anodized aluminum, nitrile rubber			
Weight	52 lb (23.5 kg)			
Sound Pressure Level	80 dB(A)			
Sound Power Level	88 dB(A)			
Instruction Manual	313431			















#### **Typical Mounting Configurations**



















#### SD 10/20 Reel Assembly Ordering Guide

SD Series reels are available in five colors. Use the chart below to determine the correct part number to order. The last character of each part number indicates the hose reel color.

Reel Color	Identifier
White	А
Metallic Blue	В
Red	С
Black	D
Yellow	F

**Order Example:** 

Arm in overhead mount position, SD 20, oil, 1/2 in ID hose, 50 ft hose length

1

**Select your reel position:** 

**HPM65**#



Select your reel color:

Metallic Blue = "B"

(from Reel Assembly Ordering Guide – opposite)

**Order Part Number:** 

HPM65B



#### **Arm in Overhead Mount Position**

Assembled with hose, ball stop kit and roller guide. Required hose inlet kit sold separately.

	Reel		Но	se	Connection Size		Maximum	Assembly	Recommended
	Size	Fluid	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Hose Inlet Kit
			3/8 (10)	35 (11)	1/2 (13)	3/8 (10)	300 (20.7)	HPL23#	
	SD 10	Air/Water/ Anti-Freeze/ Windshield Washer Fluid	3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	300 (20.7)	HPL25#	218549
			1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	300 (20.7)	HPL33#	
	CD 00		3/8 (10)	65 (20)	1/2 (13)	3/8 (10)	300 (20.7)	HPL56#	
	SD 20		1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	300 (20.7)	HPL65#	
	SD 10	0.1	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	2,000 (138)	HPM33#	
	SD 20	Oil	1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	2,000 (138)	HPM65#	
•	CD 10		1/4 (6)	50 (15)	3/8 (10)	1/4 (6)	5,000 (345)	HPH15#	218550
	SD 10	Grease	3/8 (10)	35 (11)	3/8 (10)	1/4 (6)	4,800 (331)	HPH23#	
	SD 20		3/8 (10)	50 (15)	3/8 (10)	1/4 (6)	4,800 (331)	HPH55#	

#### **Arm in Tank/Bench Mount Position**

Assembled with hose, ball stop kit and roller guide. Required hose inlet kit sold separately.

Reel		Но	se	Connection Size		Maximum	Assembly	Recommended
Size	Fluid	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Hose Inlet Kit
SD 20 —	Air/Water/ Anti-Freeze/ Windshield Washer Fluid	3/8 (10)	65 (20)	1/2 (13)	3/8 (10)	300 (20.7)	HPL5J#	
		1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	300 (20.7)	HPL6H#	218549
	Oil	1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	2,000 (138)	HPM6H#	
	Grease	3/8 (10)	50 (15)	3/8 (10)	1/4 (6)	4,800 (331)	HPH5H#	218550

















>>> Ordering Information

#### **Bare Reels**

#### **Arm in Overhead Mount Position**

Required hose inlet kit sold separately. Fluid hose not included.

	Reel		Hose (Not	Included)	cluded) Connection Size		Maximum	Assembly	Recommended
	Size	Fluid	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Hose Inlet Kit
	SD 10		3/8 (10)	50 (15)	1/2 (13)	3/8 (10)	300 (20.7)	HPL2D#	
	30 10	Air/Water/ Anti-Freeze/	1/2 (13)	35 (11)	1/2 (13)	3/8 (10)	300 (20.7)	HPL2D#	
7 3	SD 20	Windshield Washer Fluid	3/8 (10)	65 (20)	1/2 (13)	1/2 (13)	300 (20.7)	HPL6D#	218549
			1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	300 (20.7)	HPL6D#	
	SD 10	Oil	1/2 (13)	35 (11)	1/2 (13)	1/2 (13)	2,000 (138)	HPM3B#	
	SD 20	UII	1/2 (13)	50 (15)	1/2 (13)	1/2 (13)	2,000 (138)	HPM6D#	
	SD 10		1/4 (6)	50 (15)	3/8 (10)	3/8 (10)	5,000 (345)	HPH1D#	
	20 10	Grease	3/8 (10)	35 (11)	3/8 (10)	3/8 (10)	5,000 (345)	HPH1D#	218550
	SD 20		3/8 (10)	50 (15)	3/8 (10)	3/8 (10)	5,000 (345)	HPH5D#	

















#### **SD 10 Oil Reel Packages**

	Reel Size	Fluid	Valve Type	Enclosure	Package		Package	Includes	
_	neer Size	11001 0120	valve Type	Eliciosule	Number	Reel Assembly	Enclosure	Hose Inlet Kit	Meter
<b>6</b>			SDM8 Manual Meter with Rigid Extension	No	24E001	НРМЗЗВ	-	218549	25M404
1		O.		Yes	24D996	НРМЗЗВ	24A217	218549	25M404
	SD 10		Oil SDM8 Manual Meter with Flexible Extension	No	24E002	НРМЗЗВ	-	218549	25M406
	30 10	Oii		Yes	24D997	HPM33B	24A217	218549	25M406
			None	Yes	24D995	HPM33B	24A217	218549	-

#### **SD 10 Air/Water Reel Packages**

					Package			Package Includes	3	
	Reel Size	Fluid	Valve Type	Enclosure	Number	Reel Assembly	Enclosure	Hose Inlet Kit	Valve	Fitting
				No	24D999	HPL23B	-	218549	180685	150287
		Water	Water Bib Dispense Valve	Yes -	24D993	HPL23B	24A217	218549	180685	150287
					24D994	HPL33B	24A217	218549	180685	159842
	CD 40	0 10 Air	Air Tire Chuck Valve	No	24D998	HPL23B	-	218549	218545	-
	20 10			Yes	24D992	HPL23B	24A217	218549	218545	-
	Air/W	Air/Water			24D989	HPL23B	24A217	218549	-	-
			None	Yes	24D990	HPL25B	24A217	218549	-	-
					24D991	HPL33B	24A217	218549	-	-

#### **SD Series Hose Reel Accessories**

















Ordering Information

#### **Enclosure Kits for One Reel**

Open mounting accommodates up to six reels. Includes all parts necessary to mount on wall or ceiling. Requires mounting channel.



Reel Size	White	Metallic Blue	Red	Black	Dark Blue	Yellow	Required End-Caps (set of 2)
SD 10	24A217	24A940	24A941	24A942	24A943	24A944	24A950
SD 20	24A218	24A945	24A946	24A947	24A948	24A949	24A951

Part Number

218549

218550

224417


#### **Hose Inlet Kits**

A hose inlet kit is required when ordering an SD reel.



#### **Ball Stop Kits**

SD reel packages include ball stop kits. Items below are available for bare reels and as replacement parts.



#### **Mounting Channels**

Accommodates up to six reels. Includes all parts necessary to mount on wall or ceiling.

	Description	1 Reel	2 Reels	3 Reels	4 Reels	5 Reels	6 Reels
	Enclosed Reel Mounting Channel	203521	203522	203523	203524	203525	203526
P	Open Reel Mounting Channel	24A934	24A935	24A936	24A937	24A938	24A939
	I-Beam Mounting Bracket*		204741 (x 2)			204741 (x 3)	

Length

ft (m)

2 (0.6)

\*Secures mounting channel to I-beam without drilling – 2 are required for 1-3 reels, and 3 are required for 4-6 reels.

















#### **Swivel Mounting Bracket**

Allows reel to swivel 120° with two lockable positions.

The Village	Part Number	Description
	24N444	Swivel mounting bracket for installing SD 10 reels

#### **Easy Slide-In Mount**

Allows reel to slide in and out of mount for easy installation.

Part Number	Description
24H193	Ceiling or wall slide-in mount for SD 10 or SD 20 reels

#### **Retrofit Adapter Kits**

Part Number	Description
24C100	Includes all parts to mount an SD 10 hose reel to an existing 250 series mounting pattern with enclosure

#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
() GRACO	17\$659	Red
G GRACO	17S660	Blue
O GRACO	17S661	Green
Oanaco	17S662	Yellow
OGRACO	17S663	White

#### **SD Series Cord and Light Reels**

#### **Quality Cord and Light Reels**

Organize your work space for a safer, more productive work environment. Make Graco your single source for your entire reel bank.



#### **Durable Frame in Two Sizes**

Choose from the heavy-duty steel construction of the SD Series 5 or 10.

#### Multiple Cord Lengths

Choose from 35, 50 and 95 foot (11, 15, 29 meter) options to fit your shop perfectly. Features a 5 foot lead-in cable.

#### Adjustable Arm

Easily change the arm position to fit more applications. Works on walls, ceilings or bench mounts.

#### Heavy-Duty Pedestal

High-strength steel construction with rolled edges and ribbed stress points that won't flex or twist.


#### Multiple Configurations Available

Comes with or without receptacles so you can configure it for your specific needs. Light reels come in your choice of fluorescent or LED with optional tool tap receptacle.

#### **Typical Applications**

- · Automotive dealerships
- · Fast lube centers
- · Service shops
- · Heavy-duty dealerships
- · Fleet services facilities
- In-plant
- · Lube trucks
- Mining

im	mensions					
		SD Series 5	SD Series 10			
	Α	3.5 in (89 mm)	3.5 in (89 mm)			
	В	6.38 in (162 mm)	7.5 in (191 mm)			
	С	4.7 in (120 mm)	4.7 in (120 mm)			
	D	7.48 in (190 mm)	9 in (229 mm)			
	Е	14.8 in (376 mm)	19.5 in (498 mm)			
	F	6.6 in (168 mm)	7 in (177 mm)			
	G	13.84 in (352 mm)	17.5 in (445 mm)			



#### **Technical Specifications**

U							
	Ope	rating	Temperature Range				
		Cord	Reels	-22°F to 122°F (-30°C to 50°C)			
		Ligh	t Reels	-4°F to 104°F (-20°C to 40°C)			
	Weig	ght wi	thout Accessories				
		SD 5	16 AWG, Length 35 ft	25.4 lb			
			16 AWG, Length 50 ft	27.6 lb			
	20V		12 AWG, Length 35 ft	28.2 lb			
	12		12 AWG, Length 50 ft	32.0 lb			
		10	16 AWG, Length 95 ft	46.3 lb			
		SD	12 AWG, Length 95 ft	51.8 lb			
	Instr	uctior	n Manual	3A2592			

**UL/CSA** Approved





#### SD Cord and Light Reels – 120 Volt

120 volt cord and light reels have a black finish and are ETL approved to US and CSA standards.

	Accessory	Reel Size	AWG	Amp	Cord Length	Insulation	Part Number
		SD 5	12	20	50 ft (15 m)	SJOOW	24Y859
	No Accessory – Cord Only	SD 10	12	18	95 ft (29 m)	SJOOW	24Y880
		SD 5	16	13	50 ft (15 m)	SJTOW	24Y861
		SD 5	12	20	35 ft (11 m)	SJ00W	24Y862
	Single Industrial Receptacle	SD 5	12	20	50 ft (15 m)	SJ00W	24Y863
		SD 10	12	18	95 ft (29 m)	SJ00W	24Y882
	Tri-Plug GFCI Industrial Receptacle	SD 5	12	15	50 ft (15 m)	SJ00W	24Y864
		SD 10	12	15	95 ft (29 m)	SJ00W	24Y883
	LED Light	SD 5	16	<1	35 ft (11 m)	SJTOW	24Y869
G man		SD 5	16	<1	50 ft (15 m)	SJTOW	24Y870
		SD 10	16	<1	95 ft (29 m)	SJTOW	24Y886
k		SD 5	16	12	35 ft (11 m)	SJTOW	24Y871
Gana	LED Light with In-line Tool Tap	SD 5	16	12	50 ft (15 m)	SJTOW	24Y872
		SD 10	16	10	95 ft (29 m)	SJTOW	24Y887

### **SD Series Cord and Light Reels**



#### Accessory Ordering Information

#### **Enclosure Kits**

Includes an enclosure for one reel. A set of end-caps are required per single or bank of reels. Requires you to order Enclosed Reel Mounting Channel separately. For mounting SD 5 or SD 10 reels in size 20 enclosures, please see Adapter Kits on page 227.



Reel Size	White	Metallic Blue	Red	Black	Dark Blue	Yellow	Required End-Caps (set of 2)
SD 5 with size 10 enclosure	24N690	24N682	24N683	24N684	24N691	24N685	24A950
SD 10 with size 10 enclosure	24A217	24A940	24A941	24A942	24A943	24A944	24A950

#### **Mounting Channels**

Accommodates up to six reels. Includes all parts necessary to mount on wall or ceiling.

_	Description	Reel Size	1 Reel	2 Reels	3 Reels	4 Reels	5 Reels	6 Reels
	Enclosed Reel Mounting Channel	SD 5 and SD 10	203521	203522	203523	203524	203525	203526
	Open Reel Mounting Channel	SD 5	24N674	24N675	-	-	-	-
		SD 10	24A934	24A935	24A936	24A937	24A938	24A939
I-Beam Mounting Bracket* SD 5		SD 5 and SD 10	204741 (x 2)			204741 (x 3)		

<sup>\*</sup>Secures mounting channel to I-beam without drilling - 2 are required for 1-3 reels, and 3 are required for 4-6 reels.

#### Ordering Information

#### **Swivel Mounting Bracket**

Allows reel to swivel 120° with two lockable positions.



Reel Size	Part Number	Description			
SD 5	24N814	Swivel mounting bracket for installation			
SD 10	24N444	Swivel mounting bracket for installation			

#### **Wall/Ceiling Mounting Bracket**

Allows you to slide the reel in and out for easy installation.

Reel Size	Part Number	Description
SD 5	24N686	Wall/ceiling easy mount plate kit
SD 10	24H193	Wall/ceiling easy mount plate kit

#### **Adapter Kits**



	Part Number	Description
24P164 Space		Spacer bracket for mounting a size 5 reel to an existing size 10 enclosure
	24P880	Spacer bracket for mounting a size 5 reel to an existing size 20 enclosure
	24P881	Spacer bracket for mounting a size 10 reel to an existing size 20 enclosure
	16N883	Clamping plate to mount a size 5 reel to an existing SD Series open channel

#### **Hands-Free Magnetic Clip**

Non-marring cover won't scratch vehicle finish. Snap onto light tube for hands-free operation.

Part Number	Description
16P999	Magnetic clip for light tube

#### **XD Series Hose Reels**















10 / 20 / 20 HN



#### **Extreme Performer**

The high-performance and heavy-duty XD Series Hose Reel is ideal for rugged indoor and outdoor use in truck dealerships, fleet maintenance, mining maintenance, public works garages, construction vehicle maintenance and service trucks. Features high-strength dual pedestals for reliable performance in extreme applications.

#### Spring Adjustment

Increase or decrease spring tension while reel is pressurized with fluid.

#### Full-Flow Swivel

Maximize material flow with minimal pressure drop for faster fills to get more vehicles through your shop.

#### Optional Adjustable Arm

Easily change to one of six arm positions to fit your application. Order with arm (HS models) or without (HN models).

#### **Durable Finish**

Baked-on enamel finish (three colors available) protects reel from corrosion.

#### Large Hose Capacity with Small Profile

Compact pedestal and spool fits into tight spaces and can accommodate 35-65 foot (10.7-19.8 meters) hose capacity for a wide variety of applications.

#### **Typical Applications**

- · Heavy-duty truck dealers
- Fleet maintenance
- · Mining maintenance
- Public works garage
- Construction vehicle maintenance
- Heavy-duty mobile service trucks
- Mining
- · Lube trucks

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Air
- Water
- Grease
- Anti-freeze
- · Windshield washer fluid

#### **Technical Specifications**

Operating Temperature Range				
Air/Water/Anti-Freeze/ Windshield Washer Fluid	-20°F to 190°F (-28°C to 87°C)			
Oil	-20°F to 190°F (-28°C to 87°C)			
Grease	-40°F to 200°F (-40°C to 93°C)			
Wetted Parts				
Air/Water/Anti-Freeze/ Windshield Washer Fluid	Zinc plated steel, anodized aluminum, nitrile rubber			
Oil	Zinc plated steel, anodized aluminum, nitrile rubber			
Grease	Zinc plated steel, polyurethane, steel			
Weight (Without Hose)				
HS Models (With Adjustable Arm)	59 lb (26.5 kg)			
HN Models (Without Arm)	52 lb (23.5 kg)			
Sound Pressure Level	80 dB(A)			
Sound Power Level	88 dB(A)			
Instruction Manual	313431			



















Dime	ensions		
	HS Models (with	HN Models (without Arm)	
	XD 10	XD 20	XD 20
Α	7.5 in (196 mm)	7.5 in (196 mm)	7.5 in (196 mm)
В	16.2 in (412 mm)	18.1 in (460 mm)	18.1 in (460 mm)
С	21.0 in (533 mm)	23.4 in (594 mm)	23.4 in (594 mm)
D	18.0 in (457 mm)	20.0 in (508 mm)	20.0 in (508 mm)
Е	18.5 in (470 mm)	21.0 in (533 mm)	21.0 in (533 mm)
F	22.5 in (571 mm)	25.2 in (640 mm)	25.2 in (640 mm)






#### **HN Models**



#### **Typical Mounting Configurations**





#### **XD Series Hose Reels**















10 / 20 / 20 HN



#### **XD 10/20 Reel Assembly Ordering Guide**

XD Series reels are available in three colors. Use the chart below to determine the correct part number to order. The last character of each part number indicates the hose reel color.

Reel Color	Identifier
White	А
Metallic Blue	В
Yellow	F

**Order Example:** 

Arm in bench/truck mount position, XD 20, oil, 1/2 in ID hose, 50 ft hose length

**Select your reel position:** 

HSM65#

**Select your reel color:** 

Metallic Blue = "B"

(from Reel Assembly Ordering Guide - opposite)

**Order Part Number:** 

HSM65B



#### HS Models (with Adjustable Arm)


#### **Reel Assemblies**

Assembly includes hose, ball stop kit and roller guide. Required hose inlet kit sold separately.

	Reel		Hose (Included)		Connection Size		Maximum	Assembly	Recommended
	Size	Fluid	ID in (mm)	Length ft (m)	Inlet	Outlet	Pressure psi (bar)	Part Number	Hose Inlet Kit
		Air/Water/Anti-Freeze/	3/8 (10)	50 (15)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	HSL25#	
		Windshield Washer Fluid	1/2 (13)	35 (11)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)	HSL33#	218549
	XD 10	Oil	1/2 (13)	35 (11)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	HSM33#	
		Grease	1/4 (6)	50 (15)	3/8 NPSM(M)	1/4 NPT(M)	5,000 (552)	HSH15#	218550
	V/D 00	Air/Water/Anti-Freeze/ Windshield Washer Fluid	3/8 (10)	65 (20)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	HSL56#	
			1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)	HSL65#	218549
	XD 20	Oil	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	HSM65#	
		Grease	3/8 (10)	50 (15)	3/8 NPSM(M)	1/4 NPT(M)	4,800 (331)	HSH55#	218550

#### **Bare Reels**

Required hose inlet kit sold separately. Fluid hose not included.

















10 / 20 / 20 HN

#### Ordering Information

#### HN Models (without Adjustable Arm)

Required hose inlet kit sold separately.



Reel		Hose (Included)		Connec	tion Size	Maximum	Bare Reel,	Recommended
Size	Fluid	ID in (mm)	Length ft (m)	Inlet	Outlet	Pressure psi (bar)	Hose Assembly Part Number	Hose Inlet Kit
	Air/Water/ Anti-Freeze/	3/8 (10)	65 (20)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	HNL56#	
	Windshield Washer Fluid	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)	HNL65#	218549
XD 20	Oil	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	HNM65#	
	Grease	3/8 (10)	50 (15)	3/8 NPSM(M)	1/4 NPT(M)	4,800 (331)	HNH55#	218550

#### HN Model Specialty Packages (without Adjustable Arm)

Includes hose guide kit. Required hose inlet kit sold separately.



Reel		Hose (In	icluded)	Connecti	on Size	Maximum	Part Number			Hose	Recommended
Size	Fluid	ID in (mm)	Length ft (m)	Inlet	Outlet	Pressure psi (bar)	Metallic Blue	White	Yellow	Guide Kit (Included)	Hose Inlet Kit
	Air/Water/ Anti-Freeze/	3/8 (10)	65 (20)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	24C246	24C245	24C247		
XD 20	Windshield Washer Fluid	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)	24C249	24C248	24C250	15Y478	218549
	Oil	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	24C252	24C251	24C253		
	Grease	3/8 (10)	50 (15)	3/8 NPSM(M)	1/4 NPT(M)	4,800 (331)	24C255	24C254	24C256		218550

#### **XD Series Hose Reel Accessories**















10 / 20 / 20 HN



#### >>> Ordering Information

#### **Ball Stop Kits**

XD HS models include ball stop kits. Order separately if ordering a bare reel or if needed with HN models.



Part Number	Description
222225	For 1/4 in (6 mm) ID hose (not compatible with XD30, 700 or 750)
218340	For 1/4 in to 3/8 in (6 mm to 10 mm) ID hose (not for use with XD30, 700 or 750)
218341	0.782 in ID used for 3/8 in and 1/2 in (10 mm and 13 mm) hose (not compatible with XD30, 700 or 750)
237872	1.0 in ID used for 5/8 in (16 mm) hose
237873	1.123 in ID used for 3/4 in (19 mm) hose
237874	1.374 in ID used for 1 in (25 mm) hose
24D132	For 3/8 in (10 mm) ID hose
24D133	For 1/2 in (13 mm) ID hose

#### **Hose Inlet Kits**

A hose inlet kit is required when ordering an SD reel.

	Maximum Working Pressure psi (bar)	Size in (mm)	Length ft (m)	Part Number
	2,000 (137)	1/2 (13)		218549
	4,000 (276)	3/8 (10)	2 (0.6)	218550
	5,000 (345)	1/4 (6)		224417

#### **Mounting Channels**

Accommodates up to six reels. Includes all parts necessary to mount on wall or ceiling.

_	Description	1 Reel	2 Reels	3 Reels	4 Reels	5 Reels	6 Reels
	Enclosed Reel Mounting Channel	24N323	24N324	24N325	24N326	24N327	24N328
	Open Reel Mounting Channel	24A219	24A220	24A221	24A222	24A222	24A222
	I-Beam Mounting Bracket*	204741 (x 2)			204741 (x 3)		

\*Secures mounting channel to I-beam without drilling - 2 are required for 1-3 reels, and 3 are required for 4-6 reels.



















10 / 20 / 20 HN



#### **Enclosure Kits for One Reel**

Open mounting accommodates up to six reels. Includes all parts necessary to mount on wall or ceiling. Requires Enclosed Reel Mounting Channel.

	Reel Size	White	Metallic Blue	Red	Black	Dark Blue	Yellow	Required End-Caps (set of 2)
G	XD 10	24N331	24N332	24N333	24N334	24N335	24N336	24A950
	XD 20	24N337	24N339	24N340	24N341	24N342	24N343	24A951

#### **Retrofit Adapter Kit**

	Part Number	Description
	24A224	Includes all parts to mount hose reel to existing 500 series mounting pattern without enclosure
-	24P914	Includes all parts to convert XD20 hose reels to fit existing 500 series enclosures

#### **Valve Hanger Kit**

Part Number	Description
224444	Mounts to side of reel to allow hanging of non-metered and high-flow dispensing valves

#### **Self-Adhesive Identification Label Set**

C annual C services C annual C	Part Number	Description
© set one © premium © set one © constant © set one © water © set over © constant © set over © constant	180698	Set includes: 1 in x 5 in (25.4 mm x 127 mm) hose reels labels for Anti-Freeze, Water, SAE 5-40, SAE 10-40, SAE 20W, Hydraulic, Gear, SAE 10W, SAE 10-30, SAE 30W, Dexron, Air, Chassis, ATF

#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
OGRACO	17S659	Red
G GRACO	17S660	Blue
O GRACO	17S661	Green
Ognaco	17\$662	Yellow
OGRACO	17S663	White

#### **XD Series Hose Reels**























30 / 30 HN



#### **High Capacity Reel**

Used in applications requiring longer-range dispense and higher capacity than the standard XD 10/20 series. Ideal for use on mobile service trucks, heavy construction and industrial plants.



Increase or decrease spring tension while reel is pressurized with fluid.

#### Full-Flow Swivel

Maximize material flow with minimal pressure drop for faster fills to get more vehicles through your shop.

#### Optional Adjustable Arm

Easily change to one of seven arm positions to fit your application. Order with arm (HS models) or without (HN models).

#### **Durable Finish**

Baked-on enamel finish (four colors available) protects reel from corrosion.

#### Large Hose Capacity with Small Profile

Compact pedestal and spool fits into tight spaces and can accommodate 30-75 foot (9.1-22.8 meters) hose capacity for a wide variety of applications.

#### **Typical Applications**

- · Heavy-duty truck dealers
- Fleet maintenance
- · Mining maintenance
- · Public works garage
- · Construction vehicle maintenance
- · Heavy-duty mobile service trucks
- Mining
- · Lube trucks

#### **Typical Fluids Handled**

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- · Diesel fuel
- Air
- Water
- Grease
- Anti-freeze
- Windshield washer fluid
- Pressure wash
- Waste oil evacuation
- Diesel exhaust fluid (DEF)

#### **Technical Specifications**

1111100	mod opcomodication					
Ope	Operating Temperature Range					
	Air/Water/Anti-Freeze/ Windshield Washer Fluid	-40°F to 180°F (-40°C to 82°C)				
	Oil	-40°F to 180°F (-40°C to 82°C)				
	Grease	-40°F to 180°F (-40°C to 82°C)				
	Pressure Wash	-20°F to 225°F (-28°C to 107°C)				
	Fuel/Evacuation	-40°F to 120°F (-40°C to 49°C)				
	Diesel Exhaust Fluid (DEF)	12°F to 140°F (-11°C to 60°C)				
Wet	ted Parts (Bare Reel Only)					
	Air/Water/Anti-Freeze/ Windshield Washer Fluid Reels	Nickel plated carbon steel, aluminum, Buna-N rubber, UHMWPE				
	Oil	Nickel plated carbon steel, aluminum, Buna-N rubber, UHMWPE				
	Grease	Nickel plated stainless steel, Buna-N rubber, UHMWPE				
	Pressure Wash	Nickel plated stainless steel, Buna-N rubber, UHMWPE				
	Fuel/Evacuation	Nickel plated carbon steel, aluminum, Buna-N rubber, UHMWPE				
Diesel Exhaust Fluid (DEF)		Zinc plated steel, polyurethane, steel				
Weight (Without Hose)		98 lb (44.5 kg)				
Sound Pressure Level		85.8 dB(A)				
Soul	nd Power Level	94.9 dB(A)				
Instr	ruction Manual	3A0138				
























30 / 30 HN

Dimensions							
	HS Models (with Adjustable Arm)	HN Models (without Arm)					
А	9.0 in (229 mm)	7.5 in (196 mm)					
В	21.5 in (546 mm)	18.1 in (460 mm)					
С	26.0 in (659 mm)	23.4 in (594 mm)					
D	22.1 in (562 mm)	20.0 in (508 mm)					
Е	23.1 in (588 mm)	21.0 in (533 mm)					
F	27.6 in (701 mm)	25.2 in (640 mm)					

# **HS Models**

# **HN Models**



#### **Typical Mounting Configurations**



#### **XD Series Hose Reels**























30 / 30 HN



#### **XD 30 Reel Assembly Ordering Guide**

XD Series reels are available in four colors. Use the chart below to determine the correct part number to order. The last character of each part number indicates the hose reel color.

Reel Color	Identifier
White	А
Metallic Blue	В
Yellow	F
Desert Sand*	G

\*Desert Sand not available on HN Models.

#### **Order Example:**

Arm in overhead mount position, XD 30, oil, 3/4 in ID hose, 50 ft hose length

1 Select your reel position:

HSMD5#

2

Select your reel color:

Metallic Blue = "B"

(from Reel Assembly Ordering Guide – opposite)

**Order Part Number:** 


HSMD5B



#### HS Models (with Adjustable Arm)

#### **Reel Assemblies**

Assembly includes hose, ball stop kit and roller guide. Required hose inlet kit sold separately.



#### **Bare Reels**

Required hose inlet kit sold separately.



Fluid	Hose (Not Included)		Connection Size		Maximum		Recommended
	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Hose Inlet Kit
Oil	1/2 (13)	75 (23)	1/2 (13) (m)	1/2 (13) (m)	2,000 (138)	HSMCF#	218549
Oll	3/4 (19)	50 (15)	3/4 (19) (m)	3/4 (19) (m)	2,000 (138)	HSMDD#	24E284
Grease	1/2 (13)	50 (15)	1/2 (13) (m)	1/2 (13) (m)	5,000 (345)	HSHCD#	24E283
Pressure Wash	3/8 (10)	75 (23)	1/2 (13) (m)	3/8 (10) (m)	4,000 (276)	HSHFF#	24E283
DEF	3/4 (19)	50 (15)	3/4 (19) (m)	3/4 (19) ORB	50 (3.4)	HSDDD#	24W250 (BSPP)























30 / 30 HN

#### >>> Ordering Information

#### HN Models (without Adjustable Arm)

#### **Reels with Hose**

Required hose inlet kit sold separately.



	Hose (Included)		Connection Size		Maximum	Reel and Hose	Recommended
Fluid	ID in (mm)	Length ft (m)	Inlet	Outlet	Pressure psi (bar)	Assembly Part Number	Hose Inlet Kit
Air/Water/Anti-Freeze/	1/2 (13)	75 (23)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)	HNLC8#	218549
Windshield Washer Fluid	3/4 (19)	50 (15)	3/4 NPSM(M)	3/4 NPT(M)	300 (20.7)	HNLD5#	24E284
Oil	1/2 (13)	75 (23)	1/2 NPSM(M)	1/2 NPT(M)	1,500 (103)	HNMC8#	218549
OII	3/4 (19)	50 (15)	3/4 NPSM(M)	3/4 NPT(M)	1,250 (86)	HNMD5#	24E284
Crano	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	5,000 (345)	HNHC5#	24E283
Grease	3/8 (10)	75 (23)	1/2 NPSM(M)	3/8 NPT(F)	5,000 (345)	HNHB7#	24E283
Pressure Wash	3/8 (10)	75 (23)	1/2 NPSM(M)	3/8 NPT(M)	4,000 (276)	HNPB8#	24E283
	1/2 (13)	50 (15)	1/2 NPSM(M)	1/2 NPT(M)	4,500 (310)	HNPC5#	24E283
Fuel/Oil Evacuation	1 (13)	30 (9)	3/4 NPSM(M)	1 NPT(M)	125 (8.6)	HNLE3#	24E285

#### **Bare Reels**

Required hose inlet kit sold separately.



Fluid	Hose (Not Included)		Connection Size		Maximum		Recommended
	ID in (mm)	Length ft (m)	Inlet in (mm)	Outlet in (mm)	Pressure psi (bar)	Part Number	Hose Inlet Kit
Oil	3/4 (19)	50 (15)	3/4 (19) (m)	3/4 (19) (m)	2,000 (138)	HNMDD#	24E284
Grease	1/2 (13)	50 (15)	1/2 (13) (m)	1/2 (13) (m)	5,000 (345)	HNHCD#	24E283
Pressure Wash	3/8 (10)	75 (23)	1/2 (13) (m)	3/8 (10) (m)	4,000 (276)	HNHFF#	24E283

#### **Ball Stop Kits**

XD HS models include ball stop kits. Order separately if ordering a bare reel or if needed with HN models.



Part Number	Description					
222225	For 1/4 in (6 mm) ID hose (not compatible with XD30, 700 or 750)					
218340	For 1/4-3/8 in (6-10 mm) ID hose (not for use with XD30, 700 or 750)					
218341	0.782 in ID used for 3/8 in and 1/2 in (10 mm and 13 mm) hose (not compatible with XD30, 700 or 750)					
237872	1.0 in ID used for 5/8 in (16 mm) hose					
237873	1.123 in ID used for 3/4 in (19 mm) hose					
237874	1.374 in ID used for 1 in (25 mm) hose					
24D132	For 3/8 in (10 mm) ID hose					
24D133	For 1/2 in (13 mm) ID hose					

#### **XD Series Hose Reel Accessories**























30 / 30 HN



#### **Hose Inlet Kits**

A hose inlet kit is required when ordering an XD reel.

	Part Number	Description
	218549	1/2 in (13 mm) hose inlet kit for air/water and oil. 2,000 psi (137 bar), 1/2 in NPT hose inlet ID, 24 in (610 mm) long
	24E284	3/4 in (19 mm) hose inlet kit for air/water and oil. 1,250 psi (86 bar), 3/4 in NPT hose inlet ID, 24 in (610 mm) long
	24E283	1/2 in (13 mm) hose inlet kit for grease or pressure wash. 5,000 psi (345 bar), 1/2 in NPT hose inlet ID, 24 in (610 mm) long
	24E285	1/2 in (13 mm) hose inlet kit for fuel. 125 psi (8.6 bar), 1/4 in NPT hose inlet ID, 24 in (610 mm) long
	24W250	2 ft DEF inlet hose kit for XD 30 reels. 3/4 in BSPP(F) x cut end and 90° elbow
	24W251	6 ft DEF inlet hose kit for XD 30 reels. 3/4 in BSPP(F) x cut end and 90° elbow
	124875	2 ft DEF hose, 3/4 in BSPP(M) x cut end (inlet hose)
	124581	6 ft DEF hose, 3/4 in BSPP(M) x cut end (inlet hose)

#### **Valve Hanger Kit**

	Part Number	Description
100	224444	Mounts to side of reel to allow hanging of non-metered and high-flow dispensing valves

#### **Self-Adhesive Identification Label Set**

C mental C repond	Part Number	Description
E DES COMP C CONSIDER  E DES COMP C CONSIDER  E DAM COMP C CANADA  E DAM	180698	Set includes: 1 in x 5 in (25.4 mm x 127 mm) hose reels labels for Anti-Freeze, Water, SAE 5-40, SAE 10-40, SAE 20W, Hydraulic, Gear, SAE 10W, SAE 10-30, SAE 30W, Dexron, Air, Chassis, ATF

#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid.

	Part Number	Description
OGRACO	17S659	Red
O GRACO	17S660	Blue
O GRACO	17S661	Green
Oanaca	17S662	Yellow
OGRACO	17S663	White

40 / 50

















#### **Built-In Toughness**

Engineered to take a beating and still reliably perform in harsh environments so it's ready when you need it. Choose from more colors, thread types and hoses or choose the bare reel so you can customize it with your hose. You get a professional look, easier fit and better-performing equipment.

#### Extensive Hose Offering

Standard models come complete with factory-installed hoses on the reel. Large selection of optional reels to fit various applications.

#### Full-Flow Swivel

Maximize material flow with minimal pressure drop for faster fills to get more vehicles through your shop.

#### Rugged and Durable Body

Heavy-duty welded spool and ribbed frame for extra strength and toughness over the long haul.

#### Meets Worldwide Needs

Built standard with 90° elbow with NPT, BSPP or BSPT threads. 1-1/2 in models also include 2 in Victaulic<sup>™</sup>\*-style groove. Accessories attach without the need for adapters.

#### **Typical Applications**

- · Heavy-duty truck dealers
- Fleet maintenance
- · Mining maintenance
- Public works garages
- Construction vehicle maintenance
- Heavy-duty mobile service trucks
- Agriculture
- Lube trucks

#### Typical Fluids Handled

- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Diesel fuel
- Air
- Water
- Anti-freeze
- Waste oil evacuation

chnical Sp	hnical Specifications						
Operating	Temperature Range						
	Oil Reels – 1 inch	-20°F to 180°F (-28°C to 82°C)					
	All Other Reels	-40°F to 180°F (-40°C to 82°C)					
Wetted Pa	arts	Carbon steel, nickel plated cast iron, Buna-N rubber, FKM UHMWPE					
Maximum Mounting	n Recommended Height	15 ft (4.6 m)					
Sound Pro	essure Level	77.6 dB(A)					
Sound Po	wer Level	86.8 dB(A)					



## How to Select an XD 40/50 Hose Reel

## 2 Ways to Order!

#### Option 1 - Reel with Hose

(Pages 242-243)

All models include the hose, hose guide and ball stop kit.



#### Option 2 - Bare Reel

(Pages 242-243)

Bare reel models do not include hose and ball stop kit.



#### **Choose Your Accessories (Pages 244)**



#### **Hose Inlet Kit**

A hose inlet is required for installation. They are appropriately sized for the hose reels based on type of fluid, hose size and pressure.



#### **Support Arm**

For additional support, add arm brackets to the reel. Required for overhead mounting applications.



#### **Mounting Kit**

Overhead mounting options available for XD 40 reels.



Large selection of hoses appropriately sized for the hose reels based on type of fluid, hose size and pressure.



#### **Hose Inlet Kit**

A hose inlet is required for installation. They are appropriately sized for the hose reels based on type of fluid, hose size and pressure.



#### **Ball Stop Kit**

When the ball stop comes in contact with the hose guide, the hose is prohibited from rewinding.



#### **Support Arm**

For additional support, add arm brackets to the reel. Required for overhead mounting applications.



#### **Mounting Kit**

Overhead mounting options available for XD 40 reels.




















Dimensions											
Model	Inlet/Outlet Size	Dimensions in (mm)*									
Model	NPT(F)	Α	В	С	D	Е	F				
XD 4010 – Model 1	1 in/1 in	11.83 (300)	24 (610)	26.13 (664)	26.4 (671)	10.91 (277)	16.54 (420)				
XD 4010 – Model 2	1 in/1 in	11.83 (300)	24 (610)	26.13 (664)	26.4 (671)	10.91 (277)	17.47 (444)				
XD 5010	1 in/1 in	11.83 (300)	28.5 (724)	30.13 (765)	29.4 (747)	10.91 (277)	17.4 (444)				
XD 5015	1-1/2 in/ 1-1/2 in	11.83 (300)	28.5 (724)	30.13 (765)	29.4 (747)	10.91 (277)	18.24 (463)				

<sup>\*</sup>For complete list of dimensions, see Graco product manual 3A2990.

#### **Typical Mounting Configurations**



#### **XD Series Hose Reels**















40 / 50




#### Ordering Information

#### **XD 40 Reels with Hose**

Includes hose, ball stop kit and hose guide. Required hose inlet kit sold separately.

	Reel	Fluid	Ho	se	Connect	tion Size	Maximum	Part N	umber by Ree	l Color	Hose Inlet Kit	Truck/Bench
	Size		ID in (mm)	Length ft (m)	Inlet NPT(F)	Outlet NPT(M)	Pressure psi (bar)	Metallic Blue	Yellow	White	(Order Separately)	Mount Only
			1/2 (13)	100 (30)	1	1/2	300 (21)	24P327	24P328	24P329		
		Air/Matar	3/4 (19)	75 (23)	1	3/4	300 (21)	24P330	24P331	24P332		
		Air/Water	3/4 (19)	100 (30)	1	3/4	300 (21)	24P333	24P334	24P335		
	XD 4010		1 (25)	50 (15)	1	1	300 (21)	24P336	24P337	24P338		
HILL HOLE		Anti-Freeze	3/4 (19)	100 (30)	1	3/4	300 (21)	24P984	24P985	24P986		
		Oil	1/2 (13)	100 (30)	1	1/2	2,000 (138)	24P339	24P340	24P341	24R111	
			3/4 (19)	75 (23)	1	3/4	1,500 (103)	24P342	24P343	24P344		•
1-12			3/4 (19)	75 (23)	1	3/4	1,500 (103)	24R857	24R859	24R860		
			3/4 (19)	100 (30)	1	3/4	1,500 (103)	24P345	24P346	24P347		
			1 (25)	50 (15)	1	1	1,275 (88)	24P348	24P349	24P350		•
			1 (25)	50 (15)	1	1	1,275 (88)	24R861	24R862	24R863		
		Waste Oil Evacuation	1 (25)	50 (15)	1	1	250 (17)	24P351	24P352	24P353	24R112	
		Diesel Fuel	1 (25)	50 (15)	1	1	250 (17)	24P354	24P355	24P356	24R115	

#### **XD 40 Bare Reels**



#### **Remember to Order!**



















#### Ordering Information

#### **XD 50 Reels with Hose**

Includes hose, ball stop kit and hose guide. Required hose inlet kit sold separately.

	Reel		Но	se	Connect	tion Size	Maximum	Part N	umber by Ree	l Color	Hose Inlet Kit
	Size	Fluid	ID in (mm)	Length ft (m)	Inlet NPT(F)	Outlet NPT(M)	Pressure psi (bar)	Metallic Blue	Yellow	White	(Order Separately)
		Air/Mator	1 (25)	75 (23)	1	1	300 (21)	24P470	24P471	24P472	
		Air/Water	1 (25)	100 (30)	1	1	300 (21)	24P473	24P474	24P475	040444
	XD 5010	Anti-Freeze	1 (25)	100 (30)	1	1	300 (21)	24P987	24P988	24P989	24R111
	XD 5010	Oil	1 (25)	75 (23)	1	1	1,275 (88)	24P476	24P477	24P478	
		Diesel Fuel	1 (25)	75 (23)	1	1	250 (17)	24P485	24P486	24P487	24R115
			1 (25)	100 (30)	1	1	250 (17)	24P488	24P489	24P490	
		Waste Oil	1-1/4 (32)	35 (11)	1-1/2	1-1/4	200 (14)	24P479	24P480	24P481	
		Evacuation	1-1/4 (32)	50 (15)	1-1/2	1-1/4	200 (14)	24P482	24P483	24P484	-
	XD 5015**		1-1/4 (32)	35 (11)	1-1/2	1-1/4	250 (17)	24P491	24P492	24P493	24R117
		Diesel Fuel	1-1/4 (32)	50 (15)	1-1/2	1-1/4	250 (17)	24P494	24P495	24P496	
			1-1/2 (38)	50 (15)	1-1/2	1-1/2	150 (10)	24P497	24P498	24P499	

<sup>\*\*</sup>Standard 2 inch Vitaulic $^{\text{\tiny{IM}}}$ -style groove on inlet.

#### **XD 50 Bare Reels**

	Reel		Hose Length Capacity (in x ft (m))			Connection Size		Maximum	Part Number by Reel Color			Hose Inlet Kit
	Size		1	1-1/4	1-1/2	Inlet NPT(F)	Outlet NPT(F)	Pressure psi (bar)	Metallic Blue	Yellow	White	(order separately)
		Air/Water	100 (30)	_	_	1	1	600 (41)	24P455	24P456	24P457	
	XD 5010	Anti-Freeze	100 (30)	_	-	1	1	600 (41)	26A143	26A144	26A145	24R111
		Oil	75 (23)	-	-	1	1	2,000 (138)	24P458	24P459	24P460	
		Diesel Fuel	100 (30)	-	-	1	1	600 (41)	24P455	24P456	24P457	- 24R115
0.3			75 (23)	-	-	1	1	600 (41)	24P464	24P465	24P466	
		Waste Oil Evacuation	-	50 (15)		1-1/2	1-1/2	600 (41)	24P461	24P462	24P463	-
2	XD 5015**	Diesel Fuel	-	50 (15)	-	1-1/2	1-1/2	600 (41)	24P461	24P462	24P463	24R117
			-	50 (15)	50 (15)	1-1/2	1-1/2	600 (41)	24P467	24P468	24P469	

<sup>\*\*</sup>Standard 2 inch Vitaulic™-style groove on inlet.

#### **Remember to Order!**



Victaulic is a trademark of Victaulic Company of America.



#### **XD Series Hose Reel Accessories**















40 / 50



#### >>> Ordering Information

#### **Ball Stop Kits**



Part Number	Description
237873	Ball stop kit used for 3/4 in (19 mm) hose
237874	Ball stop kit used for 1 in (25 mm) hose
24R060	Ball stop kit used for a 1-1/4 in (32 mm) hose
24R061	Ball stop kit used for a 1-1/2 in (38 mm) hose

#### **Hose Guides**



Part Number	Description
24R072	Roller guide kit with bracket for XD 40 and XD 60
24R074	Roller guide kit with bracket for XD 50

#### **Support Arm Kits**



Part Number	Description
24R076	Support arm kit for XD 40
24R077	Support arm kit for XD 50

#### **Mounting Kit**



Part Number	Description
237932	Overhead or wall mounting kit for XD 40. Includes all parts needed for ceiling mounting 1 reel.

#### **Hose Inlet Kits**



Part Number	Description
24R111	1 in (25 mm) hose inlet kit for air/water and oil. 1,275 psi (88 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
24R112	1 in (25 mm) hose inlet kit for waste oil evacuation. 250 psi (17 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
24R115	1 in (25 mm) hose inlet kit for diesel fuel. 250 psi (17 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
24R117	1-1/2 in (38 mm) hose inlet kit for diesel fuel. 150 psi (10 bar), 1.5 in NPT hose inlet ID, 28 in (710 mm) long

#### **Self-Adhesive Identification Label Set**

40	-	8	-
40		50	400
50	846 10:00	9	ренлом
62	\$16.000	2	CHROSE
50	Bed 100	£	MACHINE.
2	SACORE	2	SIGNA
0	See new	ē	- 40

Part Number	Description
180698	Set includes: 1 in x 5 in (25.4 mm x 127 mm) hose reels labels for Anti-Freeze, Water, SAE 5-40, SAE 10-40, SAE 20W, Hydraulic, Gear, SAE 10W, SAE 10-30, SAE 30W, Dexron, Air, Chassis, ATF

#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid

	Part Number	Description
O GRACO	17S659	Red
Q GRACO	17S660	Blue
O GRACO	17S661	Green
O GRACO	17S662	Yellow
O GRACO	17S663	White



#### **XD Series Powered Bare Hose Reels**


















60 / 70 / 80



#### Safe, Versatile Powered Hose Reels

We like to think of the XD motor rewind reels as super-powered. The innovative design is packed with features to help you work safer, smarter and faster. We demand extensive product testing, often exceeding industry standards to ensure you get the best product on the market.



#### Safe, Reliable Direct Drive and Gear Motors

Drive unit is clean and lubricated for life. No need to worry about greasy, exposed drive chains that need maintenance and can be dangerous to operators.

#### Easy System Integration

Easily change the inlet and motor direction to give you the option of a right- or left-hand flow orientation.

#### Heavy-duty Welded Spool

Built to handle the weight of heavy hoses. Designed to surround and protect the drive unit from the elements to promote longer-lasting, safer operation.

#### Rugged and Durable Body

Heavy-duty one piece welded frame is engineered to flex under extreme operating conditions and is stronger than bolted frames that can loosen with use. Individually painted and powder-coated components have superior corrosion resistance over assembled and painted products.

#### **Typical Applications**

- · Heavy-duty truck dealers
- · Fleet maintenance
- · Mining maintenance
- · Public works garages
- Construction vehicle maintenance
- · Heavy-duty mobile service trucks
- Agriculture
- · Lube trucks

#### Typical Fluids Handled

- · Petroleum- and synthetic-based oils (motor, gear and ATF)
- Diesel fuel
- Air
- Water
- Grease
- Waste oil evacuation

#### **Technical Specifications**

Operating Temperature Range	
Motorless Reels	-40°F to 180°F (-40°C to 82°C)
Air/Water Applications	-40°F to 180°F (-40°C to 82°C)
Waste Oil Evacuation Applications	-40°F to 180°F (-40°C to 82°C)
Oil Applications	-40°F to 180°F (-40°C to 82°C)
Grease Applications	0°F to 180°F (-18°C to 82°C)
Diesel Fuel Applications	-40°F to 140°F (-40°C to 60°C)
Wetted Parts	Nickel plated cast iron, cast iron, Buna-N rubber, polyethylene
Electric and Hydraulic Motors Sound Pressure Level	<80 dB(A)
Pneumatic Motors Sound Pressure Level	84.6 dB(A)
Pneumatic Motors Sound Power Level	89.9 dB(A)
Instruction Manual	332630





















#### **Dimensions** Reference dimension "D" for specific motor type Dimensions in (mm) Inlet/Outlet Α С Model Size (J) (Mounting В D Ε F G NPT(F) Hydraulic Pneumatic Electric Holes) XD6010 1 in/1 in 10.45 (256) 11.8 (300) 20.4 (519) 15.7 (400) 21.6 (547) 10.9 (277) 7.8 (198) 15.5 (394) 26.1 (663) XD7010 1 in/1 in 12.95 (329) 22.9 (583) 18.2 (463) 14.3 (363) 24.1 (611) 10.9 (277) 10 (254) 10 (254) 26.1 (663) 1-1/2 in/ XD7015 12.95 (329) 14.3 (363) 10.9 (277) 23.7 (603) 19 (483) 24.8 (631) 10 (254) 10 (254) 26.1 (663) 1-1/2 in XD7020 10.2 (259) 2 in/2 in 12.95 (329) 14.3 (363) 24.1 (613) 19.4 (493) 25.2 (641) 10 (254) 10 (254) 26.1 (663) XD8010 1 in/1 in 20.68 (525) 22.1 (561) 30.7 (779) 26 (659) 31.8 (807) 13.4 (340) 18 (457) 15.5 (394) 30.1 (765) 1-1/2 in/ XD8015 20.68 (525) 32.5 (827) 13.4 (340) 22.1 (561) 31.4 (799) 26.7 (679) 18 (457) 15.5 (394) 30.1 (765) 1-1/2 in XD8020 2 in/2 in 20.68 (525) 22.1 (561) 31.9 (809) 27.1 (689) 33 (837) 12.7 (323) 18 (457) 15.5 (394) 30.1 (765)

#### **Typical Mounting Configurations**

#### **Bench/Trunk Mount**



#### Truck Mount with Remote Mounted Roller Guide



## **How to Select an XD Powered Bare Hose Reel**

#### A Complete Family of Motor Rewind Hose Reels

The innovative design of the XD reel family is packed with features to help you work safer, smarter and faster. Direct-drive motor options include hydraulic, pneumatic and electric for air, water, oil, grease, fuel dispense and waste oil evacuation applications. Use this selection chart to configure the XD reel to suit your needs.







#### Specify the Hose Fluid Type and Capacity

□ 1/2 (13)

□ 1 (25)

Determine your fluid type and capacity before selecting your reel.

- Fluid Type ☐ Air/Water ☐ Anti-Freeze
- □ Petroleum- and Synthetic-Based Oils
- □ Waste Oil □ Diesel Fuel
- Hose ID Hose Length in (mm) ft (m)
  - □ 50 (15) □ 75 (23)
- □ 100 (30) □ 1-1/2 (38) □ 2 (51) □ 150 (46)

#### **Select Your Drive Type and Frame**

Reels can be ordered with a motor or without. If you choose a model without a motor, you must purchase the motor separately.

- ☐ Order Reel with Motor Included (Pages 250-252)
- ☐ Order Reel and Motor Separately (Page 263)
  - □ Pneumatic Motor
  - ☐ Hydraulic Motor
  - □ Electric Motor
- □ 12 VDC, 1/2 HP □ 12 VDC, 2/3 HP
- □ 24 VDC, 1/2 HP
- □ 24 VDC, 2/3 HP □ 115 VAC, 0.40 HP



#### □ XD 60 □ XD 70 □ XD 80

**Choose Your Reel Size** 

#### **Choose Your Reel Color**

Select from Blue, Yellow or White.

☐ Blue ☐ Yellow ■ White

#### Choose Your Controls (Pages 254)



☐ Pneumatic 2-position, 3-way valve

#### ☐ Hydraulic Motor

- ☐ 12 VDC electric control of hydraulic motor, 3-position,
- □ 12 VDC electric control of hydraulic motor with switch, 3-position, 4-way valve
- ☐ 24 VDC electric control of hydraulic motor, 3-position, 4-way valve
- ☐ 24 VDC electric control of hydraulic motor with switch, 3-position, 4-way valve

#### □ Electric Motor

- ☐ Hazardous location on/off button
- □ 12 VDC intermittent-duty solenoid
- □ 24 VDC intermittent-duty solenoid
- ☐ Manual reset button circuit breaker (25 or 50 amp)

REQUIRED




# Hose Inlet Kit (Page 255) FOR INSTALLATION

A hose inlet is required for installation. They are appropriately sized for the hose reels based on type of fluid, hose size and pressure.

Note: All 1-1/2 in (38 mm) hose reels include a 2 in (51 mm) Victaulic-style groove on inlet. If you are using these reels, it is recommended to order an inlet kit from Graco.

- ☐ Yes (required for installation)
- ☐ No (will supply my own hose inlet kit)



#### **XD Series Bare Hose Reels**
















60 / 70 / 80



#### Ordering Information

#### Reel with Motor - 1 in (25 mm) Inlet/Outlet XD 60 Reels



#### Remember to Order!





See page 255









See page 255

















60 / 70 / 80



# Reel with Motor - 1 in (25 mm) Inlet/Outlet XD 70 / XD 80 Reels

Re	Reel	FL SI	El id	FI :	FI :	El M	Melec	Hose Capacity of Reel ft (m)	Maximum	Weight	Inlet/ Outlet	Reel Part Number by Color			Hose Accessories (Must be ordered separately)	
Si	Size	Fluid	Motor	Hann ID	Pressure psi (bar)	lb (kg)	Size NPT(F)	Metallic Blue	Yellow	White	Hose Inlet Kit	Hose				
			Pneumatic	100 (30)	600 (41)	122 (55)		24R449	24R450	24R451		126363 – 1 in x 75 ft (25 mm x 23 m) 126364 – 1 in x 100 ft (25 mm x 30 m)				
			Hydraulic	100 (30)	600 (41)	100 (45)	1 in/1 in (25 mm/	24R446	24R447	24R448						
		Air/ Water	12 VDC Electric, 1/2 HP	100 (30)	600 (41)	132 (60)		24R437	24R438	24R439						
		···aioi	24 VDC Electric, 1/2 HP	100 (30)	600 (41)	132 (60)	25 mm)	24R440	24R441	24R442						
			115 VAC Electric	100 (30)	600 (41)	132 (60)		24R443	24R444	24R445	040111					
			Pneumatic	100 (30)	3,000 (207)	100 (56)		24R464	24R465	24R466	24R111					
			Hydraulic	100 (30)	3,000 (207)	102 (46)	1 in/1 in	24R461	24R462	24R463		126504 – 1 in x 75 ft (25 mm x 23 m) 126505 – 1 in x 100 ft (25 mm x 30 m)				
XD 7	7010	Oil	12 VDC Electric, 1/2 HP	100 (30)	3,000 (207)	133 (60)	(25 mm/	24R452	24R453	24R454						
			24 VDC Electric, 1/2 HP	100 (30)	3,000 (207)	133 (60)	-	24R455	24R456	24R457						
			115 VAC Electric	100 (30)	3,000 (207)	133 (60)		24R458	24R459	24R460						
			Pneumatic	100 (30)	600 (41)	122 (55)	1 in/1 in (25 mm/	24R449	24R450	24R451	24R115	24R103 – 1 in x 75 ft (25 mm x 23 m) 24R106 – 1 in x 100 ft (25 mm x 30 m)				
		Diesel Fuel	Hydraulic	100 (30)	600 (41)	100 (45)		24R446	24R447	24R448						
1			12 VDC Electric, 1/2 HP	100 (30)	600 (41)	132 (60)		24R437	24R438	24R439						
			24 VDC Electric, 1/2 HP	100 (30)	600 (41)	132 (60)		24R440	24R441	24R442						
			115 VAC Electric	100 (30)	600 (41)	132 (60)		24R443	24R444 24R445	24R445						
			Pneumatic	150 (46)	600 (41)	164 (74)		24R531	24R532 2	24R533		-				
			Hydraulic	150 (46)	600 (41)	142 (64)	1 in/1 in (25 mm/	24R528	24R529	24R530						
24		Air/ Water	12 VDC Electric, 1/2 HP	150 (46)	600 (41)	173 (78)		24R519	24R520	24R521						
		water	24 VDC Electric, 1/2 HP	150 (46)	600 (41)	173 (78)	25 mm)	24R522	24R523	24R524						
			115 VAC Electric	150 (46)	600 (41)	173 (78)		24R525	24R526	24R527						
			Pneumatic	150 (46)	3,000 (207)	165 (75)		24R546	24R547	24R548	24R111	-				
			Hydraulic	150 (46)	3,000 (207)	143 (65)	1 in/1 in	24R543	24R544	24R545						
XD 8	8010	Oil	12 VDC Electric, 1/2 HP	150 (46)	3,000 (207)	175 (79)	(25 mm/	24R534	24R535	24R536						
			24 VDC Electric, 1/2 HP	150 (46)	3,000 (207)	175 (79)	25 mm)	24R537	24R538	24R539						
			115 VAC Electric	150 (46)	3,000 (207)	175 (79)		24R540	24R541	24R542						
			Pneumatic	150 (46)	600 (41)	164 (74)		24R531	24R532	24R533		24T252 – 1 in x 150 ft (25 mm x 46 m)				
			Hydraulic	150 (46)	600 (41)	142 (64)	1 in/1 in	24R528	24R529	24R530						
		Diesel Fuel	12 VAC Electric, 1/2 HP	150 (46)	600 (41)	173 (78)	(25 mm/	24R519	24R520	24R521	24R115					
		1 001	24 VAC Electric, 1/2 HP	150 (46)	600 (41)	173 (78)	25 mm)	24R522	24R523	24R524						
			115 VAC Electric	150 (46)	600 (41)	173 (78)		24R525	24R526	24R527						

#### **Remember to Order!**



#### **XD Series Bare Hose Reels**















60 / 70 / 80



#### Ordering Information

#### Reel with Motor - 1-1/2 in (38 mm) Inlet/Outlet **XD 70 / XD 80 Reels**

	Reel	Fluid	Motor	Hose Capacity of Reel ft (m)	Maximum Pressure	Weight Ib (kg)	Inlet/ Outlet Size NPT(F)	Reel Part Number by Color			Hose Accessories (Must be ordered separately)	
	Size			Hose ID 1-1/2 in (38 mm)	psi (bar)			Metallic Blue	Yellow	White	Hose Inlet Kit	Hose
			Pneumatic	65 (20)	600 (41)	100 (56)		24R516	24R516 24R517	24R518		24R110 – 1-1/4 in x 50 ft (32 mm x 15 m) 24R114 – 1-1/2 in x 50 ft
			Hydraulic	65 (20)	600 (41)	102 (46)	24R512 24R503 24R506 24R509 24R516	24R512	24R513	24R515	24R117	
	XD 7015	Diesel Fuel	12 VDC Electric, 1/2 HP	65 (20)	600 (41)	133 (60)		24R503	24R504	24R505		
			24 VDC Electric, 1/2 HP	65 (20)	600 (41)	133 (60)		24R506	24R507	24R508		(38 mm x 15 m)
			115 VAC Electric	65 (20)	600 (41)	133 (60)		24R509	24R510	24R511		
		Waste	Pneumatic	50 (15)	600 (41)	100 (56)		24R517	24R518		126380 – 1-1/4 in x 35 ft	
			Hydraulic	50 (15)	600 (41)	102 (46)	1-1/2 in/	24R512	24R513	24R515	05 – 08	(32 mm x 11 m)
		Oil	12 VDC Electric, 1/2 HP	50 (15)	600 (41)	133 (60)	1-1/2 in (38 mm/	24R503	24R504	24R505		126688 – 1-1/4 in x 50 ft (32 mm x 15 m)
		Evac.	24 VDC Electric, 1/2 HP	50 (15)	600 (41)	133 (60)	38 mm)	24R506	24R507	24R508		127173 – 1-1/2 in x 50 ft
			115 VAC Electric	50 (15)	600 (41)	133 (60)		24R509	24R510	24R511		(38 mm x 15 m)
	XD 8015		Pneumatic	100 (50)	600 (41)	165 (75)	24R561	24R561	24R562	24R563		
		Diesel Fuel	Hydraulic	100 (50)	600 (41)	143 (65)		24R558 24R559 24F	24R560			
			12 VDC Electric, 1/2 HP	100 (50)	600 (41)	175 (79)		24R549	24R550	24R551	24R117	24T253 – 1-1/2 in x 100 ft (38 mm x 30 m)
			24 VDC Electric, 1/2 HP	100 (50)	600 (41)	175 (79)		24R552	24R553	24R554		(00 11111 X 00 111)
			115 VAC Electric	100 (50)	600 (41)	175 (79)		24R555	24R556	24R557		

#### Reel with Motor - 2 in (51 mm) Inlet/Outlet **XD 70 / XD 80 Reels**

	Reel Size	Fluid	Motor	Hose Capacity of Reel ft (m)	Maximum	Weight Ib (kg)	Inlet/ Outlet Size NPT(F)	Reel Part Number by Color			Hose Accessories (Must be ordered separately)	
			Wiotoi	Hose ID 2 in (51 mm)	Pressure psi (bar)			Metallic Blue	Yellow	White	Hose Inlet Kit	Hose
		Diesel Fuel	Pneumatic	33 (10)	600 (41)	128 (58)		24T023	24T024	24T025	- 24R118 ·	127167 – 2 in x 33 ft (51 mm x 10 m)
	XD 7020		Hydraulic	33 (10)	600 (41)	106 (48)	24T 24T 2 in/2 in (51 mm/ 51 mm) 24F 24F 24F	24T020	24T021	24T022		
			12 VDC Electric, 1/2 HP	33 (10)	600 (41)	137 (62)		24T011	24T012	24T013		
			24 VDC Electric, 1/2 HP	33 (10)	600 (41)	137 (62)		24T014	24T015	24T016		
			115 VAC Electric	33 (10)	600 (41)	137 (62)		24T017	24T018	24T019		
	XD 8020		Pneumatic	50 (15)	600 (41)	169 (76)		24R576	24R577	24R578		24T254 – 2 in x 50 ft (51 mm x 15 m)
			Hydraulic	50 (15)	600 (41)	147 (67)		24R573	24R574	24R575		
			12 VDC Electric, 1/2 HP	50 (15)	600 (41)	179 (81)		24R564	24R565	24R566		
			24 VDC Electric, 1/2 HP	50 (15)	600 (41)	179 (81)		24R567	24R568	24R569		
			115 VAC Electric	50 (15)	600 (41)	179 (81)		24R570	24R571	24R572		

#### Remember to Order!



























60 / 70 / 80



#### **Reel Frames Only**

#### XD 60 / XD 70 / XD 80 Reels

Motor is not included and must be purchased separately.

	Reel			Hose Ca	pacity of Re	eel ft (m)		Maximum	Weight	Inlet/ Outlet	Reel Pa	art Number b	y Color
	Size	Fluid	Hose ID in (mm)					lb (kg)	Size	Metallic	Yellow	White	
			1/2 (13)	3/4 (19)	1 (25)	1-1/2 (38)	2 (51)	por (bar)		NPT(F)	Blue	IGIIOW	WILLE
		Air/Water/ Diesel Fuel	100 (30)	100 (30)	50 (15)	-	-	600 (41)	87 (39)	_	24T104	24T105	24T106
	XD 6010	Oil	100 (30)	100 (30)	50 (15)	-	-	3,000 (207)	88 (40)		24T107	24T108	24T109
		Waste Oil Evac.	_	_	50 (15)	-	-	600 (41)	87 (39)		24T104	24T105	24T106
		Grease	-	_	50 (15)	-	-	3,000 (207)	88 (40)	1 in/1 in	24T107	24T108	24T109
	XD 7010	Air/Water/ Diesel Fuel	-	_	100 (30)	-	-	600 (41)	86 (39)	(25 mm/25 mm) - -	24T110	24T111	24T112
		Oil	_	_	100 (30)	-	_	3,000 (207)	87 (39)		24T113	24T114	24T115
	XD 8010	Air/Water/ Diesel Fuel	-	_	150 (46)	-	-	600 (41)	127 (58)		24T122	24T123	24T124
		Oil	_	_	150 (46)	_	-	3,000 (207)	129 (58)		24T125	24T126	24T127
	VD 701E	Waste Oil Evac.	-	_	_	50 (15)	-	600 (41)	87 (39)	1-1/2 in/	24T116	24T117	24T118
	XD 7015		-	_	_	65 (20)	-	600 (41)	87 (39)	1-1/2 in	24T116	24T117	24T118
	XD 8015	Diesel Fuel	-	_	-	100 (30)	-	600 (41)	129 (58)	(38 mm/38 mm)	24T128	24T129	24T130
	XD 7020	DIESEI FUEI	-	_	_	-	33 (10)	600 (41)	91 (41)	2 in/2 in	24T119	24T120	24T121
	XD 8020		-	-	-	-	50 (15)	600 (41)	133 (60)	(51 mm/51 mm)	24T131	24T132	24T133

#### **Motor Assemblies – Pair with Frame-Only Models**

	Part Number	Description
	24T892	Pneumatic motor assembly, reversible type. For installing motor to bare XD reel.
	24T891	Hydraulic motor assembly, reversible type. For installing motor to bare XD reel.
	24T886	12 VDC, 1/2 HP motor assembly, reversible type. For installing motor to bare XD frame.
	24T910	12 VDC, 2/3 HP motor assembly, reversible type. For installing motor to bare XD frame.
	24T888	24 VDC, 1/2 HP motor assembly, reversible type. For installing motor to bare XD frame.
3	24T911	24 VDC, 2/3 HP motor assembly, reversible type. For installing motor to bare XD frame.
	24T889	115 VAC, 0.40 HP motor assembly, reversible type. For installing motor to bare XD frame.

#### **Remember to Order!**



## **XD Series Bare Hose Reel Accessories**

















#### >>> Ordering Information

## **Motor Controls (Required)**

	Part Number	Description
	127271	Pneumatic valve to control XD 60/70/80 pneumatic powered hose reels. 2-position, 3-way valve.
	24T875	Hydraulic control module for electric over hydraulic control of XD 60/70/80 hydraulic powered hose reels, 12 VDC. 3-position, 4-way valve.
	24T876	Hydraulic control module for electric over hydraulic control of XD 60/70/80 hydraulic powered hose reels, 24 VDC. 3-position, 4-way valve.
3	127224	Hydraulic control module for electric over hydraulic control of XD 60/70/80 hydraulic powered hose reels, 12V, includes switch. 3-position, 4-way valve.
N. Comments	127225	Hydraulic control module for electric over hydraulic control of XD 60/70/80 hydraulic powered hose reels, 24V, includes switch. 3-position, 4-way valve.
	127214	Momentary push-button on/off switch with red rubber cap. Use for 12 or 24 VDC.
8	127217	Hazardous-location push-button on/off switch. Use for 12 and 24 VDC.
61	127223	Hazardous-location push-button on/off switch. Use for 115 and 220 VAC.
	127218	Hazardous-location junction box
10 12	127219	12 VDC intermittent-duty solenoid recommended for activating rewind on 12 VDC motor
	127220	24 VDC intermittent-duty solenoid recommended for activating rewind on 24 VDC motor
	127221	Manual-reset push-button circuit breaker, 50 amp rating
•	127222	Manual-reset push-button circuit breaker, 25 amp rating



















#### **Ball Stop Kits**

|--|--|

Part Number	Description
237873	Ball stop kit used for 3/4 in (19 mm) hose
237874	Ball stop kit used for 1 in (25 mm) hose
24R060	Ball stop kit used for 1.25 in (32 mm) hose
24R061	Ball stop kit used for 1.5 in (38 mm) hose

#### **Hose Guide**

 2.

	Part Number	Description
<b>SEI</b>	24T327	Stainless steel hose guide for XD 60
JE .	24T328	Stainless steel hose guide for XD 70
	24T329	Stainless steel hose guide for XD 80
	24R072	Roller guide kit with bracket for XD 40 and XD 60
1	24T330	Roller guide kit with bracket for XD 70
9	24T331	Roller guide kit with bracket for XD 80

#### **Support Arm Kit with Hose Guide**

Part Number	Description
24T332	Arm kit with stainless steel hose guide for XD 60 (24T327)
24T333	Arm kit with stainless steel hose guide for XD 70 (24T328)
24T334	Arm kit with stainless steel hose guide for XD 80 (24T329)
24T335	Arm kit with roller guide for XD 60 (24R072)
24T336	Arm kit with roller guide for XD 70 (24T330)
24T337	Arm kit with roller guide for XD 80 (24T331)

#### **Hose Inlet Kits**

EXT.	-	

	Part Number	Description
	24R111	1 in (25 mm) hose inlet kit for air/water and oil 1,275 psi (88 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
	24R112	1 in (25 mm) hose inlet kit for waste oil evacuation 250 psi (17 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
NE DE	24R115	1 in (25 mm) hose inlet kit for diesel fuel 250 psi (17 bar), 1 in NPT hose inlet ID, 28 in (710 mm) long
	24R117	1-1/2 in (38 mm) hose inlet kit for diesel fuel 150 psi (10 bar), 1-1/2 in NPT hose inlet ID, 28 in (710 mm) long
	24R118	2 in (51 mm) hose inlet kit for diesel fuel 150 psi (10 bar), 2 in NPT hose inlet ID, 28 in (710 mm) long
	24T858	1-1/2 in (38 mm) hose inlet kit for waste oil evacuation 150 psi (10 bar), 1-1/2 in NPT hose inlet ID, 28 in (710 mm) long

#### **Self-Adhesive Identification Label Set**

50	AND PERSON	92	prospersor, or
- 62	BAE 19-65	92	400
50	BASE HOUSE	92	pomon
92	845 9-49	92	CHARGE
52	BAE 10W	2	WATER
2	SAE 20W	2	GEAR
0	SALE NAME	6	400

Part Number	Description
180698	Set includes: 1 in x 5 in (25.4 mm x 127 mm) hose reels labels for Anti-Freeze, Water, SAE 5-40, SAE 10-40, SAE 20W, Hydraulic, Gear, SAE 10W, SAE 10-30, SAE 30W, Dexron, Air, Chassis, ATF























#### **Hose Identification Wraps**

Vinyl hose wrap for easy identification of meter fluid

	Part Number	Description
OGRACO	17S659	Red
GGRACO	17\$660	Blue
G GRACO	17S661	Green
O GRACO	17S662	Yellow
O GRACO	17S663	White

#### **Air/Water/Anti-Freeze Hoses**



Part Number	Description	Compatible Reel Series
253848	3/8 in x 35 ft (10 mm x 11 m) hose for air/water, 300 psi (20.6 bar)	SD 10, XD 10
253849	3/8 in x 50 ft (10 mm x 15 m) hose for air/water, 300 psi (20.6 bar)	SD 10, XD 10
253850	3/8 in x 65 ft (10 mm x 20 m) hose for air/water, 300 psi (20.6 bar)	SD 20, XD 20
253852	1/2 in x 35 ft (13 mm x 11 m) hose for air/water, 300 psi (20.6 bar)	SD 10, XD 10
253853	1/2 in x 50 ft (13 mm x 15 m) hose for air/water, 300 psi (20.6 bar)	SD 20, XD 20
16A684	1/2 in x 75 ft (13 mm x 23 m) hose for air/water, 300 psi (20.6 bar)	XD 30
126359	1/2 in x 100 ft (13 mm x 30 m) hose for air/water, 300 psi (20.6 bar)	XD 40, XD 60
16A707	3/4 in x 50 ft (19 mm x 15 m) hose for air/water, 300 psi (20.6 bar)	XD 30
126360	3/4 in x 75 ft (19 mm x 23 m) hose for air/water, 300 psi (20.6 bar)	XD 40
126361	3/4 in x 100 ft (19 mm x 30 m) hose for air/water, 300 psi (20.6 bar)	XD 40, XD 60
126362	1 in x 50 ft (25 mm x 15 m) hose for air/water, 300 psi (20.6 bar)	XD 40, XD 60
126363	1 in x 75 ft (25 mm x 23 m) hose for air/water, 300 psi (20.6 bar)	XD 50
126364	1 in x 100 ft (25 mm x 30 m) hose for air/water, 300 psi (20.6 bar)	XD 50, XD 70

#### Oil Hoses



Part Number	Description	Compatible Reel Series
26C121	1/2 in x 35 ft (13 mm x 11 m) hose for oil, 2,000 psi (138 bar)	SD 10, XD 10
26C122	1/2 in x 50 ft (13 mm x 15 m) hose for oil, 2,000 psi (138 bar)	SD 20, XD 20
26C123	1/2 in x 75 ft (13 mm x 23 m) hose for oil, 2,000 psi (138 bar)	XD 30
26C124	1/2 in x 100 ft (13 mm x 30 m) hose for oil, 2,000 psi (138 bar)	XD 40, XD 60
126376	3/4 in x 75 ft (19 mm x 23 m) hose for oil, 1,500 psi (103 bar)	XD 40, XD 60
126377	3/4 in x 100 ft (19 mm x 30 m) hose for oil, 1,500 psi (103 bar)	XD 40, XD 60
126503	1 in x 50 ft (25 mm x 15 m) hose for oil, 1,275 psi (88 bar)	XD 40, XD 60
126504	1 in x 75 ft (25 mm x 23 m) hose for oil, 1,275 psi (88 bar)	XD 50
126505	1 in x 100 ft (25 mm x 30 m) hose for oil, 1,275 psi (88 bar)	XD 70, XD 80

























#### **Grease Hoses**



Part Number	Description	Compatible Reel Series
109158	1/4 in x 50 ft (6 mm x 15m) hose for grease, 5,000 psi (345 bar)	SD 10, XD 10
124470	3/8 in x 35 ft (10 mm x 11 m) hose for grease, 4,800 psi (331 bar)	SD 10, XD 10
124461	3/8 in x 50 ft (10 mm x 15 m) hose for grease, 4,800 psi (331 bar)	SD 20, XD 20
126076	3/8 in x 75 ft (10 mm x 23m) hose for grease, 5,000 psi (345 bar)	XD 30
16A674	1/2 in x 50 ft (13 mm x 15 m) hose for grease, 5,000 psi (345 bar)	XD 30

#### **Waste Oil Evacuation Hoses**



Part Number	Description	Compatible Reel Series
16A686	1 in x 30 ft (25 mm x 9 m) hose for waste oil or fuel, 125 psi (9 bar)	XD 30
126379	1 in x 50 ft (25 mm x 15 m) hose for waste oil, 250 psi (17 bar)	XD 40, XD 60
126380	1 1/4 in x 35 ft (32 mm x 10.5 m) hose for waste oil, 200 psi (13.8 bar)	XD 50
126688	1 1/4 in x 50 ft (32 mm x 15 m) hose for waste oil, 200 psi (13.8 bar)	XD 50
127173	1 1/2 in x 50 ft (38 mm x 15 m) hose for waste oil, 200 psi (13.8 bar)	XD 50

#### **Diesel Fuel Hoses**



	Part Number	Description	Compatible Reel Series
	16A686	1 in x 30 ft (25 mm x 9 m) hose for waste oil or fuel, 125 psi (9 bar)	XD 30
	24R102	1 in x 50 ft (25 mm x 15 m) hose for diesel fuel, 250 psi (17 bar)	XD 40, XD 60
	24R103	1 in x 75 ft (25 mm x 23 m) hose for diesel fuel, 250 psi (17 bar)	XD 50
	24R106	1 in x 100 ft (25 mm x 30 m) hose for diesel fuel, 250 psi (17 bar)	XD 50, XD 70
	24T252	1 in x 150 ft (25 mm x 46 m) hose for diesel fuel, 250 psi (17 bar)	XD 80
,	24R108	1 1/4 in x 35 ft (32 mm x 10.5 m) hose for diesel fuel, 250 psi (17 bar)	XD 50
	24R110	1 1/4 in x 50 ft (32 mm x 15 m) hose for diesel fuel, 250 psi (17 bar)	XD 50
	24R114	1 1/2 in x 50 ft (38 mm x 15 m) hose for diesel fuel, 150 psi (11 bar)	XD 50
	24T253	1 1/2 in x 100 ft (38 mm x 30 m) hose for diesel fuel, 150 psi (11 bar)	XD 80
	127167	2 in x 33 ft (51 mm x 10 m) hose for diesel fuel, 150 psi (11 bar)	XD 80
	24T254	2 in x 50 ft (51 mm x 15 m) hose for diesel fuel, 150 psi (11 bar)	XD 80

#### **Diesel Exhaust Fluid (DEF) Hoses**




Part Number	Description	Compatible Reel Series
125242	3/4 in x 50 ft (19 mm x 15 m) hose for DEF fluid, 50 psi (3 bar)	XD 30

#### **Pressure Wash Hoses**



Part Number	Description	Compatible Reel Series
16A688	3/8 in x 75 ft (10 mm x 23m) hose for pressure wash, 4,000 psi (276 bar)	XD 30
126075	1/2 in x 50 ft (13 mm x 15 m) hose for pressure wash, 4,500 psi (310 bar)	XD 30

Notes	



	Pag€
Oil King <sup>™</sup>	260
Coolant King <sup>™</sup>	261
Oil Ace <sup>™</sup>	. 262-264
16-Gallon Mobile Receiver	265
Big Hauler <sup>™</sup> Truck Drain	266
Track Receivers	266
Diaphragm Evacuation Pumps	267
Evacuation Pump Packages	. 268-270
Fluid Reclaim Accessories	. 271-273

() GRACO



#### **Convenient Used-Oil Receiver**

Oil King is designed with the busy shop in mind. With oversized tires and push-pull handles it allows for smooth maneuvering. The large funnel can collect fluids from both a drain plug and a filter port at the same time.



#### Large Offset Collection Pan

This funnel can be raised to a maximum height of 72 in (183 cm) and is equipped with a filter screen to prevent debris from entering the tank.

#### Filter Drain Tray

Used filters are able to drain separately from the collection pan.

#### Convenient Tool Tray

Built-in holding bins for new or used filters, wrenches and rags all at your fingertips.

#### Liquid Sight Gauge

A full-length liquid level sight gauge lets you know when the tank is full.

#### Large 25-Gallon (94.6 I) Capacity Receiver

Made from a heavy-duty, durable UV stabilized polymer. Dent-, rust- and corrosion-resistant.

#### **Oversized Tires**

Easily maneuver over hose and rough floors.

#### Two Evacuation Port Options

Choose from the gravity drain valve at the bottom or suction evacuation at the top.

#### **Typical Applications**

- Automotive dealerships
- · Fast lube centers
- · Service shops
- · Heavy-duty dealerships
- · Fleet services facilities

#### Typical Fluids Handled

Used oil

echnical Specifications		
Fluid	Used Oil	
Fluid Capacity	25 gal (95 l)	
Evacuation	Bottom — Gravity / Top — Suction	
Receiver Material	Polyethylene	
Length	24 in (60 cm)	
Width	24 in (60 cm)	
Height	45 to 72 in (1.1 to 1.8 m)	
Funnel Size	22 x 24 in (50 x 56 cm)	
Dry Weight	54 lb	
Instruction Manual	308667	

#### **Ordering Information**

Part Number	Description
238866	25 gal (95 l) used-oil receiver with used-filter tray, tool holders and sight gauge. Must use wall mount package (224873) for topside evacuation.

Must ship via truck.







# **5 Year** *Warranty!*

#### **Durable Receiver**

Coolant King is designed with the busy shop in mind.
With oversized tires and push-pull handles it allows
for smooth maneuvering. The full-length sight gauge
lets you know when the tank is full.

#### Large Offset Collection Pan

This funnel can be raised to a maximum height of 72 in (183 cm) and is equipped with a filter screen to prevent debris from entering the tank.

#### Convenient Tool Tray

Built-in holding bins for shop tools at your fingertips.

#### Liquid Sight Gauge

A full-length liquid-level sight gauge lets you know when the tank is full.

#### Large 25-Gallon (94.6 I) Capacity Receiver

Made from a heavy-duty, durable UV stabilized polymer. Dent-, rustand corrosion-resistant. Color specific for easy fluid identification.

#### **Oversized Tires**

Easily maneuver over hose and rough floors.

#### Two Evacuation Port Options

Choose from the gravity drain valve at the bottom or suction-evacuation at the top.

#### **Typical Applications**

- Automotive dealerships
- · Fast lube centers
- Service shops
- Heavy-duty dealerships
- Fleet services facilities

#### Typical Fluids Handled

· Used anti-freeze

echnical Specifications		
	Fluid	Anti-freeze
	Fluid Capacity	25 gal (95 l)
	Evacuation	Bottom – Gravity / Top – Suction
	Receiver Material	Polyethylene
	Length	24 in (60 cm)
	Width	24 in (60 cm)
	Height	45 to 72 in (1.1 to 1.8 m)
	Funnel Size	22 x 24 in (50 x 56 cm)
	Dry Weight	54 lb
	Instruction Manual	308667

#### >>> Ordering Information

Part Number	Description
248632	25 gal (95 l) used-anti-freeze receiver with used-filter tray, tool holders and sight gauge. Must use wall mount package (224873) for topside evacuation.

Must ship via truck.



#### **Pressurized Oil Drain**

Drain, evacuate and transfer used oil reliably, quickly and in the most cost-effective manner.



#### Large Offset Collection Pan

23 inch (58 cm) diameter offset collection bowl gives you a 31 inch (79 cm) total reach.

#### Superior Maneuverability

Wider and thicker handle for comfort.

#### Easy to Drain

Pressurize using shop air for easy oil evacuation.

#### Large 24-Gallon (90 I) Capacity Receiver

Perfect for small to large shops without an evacuation system.

#### Liquid Sight Gauge

Easy-to-read tank-level gauge lets you know when the tank is full.

#### Large Casters

Easily move around rough shop floors.

#### **Typical Applications**

- Automotive dealerships
- · Fast lube centers
- · Service shops
- · Heavy-duty dealerships
- · Fleet services facilities

#### Typical Fluids Handled

Used oil

echnical Specifications		
	Fluid	Used oil
	Fluid Capacity	24 gal (91 l)
	Evacuation	Pressurized
	Receiver Material	Steel
	Length	24 in (60 cm)
	Width	16 in (40.6 cm)
	Height	56 to 80 in (143.5 to 203 cm)
	Funnel Size	24 in (61 cm) diameter
	Dry Weight	74 lb
	Instruction Manual	310864

#### **Ordering Information**

Part Number	Description
119577	24 gal (90 l) steel-tank pressurized oil drain



#### Vacuum-Assisted Oil Collection System

Large-capacity collection systems make removing drain plugs a thing of the past. Oil Ace models with optional sight chamber offer the technician a visual indication of the waste fluid quantity. This technology reduces the threat of costly damages caused by over- or under-torquing or cross-threading drain plugs.

#### Large Offset Collection Pan

Wide offset collection bowl prevents splashing.

#### Vacuum Gauge

Ensure peak performance with easy-to-read vacuum gauge.

#### Sight Glass

Inspect oil quality via large, clear evacuation chamber and verify amount extracted.



#### Easy to Drain

Pressurize using shop air for easy oil evacuation.

#### Vacuum Probes

Variety of flexible suction attachments and adapters included.

#### Large 24 Gallon (90 I) Capacity Receiver

Perfect for small to large shops without an evacuation system.

#### Typical Applications

- Automotive dealerships
- Fast lube centers
- Service shops
- · Heavy-duty dealerships
- · Fleet services facilities

#### Typical Fluids Handled

Used oil

Fluid	Used oil
Tank Capacity	24 gallon (90 l)
Evacuation	Pressurized
Receiver Material	Steel
Length	24 in (61 cm)
Width	16 in (40.6 cm)
Height	39 to 70.8 in (99 to 180 cm)
Funnel Size	23.8 in (60 cm)
Dry Weight	50.7 to 73.2 lbs (23 to 33.2 kg)
nstruction Manual	310864



Part Number	Description
26C061	24 gal (90 I) steel tank with suction probes and adapters
26C062	24 gal (90 l) steel tank with suction probes, adapters and sight glass
26C063	24 gal (90 l) steel tank with suction probes, adapters and oil drain funnel
26C064	24 gal (90 l) steel tank with suction probes, adapters, sight glass and oil drain funnel





#### **Typical Applications**

- Automotive dealerships
- · Heavy-duty dealerships
- Fast lube centers
- · Fleet services facilities
- Service shops

#### Typical Fluids Handled

• Used oil

Technical Specifications		
Fluid	Used oil	
Fluid Capacity	16 gal (61 l)	
Evacuation	Gravity	
Receiver Material	Steel (239302 does not include drum)	
Manual	306449	
Length	26 in (66 cm)	
Width	23 in (58 cm)	
Height	42 to 70 in (107 to 177 cm)	
Funnel Size	23 x 23 in (58 x 58 cm)	
Dry Weight	40 lb (18 kg)	

#### >>> Ordering Information

Part Number	Description
239301*	16 gal (60 l) Oil receiver with steel drum oil receiver
239302	16 gal (60 l) Oil receiver without drum

 $<sup>^*</sup>$ Use with evacuation kit 224873 or 24E166. 240832 can be ordered separately for existing diaphragm pump evacuation systems.

#### **Accessories**

#### **Funnel Kit**

Part Number	Description
243650	Use with 238866, 239301, 239302 and 248632. Includes tray and pipe.

#### **Wall-Mounted Funnel Drain**

Part Number	Description
154616	Use with Pedestal Receiver 225272 to open automatic check-valve and drain used oil through wall to waste tank. Drain has 1-1/4 NPT(F) outlet.

#### **Drum-Mounted Funnel Drain**

Part Number	Description
156789	Use with Pedestal Receiver 225272 to open automatic check-valve and drain used oil into standard drum. Funnel drain has 2 in NPT bung fitting for use with 55 gal (210 l) or 16 gal (60 l) drums or 275 gallon (1,100 l) tanks.

#### **ATF Drain Funnel**

Part Number	Description	
208009	Use with Pedestal Receiver 225272 to extend funnel reach. Use for draining transmissions. Not equipped with drain plug. 16 in x 24-1/2 in.	





#### **Typical Applications**

- Truck maintenance facility
- · Heavy-duty dealerships
- · Fleet services facilities

#### Typical Fluids Handled

Used oil

echnical Specifications  Fluid Used o	il
1.0.0	···
Fluid Capacity 26 gal	(98.4 I)
Evacuation Gravity	(00.11)
Receiver Material Steel	
Length 42 in (	106.7 cm)
,	76.2 cm)
Height 9 to 11	in (22.9 to 27.9 cm)
Instruction Manual 30919	

#### Ordering Information

Part Number	Description
244055*	Big Hauler truck drain specially designed for truck maintenance facilities

\*Use with evacuation kit 224873 or 24E166. 240832 can be ordered separately for existing

## **Track Receivers**





#### **Typical Applications**

- · Fast lube centers
- Fleet services facilities

#### Typical Fluids Handled

Used oil

Technical Specifications					
	Part Number	218969	235346		
	Fluid	Oil	Oil		
	Fluid Capacity	30 gal (113 l)	27 gal (102 l)		
	Evacuation	Gravity	Gravity		
	Receiver Material	Steel	Steel		
	Extension Range	37.5 to 46 in (0.95 to 1.17 m)	34.1 to 42.6 in (0.87 to 1.08 m)		
	Instruction Manual	307727	307727		

#### Ordering Information

Part Number	Description
218969	Specially designed for car and truck fast lube facilities where speed and mobility are important. Adjustable steel rollers fit track widths.
235346	Narrow rolling used-oil receiver, specially designed for car and truck fast lube facilities where speed and mobility are important. Adjustable steel rollers fit track widths. Same as 218969 except track width range.



#### Typical Applications

- Automotive dealerships
- Fast lube centers
- Service shops
- Heavy-duty dealerships
- Fleet services facilities

#### Typical Fluids Handled

• Used oil



313597



echnical Specifications			
	Husky 716	Husky 1050	
Maximum Fluid Working Pressure	100 psi (7.0 bar / 0.7 MPa)	100 psi (7.0 bar / 0.7 MPa)	
Approximate Free Flow Rate @ 100 psi	16 gal/min (61 l/min)	50 gal/min (189 l/min)	
Output per Cycle	0.04 gal (0.15 l)	0.17 gal (0.64 l)	
Air Inlet	1/4 in	1/2 in	
Fluid Inlet	3/4 in	1 in	
Fluid Outlet	3/4 in	1 in	
Maximum Pump Speed	400 cpm	275 cpm	
Cycles per Gallon	25 cpg	5.9 cpg	
Cycles per Liter	6.7 cpl	1.6 cpl	
Wetted Parts	Buna-N, acetal, aluminum, stainless steel, PTFE, zinc-plated steel	Aluminum, TPC-ET, acetal, PTFE, Buna-N	
Sound Pressure Level	85 dB(A)	96 dB(A)	
Sound Power Level	95 dB(A)	90 dB(A)	
Approximate Weight	8.5 lb (3.9 kg)	23 lb (10.5 kg)	

308573

### Ordering Information

Instruction Manual


Part Number	Description
241906	Husky 716 Evacuation Pump
647731	Husky 1050 Evacuation Pump



#### **Wall Mount Packages**



Package Number	24E166	25T815	224873
Diaphragm Pump 1050A (1 in) UL-listed		1050A (1 in) UL-listed	716 (3/4 in)
Pump Part Number	647731	647016	241906
Mounting Type	Wall Bracket	Wall Bracket	Wall Bracket
Mounting Part Number 24C637		24C637	224835
Fluid Oil		Anti-freeze	Oil
Evacuation	Drum Adapter	Drum Adapter	Drum Adapter
Evacuation Part Number	240832	240832	240832
Air Installation Kit	240684	240684	240684
Fluid Installation Kit 240685		240685	240685
Instruction Manual 313597		313597	308719
Listings UL, CE		UL, CE	-



268



#### **Base Pump Packages**

System evacuates lube from differential case using suction generated by a diaphragm pump. Nylon tubes ranging in size from 3/16 in OD to 1/2 in OD are included to fit through sight plug to completely drain the case. Evacuated gear lube is then pumped to waste tank. Piping and waste tank not included. Systems are fully groundable and bondable for safe transfer of used oil.






## **Fas-Vac Mobile Packages**



Package Number 224700		224701
Cart	224665	111470
Compatible Drum Size (Not included)	16 gal (60 l)	55 gal (200 l)
Pump	716 (3/4 in)	716 (3/4 in)
Pump Package	224667	224667
Fluid	Oil, Gear Lube	Oil, Gear Lube
Evacuation Kit	224669 / 224666	224702 / 224666
4-Way Valve	187359	187359
Port Size	1/2 NPT(F)	1/2 NPT(F)
Instruction Manual	308154	308154
Must be ordered separately (Not Included)		Included)
Filter Regulator Lubricator (FRL)	110149	110149
FRL Mounting Kit	224759	224759



Package 224701 installed on oil drum (Drum and filter regulator not included in package)



#### **4-Way Evacuation Valve**


Directional control valve used to simplify the filling and emptying of tanks




#### **Features and Benefits**

- Simplifies installation by eliminating need for multiple valves
- Unrestricted flow no pressure or volume loss
- · Two-position tank fill and emptying control
- Tapered, self-seating valve spool for superior sealing performance

Part Number	Description
120581	1 in NPT(F) 4-Way Evacuation Valve
120601	1-1/2 in NPT(F) 4-Way Evacuation Valve



Lube Truck/Bulk Waste Tank



#### **Air Regulators**

Provides precision control of outlet air pressure. Feedback principle provides constant pressure to pump regardless of air demand rate and fluctuations in supply pressure. Additional fittings required (except air regulators with installation kits).

	Part Number	Description
	110318	1/4 NPT(FBE)
	110147	1/4 NPT(FBE) with gauge
	110234	3/8 NPT(FBE)
Engl.	109075	3/8 NPT(FBE) with gauge
	202858	3/8 NPT(M) x 1/2 NPSM(F) with gauge
The f	104266	1/2 NPT(FBE)
1	244844	1/2 NPT(FBE) with gauge
*	207755	3/4 NPT(FBE)
å.	244845	3/4 NPT(FBE) with gauge

## **Fluid Reclaim Accessories**



>>> Ordering Information

#### **Air Filters and Drains**

Centrifugal action 1/4, 3/8 and 1/2 NPT (with 20 micron filters); 3/4 NPT having 40 micron filters to remove water and foreign particles from air supply.

	Part Number	Description
	110146	1/4 NPT(FBE) Air Filter. Manual drain.
Ŧ	106148	3/8 NPT(FBE) Air Filter. Auto-drain.
Ŧ	106149	1/2 NPT(FBE) Air Filter. Manual drain.
Ţ	106150	3/4 NPT(FBE) Air Filter. Manual drain.
	106151	Automatic filter drain float-type, 1/4 NPT(M). Use with 106150, 112859 and 217074.
	127711	Automatic filter drain float-type. Use with 106148 and 106149. Sold in NA only.

#### **Installation Kits**

Installation kits include shut-off valve, regulators, gauges and fittings as necessary for normal installation.

Part Number	Description
218316	Installation kits for Fast-Flo, Fire-Ball or Husky 307, and 716 diaphragm pumps
224512	Installation kits for Mini Fire-Ball 225 and Fire-Ball

272



#### Accessories Ordering Information

#### **Additional Accessories**

	Part Number	Description
0	221146	10 ft (3.04 m) suction hose and quick coupler with four interchangeable 15 in (38.1 cm) suction wands. OD options: 3/16 in, 1/4 in, 3/8 in, 1/2 in. For use with Husky 716 or 1050 gear oil evacuation systems.
6866	223696	Four interchangeable 15 in (38.1 cm) suction wands. OD options: 3/16 in, 1/4 in, 3/8 in, 1/2 in. For use with part 223695 evacuation pump.
	224702	32 in suction wand. 1/2 in OD.
	224762	48 in (121.9 cm) suction wand kit with four interchangeable wands. OD options: 3/16 in, 1/4 in, 3/8 in, 1/2 in.
<b>†</b>	224666	36 in suction wand storage kit
III () 100	218970	Tandem drain kit connects two rolling receivers for flow-through draining operation. Kit includes connector hose, shut-off valve, pipe nipple and quick-connect nipple. Instruction manual 307727.
	108491	Drain hose kit allows rolling used-oil receiver to be drained directly into the used-oil line.  Kit is 24 in (0.6 m) in length with camlock coupler on one end.
800	221007	Swing-Arm Drain Kit, used for servicing single rolling used-oil receiver (218969). When used with tandem drain kit (218970) it can service two receivers on a single track. Kit includes swivel elbow (108867), connector hose, dust cap (108203) and male adapter (108202).
	116229	Oil Tank Monitor. Shuts off air to the pump when tank is full.
Q.	223888	6 ft (1.8 m) suction hose for ATF and anti-freeze. Includes filter screen. Use with 223695.
	222011	Grounding clamp for all used-oil handling systems. Includes 25 ft (7.6 m) grounding wire.
	187359	4-way valve 1/2 NPT(F) ports

Notes	



Pa	ıge
Air Regulators and Valves	76
Air Valves	77
Hose Fittings	78
Lubrication Hoses	79
Air/Water Hoses	80
Quick Connect Fittings	8
Adapters and Fittings282-2	83

SORIES

AIR ACCESS

184 66 300 PSI 21 MAX WPF





#### **FRL Combination Units**

Each includes filter, regulator, pressure gauge, lubricator and connection fittings.

	Part Number	Inlet
	110149	1/4 in NPT(FBE)
	110150	3/8 in NPT(FBE)
	217072	1/2 in NPT(FBE)
	217073	3/4 in NPT(FBE)

#### **Bleed-Type Air Shut-Off Valves**

Closes air inlet to pump and relieves trapped air pressure down line from valve. Recommended for each pump drop line. Note: Be certain to install correctly. If installed backwards air will constantly escape from the valve. Maximum pressure of 250 psi (17 bar).

	Thread	1/4 in	3/8 in	1/2 in	3/4 in
	NPT(FBE)	110223	110224	110225	110226
	NPT(MXF) inlet x outlet	-	-	107142	107141

#### **Ball Valve-Type Air Shut-Off Valve – Non-Pressure Relieving**

	Part Number	Inlet	Maximum Working Pressure
	208390	1/4 in NPT(MBE)	500 psi
	208393	3/8 in NPT(MBE)	500 psi
	208630	1/2 in NPT(M) x 3/8 in NPT(F)	500 psi
	109077	3/4 in NPT(FBE)	600 psi
	118464	1 NPT(FBE)	600 psi

276



#### **Air Needle Valve**

Controls pump speed by restricting air flow to pump or other air-operated equipment.

	Part Number	Inlet	Outlet
3 0	205090	1/4 in NPSM(M)	1/4 in NPSM(F)
382	206264	1/4 in NPT(M)	1/8 in NPT(F)

#### **Air Pressure Relief Valve**

Prevents pump from operating beyond recommended working pressure by opening at a pre-set maximum air pressure.

alle-	Part Number	Maximum Pressure Rating	Thread
	110065	60 psi (4 bar)	1/4 in NPT(M)
	103347	100 psi (6.9 bar)	1/4 in NPT(M)

#### **Air Pressure Gauge**

Allows visual check of air pressure being supplied to the pump. Rated to 200 psi (14 bar)

	Part Number	Inlet	Color
	110319	1/8 in NPT(M)	Black
	100960	1/4 in NPT(M)	Black
	101180	1/4 in NPT(M)	Chrome

#### **Air Manifold**

Supply several pumps from one supply line. Larger port delivery ensures adequate air flow to all pumps.

	Part Number	Inlet Ports	Inlet Thread	Outlet Thread	Maximum Pressure Rating
1000	158990	2	1/2 in NPT(F)	3/8 in NPT(F)	5,000 psi

#### **Runaway Valve**

Prevents pump damage by automatically closing the air line to stop the pump when a runaway pump condition occurs due to an empty barrel or hose leak.

- 5	Part Number	Inlet
12000	224040	3/4 in NPT(FBE)





#### **Blow Guns**

Safety Blow Gun tip swivels freely and cannot be removed. Tip pressure will not exceed 30 psi (2 bar), adequate for cleaning. Maximum working pressure 150 psi (10 bar). Use with coupler 208536.

Part Number	Description	Inlet
236211	Air blow gun	1/4 in NPT(F)

#### **Tire Inflators**

	Doub Number	Description		Incl	udes		
	Part Number	Description					
	236205	Heavy-Duty Tire-Inflator	Yes	Yes	-	Yes	
Light Street	236206	Passenger Car Tire Inflator	Yes	-	Yes	Yes	
97)	218545	Tire Chuck with 1/4 in NPT(F) inlet	-	-	-	-	

#### **Water Valve**

Water/Anti-Freeze Bib is a durable, full-volume dispense nozzle for water, anti-freeze and windshield washer fluid. Nitrile rubber seals.

	Part Number	Inlet	Pressure Rating
19	180685	1/4 in NPT(F)	100 psi (7 bar)

278











#### **Heavy-Duty Reinforced Lubrication Hoses**

For use with grease, oil and undercoating material. Hoses are black, male connections at both ends. Lubrication hoses listed are grounded for static electrical discharge.

	ID Inch	Max PSI		Fitt	ing	
	(mm)	(bar)	Hose Length	End 1 Thread NPT(M)	End 2 Thread NPT(M)	Part Number
			12 in (0.3 m)			109145
			30 in (0.8 m)	1/8	1/8	109148
			24 in (0.8 m)	3/8	3/8	109147
			48 in (1.2 m)			109149
			72 in (1.8 m)			109150
	1/4	5,000	12 ft (3.6 m)		1/4	109151
	(6.44)	(345)	15 ft (4.6 m)			109152
			20 ft (6.1 m)	1/4	3/8	109153
			25 ft (7.6 m)		1/4	109154
			35 ft (10.6 m)			109156
			40 ft (12.2 m)		3/8	109157
			50 ft (15.3 m)			109158
			12 in (0.3 m)	1/4	1/2	109160
			24 in (0.62 m)			109161
	3/8 (9.5)		48 in (1.2 m)	3/8	3/8	109162
		4,000 (276)	72 in (1.8 m)			109163
			15 ft (4.6 m)	1/4	1/4	109165
			40 ft (12.2 m)		3/8	109169
			50 ft (15.3 m)		3/0	109170
			15 in (0.4 m)		1/2	110069
			18 in (0.5 m)			220598
			54 in (1.4 m)			220600
			72 in (1.8 m)			220591
	1.0	0.000	10 ft (3.1 m)			220590
	1/2 (12.7)	3,000 (207)	16 ft (4.9 m)	1/2	1/2	220592
			20 ft (6.1 m)			220593
			25 ft (7.6 m)			220608
			40 ft (12.2 m)			221092
			50 ft (15.3 m)			221093
			75 ft (22.9 m)		3/4	237861
			18 in (0.4 m)			109108
	3/4	2 250	72 in (1.8 m)	3/4	3/4	109105
	(19.1)	2,250 (155)	10 ft (3.0 m)			111010
			75 ft (22.9 m)	1/2	1	237865
			50 ft (15.2 m)	.,_	·	237866
	1 (25.4)	212 (14.6)	50 ft (15.2 m)	1	1	241908
	1 (25.4)	125 (8.7)	50 ft (15.2 m)	1	1	249058





#### **Air/Water Hoses**

For use with low pressure air and water. Hoses are male NPT at both ends.

	ID Inch	Max PSI	llogo l ongth	Fit	ting	Part Number
	(mm)	(bar)	Hose Length	End 1 Thread NPT(M)	End 2 Thread NPT(M)	Fait Nullibei
			18 in (0.5 m)			109123
			4 ft (1.2 m)		1/4	109124
	Fabric-Reinforced		6 ft (1.8 m)	1/4	1/4	109125
	1/4	180 (12.4)	10 ft (3.1 m)	1/4		109126
	(6.44)	(1211)	25 ft (7.6 m)		1/2	109127
			40 ft (12.2 m)		1/2	109128
			40 ft (12.2 m)	3/8	1/4	218491
			18 in (0.5 m)		204560	
			4 ft (1.2 m)	3/8	3/8	109130
			6 ft (1.8 m)	3/6		203320
	3/8 (9.5)	180 (12.4)	10 ft (3.1 m)			109131
			16 ft (4.9 m)	1/4	3/8	110326
			25 ft (7.6 m)	3/8	1/2	109132
			40 ft (12.2 m)			109134
			60 ft (18.3 m)			109135
			22 in (0.56 m)		1/2	218093
	1/2	180	4 ft (1.2 m)	1/2		110046
	(12.7)	(12.4)	6 ft (1.8 m)	1/2		205418
			10 ft (3.1 m)			214656
	1/2	300	25 ft (7.6 m)	1/2	1/0	248312
	(12.7)	(20.7)	50 ft (15.2 m)	1/2	1/2	248313
			18 in (0.5 m)			110047
			4 ft (1.2 m)			110048
	3/4 (19.1)	180 (12.4)	6 ft (1.8 m)	3/4	3/4	208610
	(,	( · · /	10 ft (3.1 m)			214955
			25 ft (7.6 m)			208611



#### **Quick-Connect Coupler**

Permits quick, convenient attachment of air supply hoses.



Part Number	Inlet	Body Size
208536	1/4 in NPT(F)	1/4 in
110198	3/8 in NPT(F)	1/4 in
110199	1/2 in NPT(F)	3/8 in
110200	3/4 in NPT(F)	1/2 in

#### **Quick-Connect Nipple**

Allows quick attachment of air supply hoses to pump motor.



Part Number	Inlet	Body Size	
169967	1/4 in NPT(F)	1/4 in	
169970	1/4 in NPT(M)	1/4 in	
169971	3/8 in NPT(M)	1/4 in	
110196	1/2 in NPT(M)	3/8 in	
110197	3/4 in NPT(M)	1/2 in	













## **Bushings and Pipe Adapters – Reducing, Standard and Expanding**



Outlet	Inlet						
Outlet	1/8 in NPT	1/4 in NPT	3/8 in NPT	1/2 in NPT	3/4 in NPT	1 in NPT	
1/8 in NPT	150171	159840	156580	-	-	-	
1/4 in NPT	100030	-	150287	159842	-	-	
3/8 in NPT	-	159841	150286	156022	-	-	
1/2 in NPT	-	100206	100081	-	168595	-	
3/4 in NPT	_	100615	100505	100896	_	-	
1 in NPT	-	-	-	100380	158586	-	

#### **Street Elbows**



Part Number	Inlet/Outlet
100840	1/4 in NPT
155699	3/8 in NPT
158683	1/2 in NPT
176393	3/4 in NPT

#### **Coupling – Standard**



Part Number	Inlet
100451	1/8 in NPT
113093	1/4 in NPT
162024	3/8 in NPT
158581	1/2 in NPT
100385	3/4 in NPT
100474	1 in NPT

## **Hex Nipples – Standard and Reducing**



Male End 2	Male End 1							
IVIAIC LIIU Z	1/4 in NPT	3/8 in NPT	1/2 in NPT	3/4 in NPT	1 in NPT			
1/8 in NPT	151519	156296	159239	_	-			
1/4 in NPT	156971	165198	162449	-	_			
3/8 in NPT	-	156849	-	194048	-			
1/2 in NPT	-	-	158491	157191	-			
3/4 in NPT	-	-	-	175013	158555			












#### **Square Head Plug**



#### **Swivel Adapters\***











Rigid End	Swivel End	Straight Swivel Adapter (m x f)	Straight Swivel Adapter (f x f)	90° Swivel Adapter (f x f)	90° Swivel (m x f)	45° Swivel Adapter (m x f)
1/8 in	1/4 in	208434	-	-	-	-
1/4 in	1/4 in	156823	155570	157676	155541	-
1/4   1	3/8 in	157705	-	-	-	-
	1/4 in	-	159153	-	155495	-
3/8 in	3/8 in	155665	156173	155677	155494	161889
	1/2 in	162505	-	159801	217430	-
	1/4 in	-	155653	-	-	-
1/2 in	3/8 in	158256-257	161077	-	161037	-
	1/2 in	156684	155865	157416	155470	-
3/4 in	3/4 in	157785	156172	156589	160327	105281
1 in	3/4 in	202965	-	-	-	-
1 in	1 in	160022	158383	-	-	-

<sup>\*</sup>Not a "live" swivel, position is stationary after tightened.

#### Tube Fittings

Maximum pressure rating of 3000 psi (207 bar) with appropriate tubing wall thickness.

	Description	lulat	Tube OD			
	Description	Inlet	5/8 in	7/8 in		
	Tube Union Flow 90° Elbow	=	101012	101376		
1 13	Straight Tube Union	_	101009	101340		
	Male Connector	3/4 in NPT	-	101339		
	Straight Female Connector	1/2 in NPT	101008	-		
C 1	Tube Tee with Female Branch	5/8 in NPT	101013	-		

## **Standard Graco Warranty**

#### 1-Year Warranty Policy

Graco warrants all equipment manufactured by Graco and bearing its name to be free from defects in material and workmanship on the date of sale by an authorized Graco distributor to the original purchaser for use. With the exception of any special, extended or limited warranty published by Graco, Graco will, for a period of twelve (12) months from the date of sale, repair or replace any part of the equipment determined by Graco to be defective.

This warranty applies only when the equipment is installed, operated and maintained in accordance with Graco's written recommendations. This warranty does not cover, and Graco shall not be liable for, general wear and tear, or any malfunction, damage or wear caused by faulty installation, misapplication, abrasion, corrosion, inadequate or improper maintenance, negligence, accident, tampering or substitution of non-Graco component parts. Nor shall Graco be liable for malfunction, damage or wear caused by the incompatibility of Graco equipment with structures, accessories, equipment or materials not supplied by Graco, or the improper design, manufacture, installation, operation or maintenance of structures, accessories, equipment or materials not supplied by Graco.

This warranty is conditioned upon the prepaid return of the equipment claimed to be defective to an authorized Graco distributor for verification of the claimed defect. If the claimed defect is verified, Graco will repair or replace free of charge any defective parts. The equipment will be returned to the original purchaser, transportation prepaid. If inspection of the equipment does not disclose any defect in material or workmanship, repairs will be made at a reasonable charge, which may include the costs of parts, labor and transportation.

THIS WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Graco's sole obligation and buyer's sole remedy for any breach of warranty shall be as set forth above. The buyer agrees that no other remedy (including but not limited to incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available. Any action for breach of warranty must be brought within two (2) years of the date of sale.

Graco makes no warranty, and disclaims all implied warranties of merchantability and fitness for a particular purpose in connection with accessories, equipment, materials or components sold but not manufactured by Graco. These items sold but not manufactured by Graco (such as electric motors, switches, hoses, etc.) are subject to the warranty, if any, of their manufacturer. Graco will provide purchaser with reasonable assistance in making any claim for breach of these warranties.

In no event will Graco be liable for indirect, incidental, special or consequential damages resulting from Graco supplying equipment hereunder, or the furnishing, performance or use of any products or other goods sold hereto, whether due to a breach of contract, breach of warranty, the negligence of Graco or otherwise.

# Graco Vehicle Service Equipment Group Extended Warranty

Graco warrants all equipment referenced in this document that is manufactured by Graco and bearing its name to be free from defects in material and workmanship on the date of sale to the distributor. Graco will, for a period as defined in the table on the opposite page from the date of sale, repair or replace equipment covered by this warranty and determined by Graco to be defective. This warranty applies only when the equipment is installed, operated and maintained in accordance with Graco's written recommendations.

This warranty does not cover, and Graco shall not be liable for, general wear and tear, or any malfunction, damage or wear caused by faulty installation, misapplication, abrasion, corrosion, inadequate or improper maintenance, negligence, accident, tampering or substitution of non-Graco component parts. Nor shall Graco be liable for malfunction, damage or wear caused by the incompatibility of Graco equipment with structures, accessories, equipment or materials not supplied by Graco, or the improper design, manufacture, installation, operation or maintenance of structures, accessories, equipment or materials not supplied by Graco.

This warranty is conditioned upon the prepaid return of the equipment claimed to be defective to an authorized Graco distributor for verification of the claimed defect. If the claimed defect is verified, Graco will repair or replace free of charge any defective parts. The equipment will be returned to the original purchaser, transportation prepaid. If inspection of the equipment does not disclose any defect in material or workmanship, repairs will be made at a reasonable charge, which may include the costs of parts, labor and transportation.

THIS WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Graco's sole obligation and buyer's sole remedy for any breach of warranty shall be as set forth above. The buyer agrees that no other remedy (including but not limited to incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available. Any action for breach of warranty must be brought within one (1) year post the warranty period.

GRACO MAKES NO WARRANTY, AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, IN CONNECTION WITH ANY ACCESSORIES, EQUIPMENT, MATERIALS OR COMPONENTS SOLD BUT NOT MANUFACTURED BY GRACO.

These items sold but not manufactured by Graco (such as electric motors, switches, etc.) are subject to the warranty, if any, of their manufacturer. Graco will provide purchaser with reasonable assistance in making any claim for breach of these warranties.

In no event will Graco be liable for indirect, incidental, special or consequential damages resulting from Graco supplying equipment hereunder, or the furnishing, performance or use of any products or other goods sold hereto, whether due to a breach of contract, breach of warranty, the negligence of Graco or otherwise.

#### FOR GRACO CANADA CUSTOMERS

The parties acknowledge that they have required that the present document, as well as all documents, notices and legal proceedings entered into, given or instituted pursuant hereto or relating directly or indirectly hereto, be drawn up in English.

Les parties reconnaissent avoir convenu que la rédaction du présente document sera en Anglais, ainsi que tous documents, avis et procédures judiciaries exécutés, donnés ou intentés à la suite de ou en rapport, directement ou indirectement, avec les procedures concernées.

# Graco Vehicle Service Equipment Group Extended Warranty (cont.)

		Warranty Period
	Oil King, Coolant King, and Oil Ace	5 Years
	Pulse Fluid Management Hubs, TLMs, PACs and Extenders	2 Years
	Cord and Light Reels	2 Years
	Electrical Components	1 Year
	LD Series Hose Reels	5 Years
	Wear Parts, including but not limited to hose, seals, swivel seats and roller guides	1 Year
REELS	SD Series Hose Reels	7 Years
æ	Power Springs	3 Years
	Wear Parts, including but not limited to hose, seals, swivel seats and roller guides	1 Year
	XD Series Hose Reels	7 Years
	Power Springs	3 Years
	Wear Parts, including but not limited to hose, seals, swivel seats, roller guides and motors	1 Year
	Mechanical Meters	5 years
	Wear parts, including but not limited to o-rings, seals and valves	1 Year
	LD Preset Meters	5 years
	Electronics	2 Years
SS.	Wear parts, including but not limited to o-rings, seals and valves	1 Year
METERS	SD Meters and Valves	5 Years
2	Electronics	3 Years
	Wear parts, including but not limited to o-rings, seals and valves	1 Year
	EM Meters and Valves / Pulse Meters and Valves	5 Years
	Electronics	3 Years
	Wear parts, including but not limited to o-rings, seals, valves and trigger locks	1 Year
	LD Oil/Grease Pumps	5 Years
	Wear Parts, including but not limited to o-rings, packings and seals	1 Year
	Hoses with pump packages	1 Year
	AODD Pumps	5 Years
	Wear Parts, including but not limited to o-rings, packings and seals	1 Year
	Hoses with pump packages	1 Year
PUMPS	Mini Fire-Ball 225 and Fire-Ball 300 Oil and Grease Pumps	7 Years
<u>-</u>	Wear Parts, including but not limited to o-rings, packings and seals	1 Year
	Hoses with pump packages	1 Year
	Fire-Ball 425 Oil and Grease Pumps	10 Years
	Wear Parts, including but not limited to o-rings, packings and seals	1 Year
	Hoses with pump packages	1 Year
	Fast-Ball and Fast-Flo Oil Pumps	5 Years
	LD Blue and SD Blue Diesel Exhaust Fluid Pumps	2 Years

Pago	Part No.	Page No.	Part No.	Page No.	art No.
	24F774	215, 216	240537	49, 65	50502
		37. 44. 215. 216			
		215, 216		15, 25, 93	
		192, 194, 268		15, 25, 93	
		37, 44, 215			
		232, 237			
167		232, 237		15, 25, 93	
107		192			
		193		257	
113, 114, 116, 120, 125, 126		71		256	
		71		257	
46, 112		75		257	
46, 113, 114		75	24D593	256	
46, 114	24F906	71	24D594	138	6F769
34, 4	24F910	75	24D595	138	6F781
	24F914	71	24D596	138	6F784
19, 25, 32, 39, 46, 114	24F915	71	24D597		SF878
31, 4		75			
35, 4:		75			
35, 36, 42, 4		71		170	
35, 4		75		227	
35, 4		71		227	
34, 4		71		50	
		75		178, 179	
19, 25, 31, 33, 34, 35, 3		75	24D605	178, 179	'C908
3		71	24D606	18	'F878
31, 3		71	24D607	18	
3	24G585	75	24D608		'R220
31, 40, 41, 42, 43, 4			24D989	15, 25, 87, 90, 93, 223, 233, 238, 244, 256	
3			24D990	15, 25, 87, 90, 93, 223, 233, 238, 244, 256	
			24D991	15, 25, 87, 90, 93, 223, 233, 236, 244, 256	
			24D992	15, 25, 87, 90, 93, 223, 233, 238, 244, 256	
111			24D993	15, 25, 87, 90, 93, 223, 233, 238, 244, 256	
111	24G603	221	24D994		
111	24G606	221	24D995	221, 222, 226	A217
	24G636	221	24D996	222	A218
96, 167	24G738	221	24D997	232	A219
166, 167	24G745	221	24D998	232	A220
			24D999	232	
			24E001		
			24E002		
223		145			
		145		222, 226	
168		145		222, 226	
19, 25, 34, 35, 36, 37, 38, 39, 41	24H420	145		222, 226	
43, 44, 45, 46, 112, 113, 114		145		222, 226	
113	24H422	145	24E011	222, 226	A939
	24H606	265, 266, 268	24E166	222, 226	A940
	24H655	269	24E167	222, 226	A941
	24H656	236, 237	24E283	222, 226	A942
215		236, 237		222, 226	
215		236, 237, 238			
215		146		222	
215		146			
215		146		222	
32, 35, 37, 39, 42, 44, 215		238		222	
113, 114, 215		238		222	
34, 4		51		222, 226, 233	
35, 4	24H669	51	24F206	222, 233	4951
	24H689	176	24F524	194	3624
		167, 168, 173		194	
		167		194	
		167, 168, 177			
		168, 175			
		215			
		215		231	
		215		231	
		215		231	
	24H777	215	24F741	231	2248
	24H799	215	24F742	231	2249
		215		231	
		215		231	
		215		231	
		215		231	
			24F758	231	
		215		231	
34, 4	24H859	215		231	C256
		0.45	0.45704	0.1.0	0440
112, 113, 114		215 215		216 215, 216	

		Part No.	Page No.	Part No.	Page
14868	42	24N691	226	240480	
	42	24N814			
1H892		24P164			
4H894		24P313			
4H915		24P315			
4H916		24P316			
4H917	39	24P317	242	24P495	
4H918	39	24P318	242	24P496	
4H940	39	24P319	242	24P497	
4H941	39	24P320	242	24P498	
4H942		24P322	242		
	39	24P323			
	41	24P324			
	41	24P325			
	41	24P326			
H967	41	24P327		24P984	
J030	112	24P328	242	24P985	
J036	113	24P329	242	24P986	
.1042	114	24P330	242	24P987	
	113	24P331			
	114				
		24P332			
	113	24P333			244,
J066		24P334			244,
• . •	116	24P335			244,
J495	32, 35, 36, 38, 39, 43, 45	24P336	242	24R074	
	113, 114, 116	24P337			
J733		24P338			
J734			242		
	44		242		251,
	44	24P341			251,
J776	37	24P342	242	24R108	
J777	44	24P343	242	24R110	252,
K285	36, 47	24P344	242	24R111	
	38	24P345			
	45		242		252,
	38	24P347			
	45	24P348			
K799	38	24P349	242	24R118	
K800	45	24P350	242	24R350	50, 54, 65, 119, 120, 124, 125, 126, 137,
K834	38	24P351	242	24R404	
	45	24P352			
	37	24P353			
	•				
	44	24P354			
	36	24P355			
K839	43	24P356	242	24R409	
(842	36	24P455	243	24R410	
(843	43	24P456	243	24R412	
	194		243		
K000	194		240		
	194	24P458	243		
	194		243		
K937	194	24P460	243	24R416	
M499	168	24P461	243	24R419	
N323	232	24P462	243	24R420	
	232		243		
	232		243		
	232		243		
	232		243		
	232		243		
l331	233	24P468	243	24R426	
N332	233	24P469	243	24R427	
	233		243		
	233		243		
	233		243		
	233		243		
	233		243		
	233	24P475	243		
1340	233	24P476	243	24R434	
l341	233	24P477	243	24R435	
	233		243		
	233		243		
	223, 227		243		
l674	226	24P481	243	24R439	
	226		243		
	226		243		
	226		243		
	#				
N684	226		243		
N684 N685			243 243	24R444	

Part No.	Page No.	Part No.	Page No.	Part No.	Page No.
24R447	251	24R563	252	24T333	255
24R448		24R564		24T334	
24R449		24R565		24T335	
24R450	251	24R566	252	24T336	255
24R451	251	24R567	252	24T337	255
24R452	251	24R568		24T875	254
24R453	251	24R569		24T876	
24R454	251	24R570		24T886	
24R455		24R571		24T888	
24R456		24R572		24T889	
24R457	<del></del> -	24R573		24T891	
24R458		24R574	·····	24T892	
24R459		24R575		24T910	
24R460		24R576		24T911	
24R461		24R577		24U227	
24R462		24R578		24U228	
24R463		24R854		24U947	
24R464		24R855			98
24R465		24R856			98
24R466		24R857			98
24R503		24R859			98
24R504		24R860			51, 98
24R505		24R861			98
24R506		24R862		24V040	
24R507		24R863			98
24R508		24T011			98
24R509		24T012	·····		98
24R510		24T013			99
24R511		24T014			99
24R512		24T015		24V058	
24R513		24T016			165
24R515		24T017			165
24R516		24T018			165
24R517		24T019		24V646	
24R518		24T020		24V656	
24R519		24T021		24V677	
24R520		24T022			167
24R521		24T023			168
24R522		24T024			179
24R523		24T025			179
24R524		24T104			179
24R525		24T105			179
24R526		24T106			179
24R527		24T107			179
24R528		24T108			168, 175
24R529		24T109			167, 175
24R530		24T110			168, 175
24R531		24T111			165, 167, 175
	251	24T112			168
	251	24T113			167
	251		253		175
	251		253		174, 236, 238
	251	24T116			174, 238
	251	24T117			99
	251	24T118			141
	251	24T119			141
	251		253		201
	251	24T121			99
	251		253		225
	251	24T123			225
	251	24T124			225
	251		253		225
	251	24T126			225
	251	24T127			225
	251	24T128			225
	252	24T129			225
	252		253		225
	252		253		225
	252		253		225
	252	24T133			225
	252		251, 257		225
	252		252, 257		225
	252		252, 257		99
	252	24T327			99
	252	24T328			99
	252	24T329			99
	252	24T330			99
	252		255		99
24R562	252	24T332	255	24Z131	9!

Page N	Part No.	Page No.	Part No.	Page No.	Part No.
00	104915	256	260122	99	047100
20			26C123 26C124	99 99	
28			26C169	19, 25	
55, 63, 112, 113, 114, 193, 27					
		113	260170	17	
				17 17, 19	
193, 201, 27			260172		
27			26C173	12, 19	
27			26C174	194	
201, 27			26C175	194	
19			26C183	113	
27			26C184	112	
27			26C185	33	
26, 63, 65, 9			26C186	33	
27			26C267	33	
59, 63, 6			26C268	33	
27			26C354	40	
13			26C355	40	
50, 51, 54, 55, 56, 63, 119, 120, 124, 12	109075		26C356	40	
126, 127, 128, 132, 133, 136, 27		24, 92	26C357	40	25C557
27		24, 92	26C358	95	
66, 67, 192, 204, 27			26C360	32, 33, 35, 37, 51, 89	
			26C361	32, 37, 39, 45, 89	
204, 28	109123	24, 55, 92	26C384	89	250905
28		24, 92	26C385	89	250915
	109125	25	26C399	89	25C916
28	109126	22	26C401	89	25C918
28	109127	25	26C409	89	250919
28	109128		100030	141	
28			100040	19. 25	25D121
28			100054	19, 25	
28			100081	89	
28			100206	89	
		-, -	100220	89	
			100380	19	
27			100385	15, 25	
			100451	90	
27			100474	90	
120, 126, 127, 128, 136, 27			100505		
			100615	15, 19, 23	
27			100737		
			100737	15, 19, 23	
125, 27			100834		
				15	
27			100835	15	
27			100837	15, 19, 25	
257, 27			100840	15	
27			100846	15	
27			100847	15	
27			100848	55, 92, 221	0511105
68, 131, 132, 133, 134, 135, 136, 27			100854	92	
123, 136, 27			100896	92, 221	
12		, - ,, - ,	10096059	92	
27			100961	92	
27			100962	92	
2			100970	50, 54, 92	
28			100971	92	
28			101008	92	
71, 75, 28			101009	92	
27			101012	16, 19	
27			101013	19	
6			101078	141	
			101180	13	
63, 167, 168, 192, 193, 27			101277	13	
6			101281	13	
63, 269, 270, 27			101283	13	
63, 27			101287	13	
193, 28			101297	13	
193, 28	110197	159	101312	13	25R981
123, 136, 28	110198		101339	268	
193, 28	110199	283	101340	242	26A140
193, 28		283	101376	242	26A141
15			101496	242	
15			101604	243	
			101605	243	
			102527	264	
			103347	264	
63, 64, 136, 167, 168, 192, 193, 27			103538		
			104266	264	
62 64 100 126 100 07		u. ua. 1a1. 1aa. //			८∪∪∪∪५
			104655	256	260121

Page I	Part No.	No.	Page I	Part No.	No.	Page N	Part No.
	155677	257	252	126380	271	123, 136, 197,	10234
2				126503			
1			251,				
2			251,				
2	156022	257	252,	126688	65		10314
2	156172	257	252,	127167	, 271	191,	10318
2	156173	257	252,	127173	277		10319
2	156296	.254			280		10326
2		.254		127217	158		10702
2		.254		127218			
46, 2		.254					
2	156789	.254			159		10706
116, 2		.254					
55, 123, 136, 2		.254					
131, 1		.254					
126, 2		.254					
2		.254					
55, 2		.254					
2			178,				
46, 112, 113, 114, 2			178,				
2			178,				
2			178,				
2						64, 139,	
2			163, 164,				
2			163, 164,				
2							
2							
2			165, 167, 168,				
2							
2							
2						156,	
2							
2			164,				
2			164, 165,				
221, 2		.176					
46, 2			165, 167, 168,				
66, 204, 2							
65, 77, 79, 137, 1					, 204	119, 120, 124, 125, 136,	
2			55, :		81		
2					, 192	71, 75, 145, 146,	
2			178,		2/3		
2			178,		, 1/6	167, 168,	
2			178,		2/6		
2			178,		262		
113, 2					2/1		
2							
2							
2					257		
113, 193, 2							
119, 120, 123, 124, 125, 136, 2							
			440 440 444				
2			112, 113, 114,			107 174 175	
2			112, 113, 114,			167, 174, 175,	
						167,	
221, 2						168,	
233, 238, 244, 2			46, 112, 116,				
						167, 168,	
1			33, 40, 46, 113, 116,				
1			15, 25				
1							
270.3						165 169	
270, 2			24 00 02			165, 168,	
67.5			24, 90, 92			168,	
67, 2						175,	
1			221				
64,			221,				
						250,	
			15			250,	
			132, 133, 134, 135, 136,			250,	
			68, 120, 126, 127, 128, 1	155494		250,	
			132, 133, 134, 135, 136, 3			251,	
		.283				251,	
			126, 127, 128, 136, 204,				
2			199,			250,	
	194347	.283		155653	, 256	250,	26377
	196220	.283				250	

Part No.	Page No.	Part No.	Page N	No.	Part No.	Page N
106/71	104	205582	1	150	220508	55, 66, 27
	158		1			27
						27
			131, 1			119, 124, 13
	50, 54, 59, 65, 77, 79, 120, 123, 126, 131,			201		119, 125, 127, 13
	132, 137, 141, 146, 148, 197, 205	206199	1	193	220969	26
200389		206264	2	277	221007	27
	158		122, 123, 1	197		27
	119, 120, 123, 124, 125, 136, 139, 154, 199			199		27
	155, 157		1			269, 27
	155			56		20
	158			.60		193, 201, 269, 27
			122, 123, 1			
	193, 271					
			56,			56, 125, 127, 133, 14
			65. 1			
			65, 1			
				68		
			1	193		
	222, 226		201, 2			
	222, 226		1			59, 63, 6
	222, 226		1			12
203524	222, 226	207948	1	157	222070	124, 125, 13
	222, 226			265		
203526	222, 226	208390	2	276	222072	120, 126, 127, 128, 13
203597	157	208393	2	276	222073	126, 12
203622	50, 54, 67, 80, 120, 125, 139	208434	2	283	222074	12
203650	64, 80, 119, 120, 124, 125, 139		193, 278, 2		222075	13
	124	208610	145, 146, 2	280		131, 132, 133, 134, 135, 13
203688		208611	2	280		19
203697	151, 156	208630	2	276		12
	151			64		19
203702	151			204		123, 13
	151		1			123, 13
	53, 54, 56, 58		2			19
	53, 54, 56, 58			280		
	53, 54, 55			80		53, 54, 5
	124, 125			63		58, 59, 6
	63, 68, 77		, -,	205 201		6
	64		2			
	67			157 280		63, 20
	157			26		222, 232, 23
				26		
	157			26		
						51, 54, 55, 62, 63, 64, 13
	126				000000	125, 13
	138		59, 63, 2			6
204134	119, 124		2		222629	10
204144	67, 197	217074	2	272	222645	10
204204	157	217359	2	204	222902	15
	53, 54, 56, 58		2			19
204264	56	218093	66, 2	280		13
	124					13
	126		62, 204, 2			26, 9
	65, 131, 132, 137		2			15
	126, 131, 132		222, 232, 2			131, 132, 133, 13
	126		222, 232, 2			10
	66, 280		2			269, 27
2045/4	77, 79, 80, 123, 125, 131, 132,		221, 2			269, 27
00.47.44	137, 141, 146, 148, 197, 205	∠18549	37, 44, 51, 55, 219, 220, 221, 2			138, 141, 14
	222, 226, 232	210550	230, 231, 232, 236, 237, 2			138, 141, 14
						127, 13
	157					
						191, 27
	277		266, 2			19
			200, 2			67, 27
			1			
	136		1			222, 23
	130, 131, 133		1			222, 23
	130, 131, 133		1			19
	66, 131, 132, 133, 134, 135, 136, 192, 280					19
	126, 131, 132, 133, 134, 133, 136, 132, 280					19
	120, 131, 132					50, 54, 27
			1			į
	100				=	

Page	Part No.	Page No.	Part No.	Page No.	Part No.
,	240685	26	236763	56, 60, 67	224570
		26		270	
		68, 77, 79		270, 273	
		77, 79, 148, 150		270	
		50, 54, 64	237075	270	
	241246	203	237129	270	224701
	241633	203	237130	270, 273	224702
			237131	76, 77	
65, ·		203		76, 77	
182, 187, 192, 194, 267, 268, 2		203		147, 148	
		203		147, 148	
139, 1		191		270	
119, 120, 123, 124, 125, 136, 139,		193		273	
139,		58, 59		198	
139, 1		63, 68		198	
		76, 77			
		279		139, 154	
		279		260, 261, 265, 266, 268	
			237866	147, 148	
		222, 232, 237		148	
				148	
				269	
		26, 55, 63, 68		125	
		77		126	
		244		126	
		58, 59		125	
132,		64		54	
132, 1		59, 63, 68		265	
		63, 66		80	
		66		80	225378
		64, 68	238370	80	225380
145, 1		86	238371	80	225384
		192, 194	238428	54	225640
	244680	65	238429	54	225642
	244681	65	238431	54	225728
	244682	65	238432	124	225773
	244844	65	238433	131	225781
		65	238434	59	
		199	238436	59	
		199	238438	124	225827
		199	238440	151	225844
134, <sup>-</sup>		68	238592	54	225852
		68		59	
		68	238595	80	225880
		68		151	225914
		260, 265	238866	54	
49, 50,	246775	86	238887	124	
118, <sup>-</sup>	246780	194	238899	126	226013
118, <sup>-</sup>	246781	193	238909	131	226018
	246903	26	238996	197	226269
	246904	26	239019	81	226289
	246906	265	239301	81	226290
	246907	265	239302	197	226342
118,		199		203	
		62		203	
		62		203	
		80		203	
		105		203	
	246916	80	239707	203	226945
	246917	130, 132, 133	239729	203	226947
	246946		239730	203	226948
		130	239731	203	
		94		203	226952
	247355	86	239829	203	226953
147, -		94	239876	124, 125, 153	233807
147, 148,	247450	122, 124	239877	153	233933
		122, 125, 126, 127, 128		197, 199	
		122, 126, 127, 128		266	
	247712	86	239949	198	235457
		86		63, 68	
-		86		63, 67, 192, 193, 204	
-		194		119, 120, 136	
-		136		158	
-		136, 199		278	
		87		278	
					236211
	247723	26, 63, 65	240417	278	
	247723 247724		240417 240429		236273

Part No.	Page No.	Part No.	Page No	. Part N	0.	Page No.
247760	07	260175	20	O LIDMOD.		
	87 71		20			220
	71		20			219 219
			20			38, 45, 51, 55, 221
			21			
	71		21			36, 37, 38, 43, 44, 45, 51, 55
	71		19			236
						174
			197			174
	71					174
	145		2			236
	145					174
	145		182, 184, 19			
	145					174
	145		182, 190, 19			230
	145		135, 13			230
247979	146	948393	128, 13	7 HSH15#		230
	146		13			230
247981	146	965129	13	0 HSHB7#		236
	49, 50, 51	CM155N	14			236
	50		14			236
	68		14			236
	280		14			230
248313	280		14			230
248324	68		14			230
	51		19			230
	51	D0B020	19	4 HSL56#.		230
248632	261, 265	D0B500	19	4 HSL65#.		230
	279	D0B525	19	4 HSLC8#		236
249440	19, 104	D0F005	19	4 HSLD5#		236
249615	120	D0F020	19	4 HSLE3#.		236
253848	256	D0F500	19	4 HSM3B#		230
253849	256	D0F525	19	4 HSM6D#		230
253850	256	D03005	19	4 HSM33#		230
253852	256	D03050	19	4 HSM65#		230
253853	256		19			236
	71, 75	D03255	19	4 HSMC8#		236
			19			236
	64		19			236
	15, 101		19			236
			19			236
	90, 103		182, 185, 191, 19			236
						145
			182, 189, 19			145
			23			145
	90, 99		23			145
	90		23			145
	15, 24, 92, 101		23 23			145 145
	93		23			145
	103		23			145
	99, 101		23			145
	34, 38, 39, 40, 41, 42, 44, 45, 51		23			145
			23			140
	40, 41, 42, 43, 44, 45, 86		23			
256719.	19, 25		23			
	87		23			
	87		23			
	134		23			
	19		22			
			22			
	86		21			
	208		21			
	206, 207		21			
260101	206, 207	HPH55#	21	9		
260102	206, 207	HPL2D#	22	0		
260104	206, 207	HPL5J#	21	9		
260105	207	HPL6D#	22	0		
	207	HPL6H#	21	9		
260108	207	HPL23#	21	9		
260109	207		22			
	208		21			
260111	208		22			
260112	208	HPL33#	21	9		
260113	208	HPL33B	22	1		
	208		21			
	209		21			
260125	209	HPM3B#	22	0		

#### **AMERICAS**

#### **MINNESOTA**

Worldwide Headquarters Graco Inc. 88-11th Avenue N.E. Minneapolis, MN 55413

#### MAILING ADDRESS

P.O. Box 1441

Minneapolis, MN 55440-1441 Tel: 800-275-5574 Fax: 612-623-6777

#### **EUROPE**

#### **BELGIUM**

Graco BVBA Industrieterrein-Oude Bunders Slakweidestraat 31 B-3630 Maasmechelen, Belgium

Tel: 32 89 770 700 Fax: 32 89 770 777

#### **ASIA PACIFIC**

#### AUSTRALIA

Graco Australia Pty Ltd. Suite 17, 2 Enterprise Drive Bundoora, Victoria 3083 Australia Tel: 61 3 9468 8500 Fax: 61 3 9468 8599

#### CHINA

Building 7, No.1-2 Wenshui Road 299, Jing'an District Shanghai 200436 P.R.China Tel: 86 21 649 50088 Fax: 86 21 649 50077

Graco Fluid Equipment (Shanghai) Co., Ltd.

#### **INDIA**

Graco Hong Kong Ltd. India Liaison Office Room 443, Level 4 Augusta Point, Golf Course Road Gurgaon, Haryana, India 122001 Tel: 91 124 435 4208 Fax: 91 124 435 4001

#### JAPAN

Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

#### KOREA

Graco Korea Inc. Shinhan Bank Building 4th Floor #1599 Gwanyang-Dong, Dongan-Ku, Anyang-si, Korea 431-060 Tel: 82 31 476 9400 Fax: 82 31 476 9801

©2021 Graco Inc. 303245 Rev. AI 2/21 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/patent or www.graco.com/trademarks.



## Graco's got you covered

**Facilities Worldwide for Global Support** 



#### **Quality First**

At Graco, we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your lubrication challenges.



#### **Global Reach**

Graco has facilities across the globe to provide you with the products and service *you* need, where *you* live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.



#### **Product Capabilities**

Graco has a broad range of products to provide solutions that meet your needs. Our products are engineered and tested to perform in the harshest environments so you can be certain your equipment is protected and working at peak performance.

## Contact us today!



Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.